


General Introduction

Typical Construction

Diaphragm Regulators

A pressure reducing regulator is positioned where the high pressure of a medium needs to be reduced and maintained to a lower and stable level. By turning the adjustment handle, the tension of range spring would be changed so as to control the outlet pressure of the regulator.



Component		Material/Specification
1	Hole Plug	ABS
2	Stem Nut	C36000/ASTM B16
3	Knob Handle	ABS
4	Stem	C36000/ASTM B16
5	O-ring	Buna-N
6	Bonnet	304 SS/ASTM A479 or Brass
7	Spring Button	304 SS/ASTM A276
8	Range Spring	Alloy
9	Diaphragm	Hastelloy
10	Spring Plate	Aluminium alloy
11	O-ring	Buna-N
12	Seal Ring	304 SS/ASTM A479
13	Seat Retainer	316L SS/ASTM A276
14	Seat	PCTFE/ASTM D1430
15	Lift Poppet	316L SS/ASTM A276
16	Poppet Spring	Alloy X-750
17	Poppet Damper	PTFE/ASTM D1710
18	Friction Sleeve	316L SS/ASTM A276
19	Body	316L SS/ASTM A479 or Brass
20	Filter	316L SS
21	Filter Ring	PTFE/ASTM D1710
22	Retaining Ring	316L SS

Features


- Convoluted diaphragm to provide accurate pressure adjustment
- Spring loaded
- 316L SS filter installed at inlet
- Some regulators are fitted with captured-vent, such as FCR-1S, FLR-3 and FLR-5 series and self-venting FCR-2 and FLR-2 series
- Users can connect the captured vent port so that the media can be contained or redirected if self-vented or the diaphragm accidentally breaks
- Optional sealing material for different gases and purity class
- Hastelloy diaphragm to provide higher burst pressure and corrosion resistance
- Low leak rates
 - Internal: $\leq 1 \times 10^{-7}$ mbar·l/s helium
 - External: $\leq 1 \times 10^{-9}$ mbar·l/s helium

A-04 Gas Control Equipment

When the regulator is in operation, the inlet pressure (F_i) plus the out pressure (F_o) should be equal to the downward force on the diaphragm by the compressed spring (F_s), namely $F_i+F_o=F_s$ to reach an equilibrium.

When the outlet pressure (F_o) is lower than the set pressure, the poppet would be pushed away from the seat by the excess downward force, allowing more high pressure gas to enter the chamber so as to increase the outlet pressure.



As soon as the outlet pressure (F_o) exceeds the set pressure, the excess upstream force shall lift the poppet back to the seat to limit high pressure gas entering, so as to reduce the outlet pressure.



Dual-stage Diaphragm Regulators

When the inlet pressure (P_i) decreases, the outlet pressure (P_o) shall increase. Even though the increase may not be significant, the dual-stage regulator would be a better option when more stable pressure required, and the upstream pressure fluctuates violently.


The function of a dual-stage regulator is similar to that of two single-stage regulators in series. The 1st-stage regulator reduces the inlet pressure to an intermediate level for the 2nd-stage regulator to adjust to a constant output, which at the most extent ensures the stability of the outlet pressure.



Piston Regulators

Although diaphragm regulators have many advantages such as precision, sealing effect, cleanliness and etc., in order to ensure sensitivity, the structural strength of the diaphragm regulators is low so as not being able to withstand high pressure. Therefore, it is recommended to utilize the piston regulators for high pressure applications.

A piston regulator has the same working principle as a diaphragm regulator. The key distinction is that the diaphragm is changed to a piston to satisfy the needs for high pressure applications. The inlet pressure of a piston regulator can reach 6000 psig. Its construction is simple and reliable with multiple options of O-rings to fulfill the various requirements of different media.



Series of Products

Cylinder Pressure Regulators (FCR)

Cylinder pressure regulators are designed to reduce the pressure of the cylinders to a lower level. The regulator is connected to the cylinder normally through a cylinder connection.

Line Pressure Regulators (FLR)

Line pressure regulators are used to further control the pressure in line.

Pressure Control Panels (FSR)

Pressure control panels are installed in the gas storage area (cylinder stock room or gas cabinet). They reduce cylinder or tank pressure to the desired line pressure for in-house use. Via the subsequent piping system, the gas will be guided to the point-of-use.

Changeover Systems (FDR)

There are manual changeover system and automatic changeover system.

Manual changeover system can connect with several independent gas sources at a time. When one gas source is depleted, it could be switched to another source quickly through a shutoff valve.


Automatic changeover system is installed onto gas pipelines which need continuous gas supply. It can connect with two independent gas sources at a time. When the gas source from one side is depleted, it can automatically switch to the gas source from the other side. Subsequently, replacing the exhausted gas source.

Point-of-use Panels (FPR)

Its function is to most precisely regulate the pressure and shut off at the point-of-use.

Products Practical Application

Gas Supply System



Selection Guide

Series																	
Pressure Reduction Design	Material																
		FCR-1	FCR-1S	FCR-2	FCR-1D	FLR-1	FLR-2	FLR-3	FSR-1	FSR-2	FDR-1	FDR-2	FDR-1L	FDR-1T	FPR-1	FPR-1S	BPR-1
Diaphragm	Brass	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	SS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Hastelloy		✓			✓	✓								✓			
Piston				✓			✓				✓	✓					✓
Preset													✓			✓	✓
Adjustable		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Single-Stage		✓	✓	✓		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Dual-Stage					✓									✓			
Cylinder		✓	✓	✓	✓												
In-Line						✓	✓	✓									
Control Panel									✓	✓	✓	✓	✓	✓			
Point-of-use															✓	✓	
Back Pressure																✓	✓
6000 psig				✓													
4500 psig		✓	✓	✓	✓		✓		✓	✓	✓	✓	✓	✓			
3000 psig		✓	✓		✓		✓	✓	✓	✓	✓	✓	✓	✓			
1500 psig						✓									✓	✓	
500 psig						✓		✓									
0~25 psig		✓	✓		✓	✓		✓	✓		✓				✓	✓	✓
0~50 psig		✓	✓		✓	✓		✓	✓		✓				✓	✓	✓
0~100 psig		✓	✓		✓	✓		✓	✓		✓				✓	✓	✓
0~150 psig		✓			✓			✓							✓		
0~200 psig		✓						✓								✓	
0~250 psig		✓				✓	✓	✓		✓		✓				✓	✓
0~300 psig																	✓
0~500 psig		✓						✓		✓		✓					✓
0~750 psig					✓			✓			✓						
0~1000 psig								✓									
0~1500 psig					✓						✓						
0~2500 psig						✓					✓						

See
page
A-50

Cylinder Pressure Regulators

FCR-1 Series General Diaphragm Regulators

Features

- Metal-to-metal seal to minimize external leak
- Convoluted diaphragm design to improve regulation precision and cycle life
- Applicable to corrosive or toxic gases
- With special cleaning and packaging, applicable to oxygen-enriched environments
- Adjustable relief pressure
- 20 µm filter installed at inlet




Technical Data

- Single-stage regulator
- Maximum inlet pressure: 3000 or 4500 psig
- Outlet pressure range: 0~25, 0~50, 0~100, 0~250 or 0~500 psig
- Material of the internal components:
 - Seat: PCTFE
 - Diaphragm: Hastelloy
 - Filter: 316L
- Temperature: -40°F~+165°F (-40°C~+74°C)
- Leak rates:
 - Internal: $\leq 1 \times 10^{-7}$ mbar·l/s helium
 - External: $\leq 1 \times 10^{-9}$ mbar·l/s helium
- Flow coefficient (Cv): 0.06
- Weight (regulator only): ≈ 1.98 lbs (0.9 kg)
- Body ports: 1/4" female NPT for inlet, outlet, gauge and relief valve


Model: FCR-16L-30-100-C330-B-B-00-R-P

Typical Flow Chart




Dimensions


Dimensions, in inches (millimeters), are for reference only.



Port Configurations



Part Number Description



Notes:

1. Most configurations are available.
 2. Before ordering, please read **Installation Instructions and Cautions** on A-77.
- Examples of part number:
- a. 2-port type (1 in, 1 out): FCR-16L-45-100-C580-00
 - b. 3-port type (1 in, 2 out): FCR-1SS-30-500-C330-B-00
 - c. 4-port type (2 in, 2 out): FCR-1B-45-250-00-B-B-34

Cylinder Pressure Regulators

FCR-1S Series Sensitive Diaphragm Regulators

Features

- Large diameter convoluted diaphragm to increase pressure sensitivity and minimize pressure drop
- Fitted with captured vent as standard
- 316L SS and Brass available for valve
- With special cleaning and packaging, applicable to oxygen-enriched environments
- Die spring for stable outlet pressure
- 20 µm filter installed at inlet




Model: FCR-1S6L-30-50-C580-B-B-00-R-P

Technical Data


- Single-stage regulator
- Maximum inlet pressure: 3000 or 4500 psig
- Outlet pressure range: 0~25, 0~50, 0~100, 0~150 or 0~200 psig
- Material of the internal components:
 - Seat: PCTFE
 - Diaphragm: 316L
 - Filter: 316L
- Temperature: -40°F~+165°F (-40°C~+74°C)
- Leak rates:
 - Internal: $\leq 1 \times 10^{-7}$ mbar·l/s helium
 - External: $\leq 1 \times 10^{-9}$ mbar·l/s helium
- Flow coefficient (Cv): 0.06
- Weight (regulator only): ≈ 2.87 lbs (1.3 kg)
- Body ports: 1/4" female NPT for inlet, outlet, gauge and relief valve

Typical Flow Chart




Dimensions


Dimensions, in inches (millimeters), are for reference only.



Port Configurations



Part Number Description



Notes:

1. Most configurations are available.
2. Before ordering, please read **Installation Instructions and Cautions** on A-77.

Examples of part number:

- a. 2-port type (1 in, 1 out): FCR-1S6L-45-25-C580-00
- b. 3-port type (1 in, 2 out): FCR-1SB-30-150-C330-B-00
- c. 4-port type (2 in, 2 out): FCR-1SB-45-200-00-00-00-00

Cylinder Pressure Regulators

FCR-2 Series High Pressure Piston Regulators

Features


- For high pressure applications
- Robust piston-sensed design to ensure safety and reliability
- 316L SS or Nickel-plated Brass body optional
- For non-corrosive gases (due to seal limit)
- With special cleaning and packaging, applicable to oxygen-enriched environments
- Venting model available
- 20 µm filter installed at inlet



Model: FCR-26L-45-750-DIN8-B-B-00-P-P


Technical Data

- Single-stage regulator
- Maximum inlet pressure: 4500 or 6000 psig
- Outlet pressure range: 0~750, 0~1500 or 0~2500 psig
- Material of the internal components:
 - Main Seat: PCTFE (PEEK for Venting Model)
 - Vent Seat: PCTFE
 - Piston: 316L
 - O-ring: Viton or Kalrez
 - Filter: 316L
- Temperature: -15°F~+165°F (-26°C~+74°C)
- Leak rates:
 - Internal: Bubble-tight
 - External: Bubble-tight
- Flow coefficient (Cv):
 - Without vent: 0.06
 - Vent: 0.1
- Weight (regulator only): ≈1.98 lbs (0.9 kg)
- Body ports: 1/4" female NPT for inlet, outlet and gauge




Construction Drawing with Venting Model

Typical Flow Chart




Dimensions

Dimensions, in inches (millimeters), are for reference only.



Port Configurations



Part Number Description

FCR - 2V Z 6L - 45 - 750 - DIN6 - M - M - 00 - P - P	
Vent Option	Inlet Pressure P1
Without	45 4500 psig
V With	60 6000 psig
O-ring Material	Connection 1
Viton	00 1/4" Female NPT
Z Kalrez	C --- CGA Number (USA)
Body Material	Connection 2
6L 316L SS	B With Gauge (psi/bar)
SS 316 SS	M With Gauge (psi/MPa)
B Brass (Nickel-plated)	P Plug
	Others refer to Connection 4
	Connection 3
	Same as Connection 2
	Connection 4
	00 1/4" Female NPT
	01 1/4" Male NPT
	10 1/4" Tube Fitting
	11 3/8" Tube Fitting
	20 6 mm Tube Fitting
	21 8 mm Tube Fitting
	30 Diaphragm Valve with 1/4" Female NPT
	31 Diaphragm Valve with 1/4" Male NPT
	32 Diaphragm Valve with 1/4" Tube Fitting
	33 Diaphragm Valve with 3/8" Tube Fitting
	34 Diaphragm Valve with 6 mm Tube Fitting
	35 Diaphragm Valve with 8 mm Tube Fitting
	Other connections are available upon request
	Connection 5
	P Plug
	00 1/4" Female NPT
	Connection 6
	Same as Connection 5

Notes:

1. Most configurations are available.
2. Before ordering, please read **Installation Instructions and Cautions** on A-77.

Examples of part number:

- a. 2-port type (1 in, 1 out): FCR-26L-45-1500-C580-00
- b. 3-port type (1 in, 2 out): FCR-2VB-45-750-C660-00-00
- c. 4-port type (2 in, 2 out): FCR-2VZSS-60-2500-00-B-B-32

Cylinder Pressure Regulators

FCR-1D Series Dual-stage Diaphragm Regulators


Features

- Compact design
- Dual-stage pressure reducing construction to provide accurate and stable pressure
- 20 µm filter installed at inlet
- With special cleaning and packaging, applicable to oxygen-enriched environments

Technical Data

- Maximum inlet pressure: 3000 or 4500 psig
- 1st stage outlet pressure range: 480~500 psig
2nd stage outlet pressure range: 0~25, 0~50, 0~100, 0~150, 0~250 psig
- Material of the internal components:
Seat: PCTFE
Diaphragm: Hastelloy
Filter: 316L
- Temperature: -40°F~+165°F (-40°C~+74°C)
- Leak rates:
Internal: $\leq 1 \times 10^{-7}$ mbar·l/s helium
External: $\leq 1 \times 10^{-9}$ mbar·l/s helium
- Flow coefficient (Cv): 0.05
- Weight (regulator only): ≈ 3.3 lbs (1.5 kg)
- Body ports: 1/4" female NPT for inlet, outlet, gauge and relief valve


Typical Flow Chart





Model: FCR-1D6L-30-100-C660-B-B-00-R-P

Dimensions


Dimensions, in inches (millimeters), are for reference only.



Port Configurations



Part Number Description



Notes:

1. Most configurations are available.
2. Before ordering, please read **Installation Instructions and Cautions** on A-77.

Examples of part number:

- a. 4-port type (2 in, 2 out): FCR-1DB-45-150-DIN1-B-B-30
- b. 6-port type (3 in, 3 out): FCR-1DSS-30-50-C580-B-B-00-R-P

Line Pressure Regulators

FLR-1 Series Compact Diaphragm Regulators

Features

- Similar to FCR-1 Series Regulators with larger orifice to provide higher flow capacity
- Three port configurations available
- 316L SS body for corrosive or toxic gases,
Nickel-plated Brass body for non-corrosive gases
- With special cleaning and packaging, applicable to
oxygen-enriched environments
- Configuration with filter installed at inlet as standard
- Panel mounted or installed with screw at the bottom




Model: FLR-16L-15-100-00-00-Z

Technical Data


- Single-stage regulator
- Maximum inlet pressure: 500 or 1500 psig
- Outlet pressure range: 0~25, 0~50, 0~100 or 0~250 psig
- Material of the internal components:
Seat: PCTFE
Diaphragm: Hastelloy
Filter: 316L
- Temperature: -40°F~+165°F (-40°C~+74°C)
- Leak rates:
Internal: $\leq 1 \times 10^{-7}$ mbar·l/s helium
External: $\leq 1 \times 10^{-9}$ mbar·l/s helium
- Flow coefficient (Cv): 0.14
- Weight (regulator only): ≈ 1.98 lbs (0.9 kg)
- Body ports: 1/4" female NPT for inlet, outlet and gauge

Typical Flow Chart




Dimensions

Dimensions, in inches (millimeters), are for reference only.



Port Configurations



Part Number Description

FLR - 16L	-	15	-	100	-	00	-	B	-	B	-	00	-	Z
Body Material		Inlet Pressure P1		Connection 1		Connection 2		Connection 3		Connection 4		Installation Type		
6L 316L SS		05 500 psig		00 1/4" Female NPT		B With Gauge (psi/bar)		Same as Connection 2		Same as Connection 1				
SS 316 SS		15 1500 psig		01 1/4" Male NPT		M With Gauge (psi/MPa)								
HC Hastelloy C-276				10 1/4" Tube Fitting		P Plug								
B Brass (Nickel-plated)				11 3/8" Tube Fitting		00 1/4" Female NPT								
				20 6 mm Tube Fitting		01 1/4" Male NPT								
				21 8 mm Tube Fitting		10 1/4" Tube Fitting								
		Outlet Pressure Range P2		Other connections are available upon request		11 3/8" Tube Fitting								
		25 0~25 psig				20 6 mm Tube Fitting								
		50 0~50 psig				21 8 mm Tube Fitting								
		100 0~100 psig				Other connections are available upon request								
		250 0~250 psig												

Notes:

1. Most configurations are available.
2. Before ordering, please read **Installation Instructions and Cautions** on A-77.

Examples of part number:

- a. 2-port type (1 in, 1 out): FLR-16L-15-25-00-00
- b. 3-port type (1 in, 2 out): FLR-16L-05-100-00-B-00

Line Pressure Regulators

FLR-2 Series Piston Regulators

Features

- Applicable to non-corrosive gases or low-viscosity liquids
- Easy to assemble and disassemble, convenient replacement of springs with different output ranges
- Robust piston-sensed design to provide safety and reliability
- With special cleaning and packaging, applicable to oxygen-enriched environments
- Three port configurations available
- Panel mounted or installed with screws at the bottom


Technical Data

- Single-stage regulator
- Maximum inlet pressure: 3000 or 4500 psig
- Outlet pressure range: 0~250, 0~500, 0~750 or 0~1000 psig
- Material of the internal components:
Main Seat: PCTFE (PEEK for Venting Model)
Vent Seat: PCTFE
Piston: 316L
O-ring: Viton or Kalrez
Filter: 316L
- Temperature: -15°F~+165°F (-26°C~+74°C)
- Leak rates:
Internal: Bubble-tight
External: Bubble-tight
- Flow coefficient (Cv):
Without vent: 0.06
Vent: 0.1
- Weight (regulator only): ≈1.98 lbs (0.9 kg)
- Body ports: 1/4" female NPT for inlet, outlet and gauge




Model: FLR-2SS-45-1000-00-00-Z

Typical Flow Chart




Dimensions

Dimensions, in inches (millimeters), are for reference only.



Port Configurations



Part Number Description

FLR - 2V	Z	6L	-	45	-	500	-	10	-	B	-	B	-	10	-	Z
Vent Option																
Without																
V With																
O-ring Material																
Viton																
Z Kalrez																
Body Material																
6L 316L SS																
SS 316 SS																
B Brass (Nickel-plated)																
Inlet Pressure P1																
30 3000 psig																
45 4500 psig																
Outlet Pressure Range P2																
250 0~250 psig																
500 0~500 psig																
750 0~750 psig																
1000 0~1000 psig																
Connection 1																
00 1/4" Female NPT																
01 1/4" Male NPT																
10 1/4" Tube Fitting																
11 3/8" Tube Fitting																
20 6 mm Tube Fitting																
21 8 mm Tube Fitting																
Other connections are available upon request																
Connection 2																
B With Gauge (psi/bar)																
M With Gauge (psi/MPa)																
P Plug																
00 1/4" Female NPT																
01 1/4" Male NPT																
10 1/4" Tube Fitting																
11 3/8" Tube Fitting																
20 6 mm Tube Fitting																
21 8 mm Tube Fitting																
Other connections are available upon request																
Connection 3																
Same as Connection 2																
Connection 4																
Same as Connection 1																
Installation Type																
Not Required																
Z Installed with One Panel Nut																
N Installed with Screws at the Bottom																

Notes:

1. Most configurations are available.
2. Before ordering, please read **Installation Instructions** and **Cautions** on A-77.

Examples of part number:

- a. 2-port type (1 in, 1 out): FLR-26L-30-250-00-00
- b. 3-port type (1 in, 2 out): ,FLR-2SS-45-1000-00-00-00

Other connections are available upon request

Line Pressure Regulators

FLR-3 Series Medium Flow Diaphragm Regulators

Features

- For high inlet pressure applications
- Balanced poppet
- With large orifice to minimize outlet pressure change when inlet pressure reduces
- Large diameter convoluted diaphragm to increase pressure sensitivity
- 316L SS body for corrosive or toxic gases,
Brass body for non-corrosive gases
- With special cleaning and packaging, applicable to oxygen-enriched environments
- Three port configurations available
- Panel mounted or installed with screws at the bottom
- Fitted with captured vent as standard




Technical Data

- Single-stage regulator
- Maximum inlet pressure: 500 or 3000 psig
- Outlet pressure range: 0~25, 0~50, 0~100, 0~150 or 0~200 psig
- Material of the internal components:
Seat: PCTFE
Diaphragm: Hastelloy
- Temperature: -40°F~+140°F (-40°C~+60°C)
- Leak rates:
Internal: Bubble-tight
External: $\leq 1 \times 10^{-9}$ mbar·l/s helium
- Flow coefficient (Cv): 1.0
- Weight (regulator only): ≈ 3.53 lbs (1.6 kg)
- Body ports: 1/2" female NPT for inlet, outlet
1/4" female NPT for gauge


Model: FLR-3SS-30-100-04-04-Z

Typical Flow Chart




Dimensions

Dimensions, in inches (millimeters), are for reference only.



Port Configurations



Part Number Description

FLR - 3B	-	30	-	100	-	04	-	B	-	B	-	04	-	Z
Body Material		Inlet Pressure P1		Connection 1		Connection 2		Connection 3		Connection 4				
6L 316L SS		05 500 psig		04 1/2" Female NPT		B With Gauge (psi/bar)		3 Ports Same as Connection 1		Same as Connection 1				
SS 316 SS		30 3000 psig		11 3/8" Tube Fitting		M With Gauge (psi/MPa)		4 Ports Same as Connection 2						
B Brass				12 1/2" Tube Fitting		P Plug								
		Outlet Pressure Range P2		22 10 mm Tube Fitting		00 1/4" Female NPT								
		25 0~25 psig		23 12 mm Tube Fitting		01 1/4" Male NPT								
		50 0~50 psig		Other connections are available upon request		10 1/4" Tube Fitting								
		100 0~100 psig				11 3/8" Tube Fitting								
		150 0~150 psig				20 6 mm Tube Fitting								
		200 0~200 psig				21 8 mm Tube Fitting								
Notes:														
1. Most configurations are available.														
2. Before ordering, please read Installation Instructions and Cautions on A-77.														
Examples of part number:														
a. 2-port type (1 in, 1 out): FLR-36L-30-150-04-04														
b. 3-port type (1 in, 2 out): FLR-3SS-05-200-04-00-04														

Line Pressure Regulators

FLR-5 Series High Flow Diaphragm Regulators

Features

- Suitable for low pressure and high flow applications
- Large diameter convoluted diaphragm to increase pressure sensitivity
- 316L SS body for corrosive gases, and Brass body for non-corrosive gases
- Fitted with captured vent as standard
- With special cleaning and packaging, applicable to oxygen-enriched environments
- Panel mounted or installed with screws at the bottom




Model: FLR-56L-05-100-04-04-Z

Technical Data


- Single-stage regulator
- Maximum inlet pressure: 500 psig
- Outlet pressure ranges: 0~15, 0~30, 0~75, 0~150 psig
- Material of the internal components:
 - Seat: PCTFE
 - Diaphragm: Hastelloy
- Temperature: -40°F~+165°F (-40°C~+74°C)
- Leak rates:
 - Internal: Bubble-tight
 - External: $\leq 1 \times 10^{-9}$ mbar.l/s helium
- Flow coefficient (Cv): 1.8
- Weight (regulator only): ≈ 5.95 lbs (2.7 Kg)
- Body ports: 3/4" female NPT for inlet, outlet,
1/4" female NPT for gauge

Typical Flow Chart




Dimensions



Dimensions, in inches (millimeters), are for reference only.



Panel Cut-out




Bottom Panel Cut-out



$2\times M5\times 0.8-6H$
The holes are compatible
with 10-32 mounting screws

Port Configurations



Part Number Description

FLR - 56L	-	05	-	150	-	05	-	B	-	B	-	05	-	Z			
Body Material		Inlet Pressure P1		Connection 1		Connection 2		Connection 3		Connection 4							
6L 316L SS		05 500 psig		05 3/4" Female NPT		B With Gauge (psi/bar)		Same as Connection 2		Same as Connection 1							
SS 316 SS				14 3/4" Tube Fitting		M With Gauge (psi/MPa)											
B Brass				16 1" Tube Fitting		P Plug											
Outlet Pressure Range P2				25 16 mm Tube Fitting		00 1/4" Female NPT											
15 0~15 psig				26 18 mm Tube Fitting		01 1/4" Male NPT											
30 0~30 psig				27 20 mm Tube Fitting		10 1/4" Tube Fitting											
75 0~75 psig				28 22 mm Tube Fitting		11 3/8" Tube Fitting											
150 0~150 psig				Other connections are available upon request													
Installation Type																	
Not Required																	
Z Installed with One Panel Nut																	
M Installed with Two Panel Nuts																	
N Installed with Screws at the Bottom																	

Notes:

1. Most configurations are available.
2. Before ordering, please read **Installation Instructions and Cautions** on A-77.

Examples of part number:

- a. 2-port type (1 in, 1 out): FLR-56L-05-15-05-05
- b. 3-port type (1 in, 2 out): FLR-56L-05-30-05-B-05
- c. 4-port type (2 in, 2 out): FLR-55S-05-150-05-B-B-05

Line Pressure Regulators

FBR-1 Series Miniature Piston Regulators

Features

- Applicable to non-corrosive gases or low-viscosity liquids
- Easy to assemble and disassemble, convenient replacement of springs with different output ranges
- Robust piston-sensed design to provide safety and reliability
- With special cleaning and packaging, applicable to oxygen-enriched environments





Model: FBR-1SS-60-220-00-00-00-00

Technical Data


- Media contact materials
 - Body: 316, 316L or Brass (Nickel-plated)
 - Seat: PCTFE, PEEK or Vespel
 - Piston: Aluminium Alloy
 - O-ring: Viton, Kalrez or Buna-N
 - Filter: 316L
- Operating conditions
 - Maximum rated inlet pressure: 6000 psig
 - Outlet pressure ranges: 0~80, 0~140, 0~220, 0~700, 0~1200, 0~1800 psig
 - Temperature: -15°F~+165°F (-26°C~+74°C)
- Functional performance
 - Test pressure: 150% of maximum rated pressure
 - Burst pressure: 300% of maximum rated pressure
 - Leak rates:
 - Internal: Bubble-tight
 - External: Bubble-tight
- Flow coefficient (Cv): 0.06
- Weight(regulator only): 0.93 lbs (0.4 kg)
- Body ports: 1/4" female NPT for inlet and outlet

Typical Flow Chart




Dimensions

Dimensions, in inches (millimeters), are for reference only.




Bottom Panel Cut-outs




Port Configurations



2-Port Type



Part Number Description



High Pressure Regulators

HPR-10 Series High Pressure Piston Regulators

Features

- 316 Stainless steel or brass body optional
- Robust piston sensed design
- Stable outlet pressure and easy tune
- 7 different outlet pressure ranges
- All pressure ranges can be vented to 0 psig
- Applicable to general gases or liquid
- Panel mountable


Technical Data

- Maximum inlet pressure:
Stainless: 10000 psig
Brass: 6000 psig
- Outlet pressure range: 10~500, 15~800, 15~1500, 30~2500,
50~4000, 60~6000 or 200~10000 psig
- Materials of the internal components:
Seat: PEEK
Piston: 316L
O-rings: Viton or NBR
Filter: 316L
- Temperature: -15°F~+165°F (-26°C~+74°C)
- Leak rates:
Internal: Bubble-tight
External: Bubble-tight
- Flow coefficient (Cv): 0.06
- Weight: ≈5.75 lbs (2.6 kg)
- Body ports: 1/4" female NPT for inlet, outlet and gauge




Model: HPR-10SSN-100-100-00-00-ZV

Flow Chart




Dimensions


Dimensions, in inches (millimeters), are for reference only.




Panel Cut-outs



Bottom View



Port Configurations



Part Number Description

HPR	-	10BN	-	60	-	10	-	12	-	B	-	B	-	00	-	ZV-F2
Body Material			Inlet Pressure P1			Connection 1		Connection 2		Connection 3		Panel Mount				
SS	316 SS		60	6000 psig		00	1/4" Female NPT	B	With Gauge (psi/bar)			Without				
B	Brass (Max. Inlet Pressure 6000 psig)		100	10000 psig		01	1/4" Male NPT	M	With Gauge (psi/MPa)			With				
O-ring Material			Outlet Pressure Range P2			10	1/4" Tube Fitting	P	Plug			Vent Option				
			5	10~500 psig		11	3/8" Tube Fitting	00	1/4" Female NPT			Without				
			8	15~800 psig		20	6 mm Tube Fitting	01	1/4" Male NPT			With				
			15	15~1500 psig		21	8 mm Tube Fitting	10	1/4" Tube Fitting			Product Technology Grade				
			25	30~2500 psig			Other connections are available upon request	11	3/8" Tube Fitting			General Purpose				
			40	50~4000 psig				20	6 mm Tube Fitting			Special Cleaning and Packaging				
			60	60~6000 psig				21	8 mm Tube Fitting							
			100	200~10000 psig												

Notes:

1. Most configurations are available but not everyone.
2. Venting port can not be blocked.
3. For liquid services, install the regulator with the venting port pointed vertically down.
4. Before ordering, please read **Installation Instructions and Cautions** on A-77.

Examples of part number:

- a. 2-port type (1 in, 1 out): HPR-10SS-60-40-00-00
- b. 3-port type (1 in, 2 out): HPR-10B-60-60-00-B-00
- c. 4-port type (2 in, 2 out): HPR-10SS-100-25-00-B-B-00

Line Pressure Regulators

HPL-06 Series High Pressure High Flow Regulators

Features

- For high pressure and high flow applications
- Large piston sensor gives excellent sensitivity
- Balanced valve design ensures stable downstream pressure
- Three port configurations available
- Panel mounting available
- With special cleaning and packaging, applicable to oxygen-enriched environments


Technical Data

- Maximum inlet pressure:
Stainless steel: 4500 psig
Brass: 3750 psig
- Outlet pressure ranges: 0~300, 0~600, 0~1000, 0~1500 psig
- Material of the main components:
Body: 316 SS or brass
Seat: PCTFE
Piston: 316L
O-rings: Viton or Kalrez
- Temperature: -15°F~+220°F (-26°C~+104°C)
- Leak rates:
Internal: Bubble-tight
External: Bubble-tight
- Flow coefficient (Cv): 2.0
- Weight (regulator only): ≈ 6.25 lbs (2.83 Kg)
- Body ports: 1/2" female NPT for inlet, outlet,
1/4" female NPT for gauge




Model: HPL-06SS-45-1000-04-04-Z

Typical Flow Chart




Dimensions


Dimensions, in inches (millimeters), are for reference only.




Panel Mounting




Panel Mounting Kit



Panel Cut-out



Port Configurations



Part Number Description

HPL - 06V	Z	6L	-	45	-	600	-	04	-	B	-	B	-	04	-	Z
Vent Option		Body Material		Inlet Pressure P1		Connection 1		Connection 2		Connection 3		Connection 4		Panel Mount		
Without		SS 316 SS		37 3750 psig		04 1/2" Female NPT		B With Gauge (psi/bar)		Same as Connection 2				Without		
V With		6L 316L SS		45 4500 psig		05 3/4" Female NPT		M With Gauge (psi/MPa)								
O-ring Material		Brass (Max. Inlet Pressure 3750 psig)		Outlet Pressure Range P2		14 3/4" Tube Fitting		P Plug								
Viton				300 0~300 psig		25 16 mm Tube Fitting		00 1/4" Female NPT								
Z Kalrez				600 0~600 psig		26 18 mm Tube Fitting		01 1/4" Male NPT								
				1000 0~1000 psig		Other connections are available upon request		10 1/4" Tube Fitting								
				1500 0~1500 psig				11 3/8" Tube Fitting								
								20 6 mm Tube Fitting								
								21 8 mm Tube Fitting								
								Other connections are available upon request								

Notes:

1. Most configurations are available.
2. Before ordering, please read **Installation Instructions and Cautions** on A-77.

Examples of part number:

- a. 2-Port type (1 in, 1 out): HPL-06B-37-600-04-04
- b. 3-Port type (1 in, 2 out): HPL-066L-45-1000-04-B-04
- c. 4-Port type (2 in, 2 out): HPL-06SS-45-1500-04-B-B-04

Pressure Control Panels

FSR-1 Series Pressure Control Panels for Single Cylinder

Features

- With a FCR-1 Series Regulator
- Maximum inlet pressure up to 4500 psig
- With vent valves to relieve residual pressure quickly, easy and safe to remove and replace gas source
- Anodized Aluminium panel
- Bracket mounting as standard


Technical Data

- Maximum inlet pressure: 3000 or 4500 psig
- Outlet pressure range: 0~25, 0~50, 0~100, 0~250 or 0~500 psig
- Material of the main components:
Seat: PCTFE (regulator and diaphragm valve)
Diaphragm: Hastelloy (regulator), Elgiloy (diaphragm valve)
Diaphragm valve body: 316L
Filter: 316L
- Temperature: -10°F~+150°F (-23°C~+65°C)
- Leak rates:
Internal: $\leq 1 \times 10^{-7}$ mbar·l/s helium
External: $\leq 1 \times 10^{-9}$ mbar·l/s helium
- Flow coefficient (regulator Cv): 0.06




Model: FSR-16L-45-100-00-B-B-00-R-P

Typical Flow Chart





Flow Schematic




Dimensions

Dimensions, in inches (millimeters), are for reference only.



Components Introduction



Part Number Description

FSR - 16L - 30 - 50	-	00	-	B	-	B	-	30	-	R	-	P
Body Material (Regulator)												
6L 316L SS												
SS 316 SS												
HC Hastelloy C-276												
B Brass (Nickel-plated)												
Inlet Pressure P1												
30 3000 psig												
45 4500 psig												
Outlet Pressure Range P2												
25 0~25 psig												
50 0~50 psig												
100 0~100 psig												
250 0~250 psig												
500 0~500 psig												
<i>Other connections are available upon request</i>												
Connection 1												
00 1/4" Female NPT												
01 1/4" Male NPT												
M With Gauge (psi/MPa)												
10 1/4" Tube Fitting												
11 3/8" Tube Fitting												
20 6 mm Tube Fitting												
21 8 mm Tube Fitting												
Connection 2												
00 1/4" Female NPT												
01 1/4" Male NPT												
10 1/4" Tube Fitting												
11 3/8" Tube Fitting												
20 6 mm Tube Fitting												
21 8 mm Tube Fitting												
Connection 3												
Same as Connection 2												
Connection 4												
00 1/4" Female NPT												
01 1/4" Male NPT												
10 1/4" Tube Fitting												
11 3/8" Tube Fitting												
20 6 mm Tube Fitting												
21 8 mm Tube Fitting												
Connection 5												
R Relief Valve												
P Plug												
00 1/4" Female NPT												
Connection 6												
Same as Connection 5												

Notes:

1. Most configurations are available.
2. Before ordering, please read **Installation Instructions and Cautions** on A-77.

Pressure Control Panels

FSR-2 Series High Pressure Control Panels for Single Cylinder

Features

- With a FCR-2 Series Regulator
- Applicable to non-corrosive gases or low-viscosity liquids
- With vent valves to relieve residual pressure quickly, easy and safe to remove and replace gas source
- Venting model available
- Anodized Aluminium panel
- Bracket mounting as standard




Model: FSR-2Z6L-45-750-00-B-B-00-P-P


Technical Data

- Maximum inlet pressure: 3000 or 4500 psig
- Outlet pressure range: 0~750, 0~1500 or 0~2500 psig
- Material of the main components:
 - Seat: PCTFE (regulator and diaphragm valve)
 - Piston: 316L
 - Diaphragm: Elgiloy (diaphragm valve)
 - Diaphragm valve body: 316L
 - O-ring: Viton or Kalrez
 - Filter: 316L
- Temperature: -10°F~+150°F (-23°C~+65°C)
- Leak rates:
 - Internal: Bubble-tight
 - External: Bubble-tight
- Flow coefficient (regulator Cv):
 - Without vent: 0.06
 - With vent: 0.1

Typical Flow Chart





Flow Schematic




Dimensions

Dimensions, in inches (millimeters), are for reference only.



Components Introduction



Part Number Description

FSR - 2V Z 6L - 30 - 1500 - 00 - B - B - 30 - P - P								
Vent Option		Inlet Pressure P1		Connection 1		Connection 2		Connection 4
Without		30 3000 psig		00 1/4" Female NPT		B With Gauge (psi/bar)		00 1/4" Female NPT
V With		45 4500 psig		01 1/4" Male NPT		M With Gauge (psi/MPa)		01 1/4" Male NPT
O-ring Material		Outlet Pressure Range P2		10 1/4" Tube Fitting		P Plug		10 1/4" Tube Fitting
Viton		750 0~750 psig		11 3/8" Tube Fitting		00 1/4" Female NPT		11 3/8" Tube Fitting
Z Kalrez		1500 0~1500 psig		20 6 mm Tube Fitting				20 6 mm Tube Fitting
Body Material (Regulator)		2500 0~2500 psig		21 8 mm Tube Fitting				21 8 mm Tube Fitting
6L 316L SS				Other connections are available upon request				30 Diaphragm Valve with 1/4" Female NPT
SS 316 SS								31 Diaphragm Valve with 1/4" Male NPT
B Brass (Nickel-plated)								32 Diaphragm Valve with 1/4" Tube Fitting
								33 Diaphragm Valve with 3/8" Tube Fitting
								34 Diaphragm Valve with 6 mm Tube Fitting
								35 Diaphragm Valve with 8 mm Tube Fitting
								Other connections are available upon request
Notes:								
1. Most configurations are available.								
2. Before ordering, please read Installation Instructions and Cautions on A-77.								

Changeover Systems

FDR-1 Series Manual Changeover System (up to 500 psig)

Features

- A small manual changeover system with a regulator similar to FCR-1 Series Regulators
- Connecting with two independent gas sources at a time, gas source selected through diaphragm valves
- Applicable to corrosive or toxic gases
- With vent valves to relieve residual pressure quickly, easy and safe to remove and replace gas source
- Anodized Aluminium panel




Model: FDR-16L-30-500-00-B-B-01-00-R


Technical Data

- Maximum inlet pressure: 3000 or 4500 psig
- Outlet pressure range: 0~25, 0~50, 0~100, 0~250 or 0~500 psig
- Material of the main components:
 - Seat: PCTFE (regulator and diaphragm valve)
 - Diaphragm: Hastelloy (regulator), Elgiloy (diaphragm valve)
 - Diaphragm valve body: 316L
 - O-ring: Viton
- Temperature: -10°F~+150°F (-23°C~+65°C)
- Leak rates:
 - Internal: $\leq 1 \times 10^{-7}$ mbar·l/s helium
 - External: $\leq 1 \times 10^{-9}$ mbar·l/s helium
- Flow coefficient (regulator Cv): 0.06

Typical Flow Chart





Flow Schematic




Dimensions

Dimensions, in inches (millimeters), are for reference only.



Components Introduction



Part Number Description

FDR - 16L - 30 - 250	- 00	- B	- B	- 01	- 00	- R
Body Material (Regulator)						
6L 316L SS	Connection 1	Connection 2	Connection 4	Connection 6		
SS 316 SS	00 1/4" Female NPT	B With Gauge (psi/bar)	00 1/4" Female NPT	R Relief Valve		
HC Hastelloy C-276	01 1/4" Male NPT	M With Gauge (psi/MPa)	01 1/4" Male NPT	P Plug		
B Brass (Nickel-plated)	10 1/4" Tube Fitting	P Plug	10 1/4" Tube Fitting	00 1/4" Female NPT		
	11 3/8" Tube Fitting	00 1/4" Female NPT	11 3/8" Tube Fitting	20 6 mm Tube Fitting		
	20 6 mm Tube Fitting		21 8 mm Tube Fitting	21 8 mm Tube Fitting		
	21 8 mm Tube Fitting			Other connections are available upon request		
Inlet Pressure P1		Connection 3		Connection 5		
30 3000 psig		Same as Connection 2		Same as Connection 1		
45 4500 psig						
Outlet Pressure Range P2						
25 0~25 psig						
50 0~50 psig						
100 0~100 psig						
250 0~250 psig						
500 0~500 psig						

Note: Before ordering, please read **Installation Instructions and Cautions** on A-77.

Changeover Systems

FDR-2 Series Manual Changeover System (up to 2500 psig)

Features

- A small manual changeover system with a regulator similar to FCR-2 Series Regulators
- Connecting with two independent gas sources at a time, gas sources switched through diaphragm valves
- Applicable to non-corrosive gases
- Venting model available
- Anodized Aluminium panel




Model: FDR-2VSS-45-2500-00-B-B-01-00


Technical Data

- Maximum inlet pressure: 3000 or 4500 psig
- Outlet pressure range: 0~750, 0~1500 or 0~2500 psig
- Material of the main components:
Seat: PCTFE (regulator and diaphragm valve)
Piston: 316L
Diaphragm: Elgiloy (diaphragm valve)
Diaphragm valve body: 316L
O-ring: Viton or Kalrez
Filter: 316L
- Temperature: -10°F~+150°F (-23°C~+65°C)
- Leak rates:
Internal: Bubble-tight
External: Bubble-tight
- Flow coefficient (regulator Cv):
Without vent: 0.06
Vent: 0.1

Typical Flow Chart





Flow Schematic




Dimensions

Dimensions, in inches (millimeters), are for reference only.



Components Introduction



Part Number Description

FDR - 2V Z 6L - 30 - 750 - 00 - B - B - 01 - 00

Vent Option	Inlet Pressure P1	Connection 1	Connection 2	Connection 4	Connection 5
Without	30 3000 psig	00 1/4" Female NPT	B With Gauge (psi/bar)	00 1/4" Female NPT	Same as Connection 1
V With	45 4500 psig	01 1/4" Male NPT	M With Gauge (psi/MPa)	01 1/4" Male NPT	
O-ring Material	Outlet Pressure Range P2	10 1/4" Tube Fitting	P Plug	10 1/4" Tube Fitting	
Viton	750 0~750 psig	11 3/8" Tube Fitting	00 1/4" Female NPT	11 3/8" Tube Fitting	
Z Kalrez	1500 0~1500 psig	20 6 mm Tube Fitting	20 6 mm Tube Fitting	20 6 mm Tube Fitting	
	2500 0~2500 psig	21 8 mm Tube Fitting	21 8 mm Tube Fitting	21 8 mm Tube Fitting	
Body Material (Regulator)		Other connections are available upon request	Other connections are available upon request	Other connections are available upon request	
6L 316L SS					
SS 316 SS					
B Brass (Nickel-plated)					

Note: Before ordering, please read **Installation Instructions and Cautions** on A-77.

Changeover Systems

FDR-1L Series Automatic Changeover System without Line Pressure Regulator

Features

- With 2 regulators similar to FCR-1 Series Regulators
- Anodized Aluminium box with clearly marked panel
- With vent valves to relieve residual pressure quickly, easy and safe to remove and replace gas source
- Automatic switching of gas source to ensure continuous gas supply
- Four fixed outlet pressure ranges available
- With special cleaning and packaging, applicable to oxygen-enriched environments




Model: FDR-1L6L-30-10B-00-00-00

Technical Data

- Maximum inlet pressure: 3000 or 4500 psig
- Outlet pressure range: 85~115, 135~165, 185~215 or 235~265 psig
- Material of the main components:
 - Seat: PCTFE (regulator and diaphragm valve)
 - Diaphragm: Hastelloy (regulator), Elgiloy (diaphragm valve)
 - Diaphragm valve body: 316L
- Temperature: -10°F~+150°F (-23°C~+65°C)
- Leak rates:
 - Internal: $\leq 1 \times 10^{-7}$ mbar·l/s helium
 - External: $\leq 1 \times 10^{-9}$ mbar·l/s helium
- Flow coefficient (regulator Cv): 0.06
- Weight: ≈ 12.1 lbs (5.5 kg)

Flow Schematic



Operation Overview

The FDR-1L Series Changeover System is mainly comprised of one adjustable outlet pressure regulator together with one fixed outlet pressure regulator.

When the 2 inlets are both open, the one side that the "IN SERVICE" arrow is pointing at by turning the handle would be the 1st source for gas supply.

Fig. 1 When the "In Service" arrow is pointing at side B, side B would be the gas source. At this time, the fixed outlet pressure of side B is higher than the set pressure of side A. Consequently, the diaphragm of side A regulator moves to enable the stem to close the regulator.




Fig. 1

Fig. 2 If side A is chosen as the gas source, the handle should be turned clockwise until the "IN SERVICE" arrow is pointing at side A. At this time, the set pressure of side A is higher than the fixed outlet pressure of side B. Consequently, the diaphragm of side B regulator moves to enable stem to close the regulator.




Fig. 2

When gas source of one side is depleted, gas source would automatically change to the other side.

Fig. 3 When "IN SERVICE" arrow is pointing at side B, but gas source of side B is depleted, its outlet pressure shall decrease to be lower than the set pressure of side A. By the force of spring, side A regulator will be opened to begin gas supply.

Before replacing new gas source of side B, the diaphragm valve should be turned off. Otherwise, gas from side A will flow back into side B. Then open the vent valve to exhaust the remaining pressure.

After the replacement, if the "IN SERVICE" arrow still points at side B, side B would be the gas source. If the arrow is turned towards side A, side A would thus be the gas source.






Fig. 3

Dimensions

Dimensions, in inches (millimeters), are for reference only.

The holes are compatible with 4x1/4" mounting screws



Part Number Description

FDR - 1L6L	-	30	-	20	-	B	-	10	-	00	-	00
Body Material (Regulator)	Inlet Pressure P1		Outlet Pressure Range P2		Gauge Scale		Inlet A		Inlet B		Outlet	
6L 316L SS	30 3000 psig		10 85~115 psig		B psi/bar		00 1/4" Female NPT		Same as Inlet A		Same as Inlet A	
SS 316 SS	45 4500 psig		15 135~165 psig		M psi/MPa		01 1/4" Male NPT					
HC Hastelloy C-276			20 185~215 psig				10 1/4" Tube Fitting					
B Brass (Nickel-plated)			25 235~265 psig				11 3/8" Tube Fitting					
							20 6 mm Tube Fitting					
							21 8 mm Tube Fitting					
							Other connections are available upon request					

Note: Before ordering, please read **Installation Instructions and Cautions** on A-77.

Changeover Systems

FDR-1T Series Automatic Changeover System with Line Pressure Regulator


Features

- With a FCR-1 Series Regulator and a FLR-1 Series Regulator to enable outlet pressure adjustment
- Anodized Aluminium box with clearly marked panel
- With vent valves to relieve residual pressure quickly, easy and safe to remove and replace gas source
- Automatic switching of gas source to ensure continuous gas supply
- With special cleaning and packaging, applicable to oxygen-enriched environments

Technical Data

- Maximum inlet pressure: 3000 or 4500 psig
- Outlet pressure range: 0~25, 0~50, 0~100 or 0~150 psig
- Material of the main components:
 - Seat: PCTFE (regulator and diaphragm valve)
 - Diaphragm: Hastelloy (regulator), Elgiloy (diaphragm valve)
 - Diaphragm valve body: 316L
- Temperature: -10°F~+150°F (-23°C~+65°C)
- Leak rates:
 - Internal: $\leq 1 \times 10^{-7}$ mbar·l/s helium
 - External: $\leq 1 \times 10^{-9}$ mbar·l/s helium
- Flow coefficient (regulator Cv): 0.05
- Weight: ≈ 19.6 lbs (8.9 kg)

Flow Schematic



Model: FDR-1T6L-45-150B-00-00-00

Operation Overview

The FDR-1T Series Changeover System is mainly comprised of one adjustable outlet pressure regulator and one fixed outlet pressure regulator, together with a line pressure regulator on the outlet port.

When the 2 inlets are both open, the one side that the "IN SERVICE" arrow is pointing at by turning the handle would be the 1st source for gas supply.

Fig. 1 When the "In Service" arrow is pointing at side B, side B would be the gas source. At this time, the fixed outlet pressure of side B is higher than the set pressure of side A. Consequently, the diaphragm of side A regulator moves to enable the stem to close the regulator.




Fig. 1

Fig. 2 If side A is chosen as the gas source, the handle should be turned clockwise until the "IN SERVICE" arrow is pointing at side A. At this time, the set pressure of side A is higher than the fixed outlet pressure of side B. Consequently, the diaphragm of side B regulator moves to enable the stem to close the regulator.




Fig. 2

When gas source of one side is depleted, gas source would automatically change to the other side.

Fig. 3 When "IN SERVICE" arrow is pointing at side B, but gas source of side B is depleted, its outlet pressure shall decrease to be lower than the set pressure of side A. By the force of spring, side A regulator will be opened to begin gas supply.

Before replacing new gas source of side B, the diaphragm valve should be turned off. Otherwise, gas from side A will flow back into side B. Then open the vent valve to exhaust the remaining pressure.

After the replacement, if the "IN SERVICE" arrow still points at side B, side B would be the gas source. If the arrow is turned towards side A, side A would thus be the gas source.





Fig. 3

Dimensions

Dimensions, in inches (millimeters), are for reference only.



Part Number Description

FDR - 1T6L	-	30	-	25	-	B	-	10	-	00	-	00
Body Material (Regulator)	Inlet Pressure P1		Outlet Pressure Range P2		Gauge Scale		Inlet A		Inlet B		Outlet	
6L 316L SS	30 3000 psig		25 0~25 psig		B psi/bar		00 1/4" Female NPT					
SS 316 SS	45 4500 psig		50 0~50 psig		M psi/MPa		01 1/4" Male NPT					
HC Hastelloy C-276			100 0~100 psig				10 1/4" Tube Fitting					
B Brass (Nickel-plated)			150 0~150 psig				11 3/8" Tube Fitting					
							Other connections are available upon request					

Note: Before ordering, please read **Installation Instructions and Cautions** on A-77.

Point-of-use Panels

FPR-1 Series Compact Regulators for Low Pressure

Features

- With a FLR-1 Series Regulator
- With metal diaphragm regulators
- Shutoff valves with window to visually indicate open and closed states
- Anodized Aluminium panel, easy to install
- Regulator body of 316L SS or Brass optional
- Three configurations available




Technical Data

- Maximum inlet pressure: 1500 psig
- Outlet pressure range: 0~25, 0~50, 0~100, 0~250 or 0~500 psig
- Material of the main components:
Seat: PCTFE (regulator and diaphragm valve)
Diaphragm: Hastelloy (regulator), Elgiloy (diaphragm valve)
Diaphragm valve body: 316L
Filter: 316L
- Temperature: -10°F~+150°F (-23°C~+65°C)
- Leak rates:
Internal: $\leq 1 \times 10^{-7}$ mbar·l/s helium
External: $\leq 1 \times 10^{-9}$ mbar·l/s helium
- Flow coefficient (regulator Cv): 0.14

Model: FPR-1U6L-15-50-11-B-11


Typical Flow Chart




Dimensions

Dimensions, in inches (millimeters), are for reference only.


Single-outlet



Dual-outlet



Triple-outlet



Components Introduction



Part Number Description

FPR - 1C 6L - 15 - 100 - 10 - M - 10 - 00 - 00

Oulet Option	Inlet Pressure P1	Connection 1	Connection 2	Connection 3	Connection 4
U Single-outlet	15 1500 psig	00 1/4" Female NPT	B With Gauge (psi/bar)	00 1/4" Female NPT	Same as Connection 1
T Dual-outlet		01 1/4" Male NPT	M With Gauge (psi/MPa)	01 1/4" Male NPT	
C Triple-outlet		10 1/4" Tube Fitting	P Plug	10 1/4" Tube Fitting	
Body Material (Regulator)	Outlet Pressure Range P2	11 3/8" Tube Fitting	00 1/4" Female NPT	11 3/8" Tube Fitting	Connection 5
6L 316L SS	25 0~25 psig	20 6 mm Tube Fitting		20 6 mm Tube Fitting	Same as Connection 1
SS 316 SS	50 0~50 psig	21 8 mm Tube Fitting		21 8 mm Tube Fitting	
HC Hastelloy C-276	100 0~100 psig	Other connections are available upon request			
B Brass (Nickel-plated)	250 0~250 psig				
	500 0~500 psig				

Note: Before ordering, please read **Installation Instructions and Cautions** on A-77.

Examples of part number:

- a. 2-port type (1 in, 1 out): FPR-1U6L-15-50-11-B-11
- b. 3-port type (1 in, 2 out): FPR-1TSS-15-100-00-B-00-00

Point-of-use Panels

FPR-1S Series Sensitive Regulators for Low Pressure

Features

- With a FCR-1S Series Regulator of large diameter metal diaphragm to provide accurate pressure control
- Shutoff valves with window to visually indicate open and closed states
- Anodized Aluminium panel, easy to install
- Three port configurations available


Technical Data

- Maximum inlet pressure: 1500 psig
- Outlet pressure range: 0~25, 0~50, 0~100, 0~150 or 0~200 psig
- Material of the main components:
Seat: PCTFE (regulator and diaphragm valve)
Diaphragm: 316L (regulator), Elgiloy (diaphragm valve)
Diaphragm valve body: 316L
Filter: 316L
- Temperature: -10°F~+150°F (-23°C~+65°C)
- Leak rates:
Internal: $\leq 1 \times 10^{-7}$ mbar·l/s helium
External: $\leq 1 \times 10^{-9}$ mbar·l/s helium
- Flow coefficient (regulator Cv): 0.06



Model: FPR-1SUSS-15-50-10-B-10


Typical Flow Chart




Dimensions

Dimensions, in inches (millimeters), are for reference only.


Single-outlet



Dual-outlet



Triple-outlet



Components Introduction



Part Number Description

FPR - 1SC 6L - 15 - 100 - 10 - M - 10 - 00 - 00

Outlet Option

U	Single-outlet
T	Dual-outlet
C	Triple-outlet

Inlet Pressure P1

15	1500 psig
25	0~25 psig
50	0~50 psig
100	0~100 psig
150	0~150 psig
200	0~200 psig

Connection 1

00	1/4" Female NPT
01	1/4" Male NPT
10	1/4" Tube Fitting
11	3/8" Tube Fitting
20	6 mm Tube Fitting
21	8 mm Tube Fitting

Other connections are available upon request

Connection 2

B	With Gauge (psi/bar)
M	With Gauge (psi/MPa)
P	Plug
00	1/4" Female NPT

Connection 3

00	1/4" Female NPT
01	1/4" Male NPT
10	1/4" Tube Fitting
11	3/8" Tube Fitting
20	6 mm Tube Fitting
21	8 mm Tube Fitting

Other connections are available upon request

Connection 4

Same as Connection 1
Connection 5

Same as Connection 1

Body Material (Regulator)

6L	316L SS
SS	316 SS
B	Brass

Note: Before ordering, please read **Installation Instructions and Cautions** on A-77.

Examples of part number:

- a. 2-port type (1 in, 1 out): FPR-1SU6L-15-25-00-B-20
- b. 3-port type (1 in, 2 out): FPR-1STB-15-200-10-M-10-10

Back Pressure Regulators

BPR-1 Series Back Pressure Diaphragm Regulators

Features

- Metal-to-metal seal with convoluted diaphragm
- Close pressure differential between crack and reseat
- Panel mounting available


Technical Data

- Maximum control pressure: 250 psig
- Pressure control range: 0~25, 0~50, 0~100 or 0~250 psig
- Material of the main components:
Seat: PCTFE
Diaphragm: Hastelloy
- Temperature: -40°F~+140°F (-40°C~+60°C)
- Leak rates:
Internal: Bubble-tight
External: $\leqslant 1 \times 10^{-9}$ mbar · l/s helium
- Flow coefficient (Cv): 0.3
- Weight: ≈ 1.98 lbs (0.9 kg)
- Body ports: 1/4" female NPT for inlet, outlet and gauge




Model: BPR-16L-250-00-00-Z

Typical Flow Chart




Dimensions


Dimensions, in inches (millimeters), are for reference only.





Bottom View



Bottom Panel Cut-out




Port Configurations



Typical Application

When the system pressure is lower than the set pressure, the diaphragm obstructs the flow by the force of spring. When the system pressure is higher than the set pressure, the diaphragm compresses the inner spring to connect the flow so as to allow the fluid to pass through the back pressure regulator to keep the pressure of the Storage Vessel stable.



Part Number Description

BPR - 16L - 100 - 10 - M - 11 - Z

Body Material	Control Pressure Range P	Connection 1	Connection 2	Connection 3	Installation Type
6L 316L SS	25 0~25 psig	00 1/4" Female NPT	B With Gauge (psi/bar)	Same as Connection 1	Not Required
SS 316 SS	50 0~50 psig	01 1/4" Male NPT	M With Gauge (psi/MPa)		Z Installed with One Panel Nut
B Brass (Nickel-plated)	100 0~100 psig	10 1/4" Tube Fitting	P Plug		N Installed with Screws at the Bottom
	250 0~250 psig	11 3/8" Tube Fitting	00 1/4" Female NPT		
		20 6 mm Tube Fitting	01 1/4" Male NPT		
		21 8 mm Tube Fitting	10 1/4" Tube Fitting		
		Other connections are available upon request	Other connections are available upon request		

Note: Before ordering, please read **Installation Instructions and Cautions** on A-77.

Examples of part number:

a. 2-port type (1 in, 1 out): BPR-16L-25-00-00

FITOK

Back Pressure Regulators

BPR-2 Series Back Pressure Piston Regulators

Features

- Durable piston-sensed design
- Bubble-tight shutoff at all reseating pressure
- Low operating torque
- Panel mounting available
- With special cleaning and packaging, applicable to oxygen-enriched environments




Model: BPR-26LZ-300-00-00-Z

Technical Data





- Maximum control pressure: 1000 psig
- Pressure control range: 10~300, 10~500 or 10~1000 psig
- Material of the main components:
Seat: PCTFE
Piston: 316L
O-rings: Viton or Kalrez
- Temperature: -15°F~+165°F (-26°C~+74°C)
- Leak rates:
Internal: Bubble-tight
External: Bubble-tight
- Flow coefficient (Cv): 0.3
- Weight: ≈1.98 lbs (0.9 kg)
- Body ports: 1/4" female NPT for inlet, outlet and gauge

Typical Flow Chart




Dimensions

Dimensions, in inches (millimeters), are for reference only.




Port Configurations



Typical Application

BPR-2 Series Back Pressure Regulators maintain the required pipeline pressure to ensure the Pump to output fluid stably when system pressure fluctuates.



Part Number Description

BPR – 26L	Z –	300	–	10	–	M	–	11	–	Z
Body Material		Control Pressure Range P		Connection 1		Connection 2		Connection 3		Installation Type
6L 316L SS		300 10~300 psig		00 1/4" Female NPT		B With Gauge (psi/bar)		Same as Connection 1		Not Required
SS 316 SS		500 10~500 psig		01 1/4" Male NPT		M With Gauge (psi/MPa)			Z	Installed with One Panel Nut
B Brass (Nickel-plated)		1000 10~1000 psig		10 1/4" Tube Fitting		P Plug			N	Installed with Screws at the Bottom
O-ring Material				11 3/8" Tube Fitting		00 1/4" Female NPT				
Viton				20 6 mm Tube Fitting		01 1/4" Male NPT				
Z Kalrez				21 8 mm Tube Fitting		10 1/4" Tube Fitting				
						Other connections are available upon request				

Note: Before ordering, please read **Installation Instructions and Cautions** on A-77.

Examples of part number:

a. 2-port type (1 in, 1 out): BPR-2SS-500-00-00

Back Pressure Regulators

BPR-3 Series Back Pressure Piston Regulators

Features

- Control of back-pressure up to 10000 psig for gas or liquid application
- Safe and reliable piston sensing
- 7 pressure control ranges
- Panel mounting available
- Special cleaning and packaging available for application in oxygen-enriched environments




Model: BPR-3SS-40-00-00-Z

Technical Data


- Maximum control pressure:
Stainless steel: 10000 psig
Brass: 6000 psig
- Pressure control ranges: 5~500, 5~800, 10~1500, 15~2500,
25~4000, 50~6000, 200~10000 psig
- Material of the main components:
Body: 316 SS or brass
Seat: PEEK
Piston: 316L
O-rings: Viton or Kalrez
- Temperature: -15°F~+165°F (-26°C~+74°C)
- Leak rates:
Internal: Bubble-tight
External: Bubble-tight
- Flow coefficient (Cv): 0.25
- Weight(regulator): ≈5.7 lbs (2.6 Kg)
- Body ports: 1/4" female NPT for inlet, outlet, and gauge

Typical Flow Chart




Dimensions


Dimensions, in inches (millimeters), are for reference only.




Bottom View



Panel Cut-out



Port Configurations



Part Number Description

BPR - 3B	Z	-	15	-	00	-	B	-	00	-	00	-	Z	-	F2
Body Material			Pressure Control Range P		Connection 1		Connection 2		Connection 3		Connection 4		Panel Mount		
SS 316 SS			5 5~500 psig		00 1/4" Female NPT		B With Gauge (psi/bar)		Same as Connection 1		Same as Connection 1		Without		
6L 316L SS			8 5~800 psig		01 1/4" Male NPT		M With Gauge (psi/MPa)						z With		
B Brass (Max. Control Pressure 6000 psig)			15 10~1500 psig		10 1/4" Tube Fitting		P Plug								
			25 15~2500 psig		11 3/8"Tube Fitting		00 1/4" Female NPT								
			40 25~4000 psig		60 50~6000 psig		01 1/4" Male NPT								
			100 200~10000 psig				10 1/4" Tube Fitting								
O-ring Material							11 3/8" Tube Fitting						Product Technology Grade		
Viton							20 6 mm Tube Fitting						General Purpose		
Z Kalrez							21 8 mm Tube Fitting						F2 Special Cleaning and Packaging		
							Other connections are available upon request								

Note: Before ordering, please read **Installation Instructions and Cautions** on A-77.

Examples of part number:

- a. 2-Port type (1 in, 1 out): BPR-3B-25-00-00
- b. 3-Port type (2 in, 1 out): BPR-3B-40-00-M-00
- c. 4-Port type (3 in, 1 out): BPR-3B-60-00-M-00-00

Purge Assemblies

FPV-1 Series

Technical Data

- Maximum working pressure: 4500 psig
- Material of the main components:
Seat: PCTFE (diaphragm valve)
Diaphragm: Elgiloy (diaphragm valve)
- Temperature: -10°F~+150°F (-23°C~+65°C)
- Leak rates:
Internal: $\leq 1 \times 10^{-9}$ mbar·l/s helium
External: $\leq 1 \times 10^{-9}$ mbar·l/s helium
- Minimum orifice: $\phi 0.13"$ (3.2 mm)

Product Types

- Straight Purge Assemblies

Consisting of a diaphragm valve and a check valve (see Fig. 1-1).

Connecting the auxiliary inlet port (see Fig. 1-2) of the regulator or in between the regulator and the cylinder (see Fig. 1-3) to allow the corrosive or toxic gas to be vented through to a safe location.




Fig. 1-1




Fig. 1-2




Fig. 1-3

- Tee Purge Assemblies

Consisting of a diaphragm valve, check valve, tee, and cylinder connections (see Fig. 2-1).

Connecting the cylinder with the regulator. Before installing a new cylinder, open the diaphragm valve, and the remaining gas is vented safely; or after a new cylinder is installed, close the regulator and open the diaphragm valve, enabling the process gas inside the cylinder to purge the atmospheric contamination between the cylinder and the regulator (see Fig. 2-2).



Fig. 2-1




Fig. 2-2

Cross Purge Assemblies

Consisting of a tee purge assembly and two additional diaphragm valves (see Fig. 3-1).

Except for process gas, purging is also made possible with inert gas from outside (see Fig. 3-2). The steps are as follows:
Before installing a new cylinder, close the diaphragm valve beside the regulator, and open the shutoff diaphragm valve on the vent line to release the residual pressure.

After installing a new cylinder, open the diaphragm valve on the bottom, allowing the inert gas from outside to purge the atmospheric contaminations between the cylinder and the diaphragm valve.




Fig. 3-1




Fig. 3-2

Part Number Description

FPV - 1C 6L - DIN1 - 00 - 00 - 00

Product Type	Body Material	Inlet Port	Vent Port	Outlet Port	Purge Inlet
S Straight Purge Assemblies	6L 316L SS	00 1/4" Female NPT	00 1/4" Female NPT	Same as Vent Port	Same as Vent Port
T Tee Purge Assemblies	SS 316 SS	01 1/4" Male NPT	01 1/4" Male NPT	Same as Vent Port	Same as Vent Port
C Cross Purge Assemblies		C--- CGA Number (USA)	10 1/4" Tube Fitting		
		DIN_ DIN Number (Germany)	20 6 mm Tube Fitting		
			21 8 mm Tube Fitting		
			Other connections are available upon request		
		Refer to page B-28 for cylinder connections based on specific gas type. Cylinder connections compliant to other standards are available upon request. Please contact FITOK Group for details.			

Diaphragm Valves

DS Series


Features

- Reduced inner capacity
- Packless diaphragm seal design for high purity
- Minimized number of components
- Manual and pneumatic actuators available
- Aluminum piston to increase operation speed



Technical Data

- Maximum working pressure: 4500 psig
- Material of the internal components:
Seat: PCTFE or Vespel
Diaphragm: Elgiloy
- Temperature:
PCTFE: -10°F~+150°F (-23°C~+65°C)
Vespel: -10°F~+250°F (-23°C~+121°C)
- Leak rates:
Internal: $\leq 1 \times 10^{-9}$ mbar·l/s helium
External: $\leq 1 \times 10^{-9}$ mbar·l/s helium
- Flow coefficient (Cv): 0.17



Part Number Description

DS	6L	-	NS	4	-	FNS	4	-	R	V	F2
Body Material			Inlet Type			Inlet Size			Actuator Type		Technology Grade
6LW	316L VIM-VAR		TB	Fractional Tube Butt Weld		4 1/4"			R		General Purpose
6L	316L SS		MTB	Metric Tube Butt Weld		6 6 mm or 3/8"			C		Special Cleaning and Packaging
SS	316 SS		FR	Male FR Fitting		8 8 mm		Specify in the same way as inlet size	O		Ultra High Purity
			FFR	Female FR Fitting						Seat	
			FL	Fractional Tube Fitting						PCTFE	
			ML	Metric Tube Fitting						V	Vespel
			NS	Male NPT							
			FNS	Female NPT							

Ball Valves

BO Series


Features

- ◎ One-piece body and one-piece ball stem
- ◎ No dead zone, such as in the area between the ball and valve chamber
- ◎ In-line inspection and repair with top entry design
- ◎ Thermal cycle performance improved and wear compensated by live-loaded design
- ◎ Multiple connections available
- ◎ Pneumatic and electric actuators available



Technical Data

- ◎ Maximum working pressure: 3000 psig (207 bar)
- ◎ Temperature: -65°F to 300°F (-54°C to 148°C)
- ◎ Seat material: PTFE



Part Number Description

BO	6L	-	NS	4 - FNS	4 - H03	-	U A	-	F2
Body Material		Connection 1 Type		Connection 2 Type		Orifice Size		Flow Pattern	
6L 316L SS		FNS Female NPT		Same as Connection 1		02 0.09" (2.4 mm)		Straight	
SS 316 SS		NS Male NPT		Specify in the same way as inlet type		03 0.13" (3.2 mm)			
B Brass		FR Male FR Fitting				05 0.19" (4.8 mm)		A Angle	
		FL Fractional Tube Fitting				07 0.28" (7.1 mm)			
		ML Metric Tube Fitting		Connection 2 Size		10 0.41" (10.3 mm)			
				Same as Connection 1				Handle	
				Specify in the same way as inlet size				Black Nylon	
			Connection 1 Size					Red Nylon	
			4 1/4"					Green Nylon	
			6 6 mm or 3/8"					Blue Nylon	
			8 8 mm or 1/2"					Black Aluminium	
				Seat Material					
				PTFE					
				H UHMWPE					
				A PFA					

Cylinder Connections



CGA DISS Series

B-16

CGA Series

B-20

DIN Series

B-27

Gas Connection Assignment Table

B-28

Features


- 100% visual inspection of critical surfaces
- Diverse material and configurations available
- Silver-plated nut threads to reduce installation torque
- Every fitting marked with size, material and heat number
- Cleaned and packaged for Oxygen and Ultra High Purity Service available
- Customized solutions available

Material

Series	Component	Material	Designator
CGA DISS	Nipples	316L SS	6L
	Nuts	304 SS	S4
	Gaskets	Nickel 200	NI
		PCTFE	K
		Aluminum	AL
	Plugs	316L SS	6L
	Adapters	316L SS	6L
CGA DIN	Caps	316L SS	6L
	Nipples	316L SS	6L
	Nuts	304 SS	S4
	Gaskets	PTFE	T
		PCTFE	K
	Plugs, Caps	316L SS	6L
	Adapters	316L SS	6L

Notes:

1. Nickel gasket heat treated; surface hardness < HB 100
2. 316L SS in compliance with SEMI F20



Ordering information


- Add material designator as a prefix to the basic ordering number to get the complete ordering number.
Example: 6L-C634-L-FR4
- CGA, DIN Series
PTFE is standard material for gasket. If PCTFE is required, please add a suffix of "-k" to the ordering number.
Example: 6L-C350-NS4-K
- CGA DISS Series
Nickel is standard material for gasket. If PCTFE is required, please add a suffix of "-k" to the ordering number.
Example: 6L-C632-FR4-K

CGA DISS Series

- Non-rotating design
- For nipples with TB or FR connections, inner surface electropolished to an average of Ra 9 µin. (0.23 µm); Ra 16 µin. (0.4 µm) for nipples with NPT connections
- Nipples with TB or FR connections cleaned for Ultra High Purity Service and packaged in a Class 100 clean room; Nipples with NPT connections packaged and cleaned for Oxygen service
- Maximum allowable leak rate: 1×10^{-9} mbar·l/s

Cylinder Connections (Including Nipples, Nuts and Gaskets)

Dimensions are in. (mm).



1/4" Butt Weld (TB)

Male NPT

Male Face Seal (FR)

CGA Number	End Connection	Assembly Basic Ordering Number	Nipple Basic Ordering Number	Nut Basic Ordering Number	Gasket Basic Ordering Number	Dimensions, in. (mm)	
						L	F
632	1/4" TB	-C632-TB4	-C632-L-TB4	-C630-N	-C630-GT	2.5 (63.5)	1 1/4 (31.8)
	1/4" FR	-C632-FR4	-C632-L-FR4			3 (76.2)	1 1/4 (31.8)
	1/4" NPT	-C632-NS4	-C632-L-NS4			3 (76.2)	1 1/4 (31.8)
634	1/4" TB	-C634-TB4	-C634-L-TB4	-C630-N	-C630-GT	2.5 (63.5)	1 1/4 (31.8)
	1/4" FR	-C634-FR4	-C634-L-FR4			3 (76.2)	1 1/4 (31.8)
	1/4" NPT	-C634-NS4	-C634-L-NS4			3 (76.2)	1 1/4 (31.8)
636	1/4" TB	-C636-TB4	-C636-L-TB4	-C630-N	-C630-GT	2.5 (63.5)	1 1/4 (31.8)
	1/4" FR	-C636-FR4	-C636-L-FR4			3 (76.2)	1 1/4 (31.8)
	1/4" NPT	-C636-NS4	-C636-L-NS4			3 (76.2)	1 1/4 (31.8)
638	1/4" TB	-C638-TB4	-C638-L-TB4	-C630-N	-C630-GT	2.5 (63.5)	1 1/4 (31.8)
	1/4" FR	-C638-FR4	-C638-L-FR4			3 (76.2)	1 1/4 (31.8)
	1/4" NPT	-C638-NS4	-C638-L-NS4			3 (76.2)	1 1/4 (31.8)


CGA Number	End Connection	Assembly Basic Ordering Number	Nipple Basic Ordering Number	Nut Basic Ordering Number	Gasket Basic Ordering Number	Dimensions, in. (mm)	
						L	F
640	1/4" TB	-C640-TB4	-C640-L-TB4	-C630-N	-C630-GT	2.5 (63.5)	1 1/4 (31.8)
	1/4" FR	-C640-FR4	-C640-L-FR4			3 (76.2)	1 1/4 (31.8)
	1/4" NPT	-C640-NS4	-C640-L-NS4			3 (76.2)	1 1/4 (31.8)
642	1/4" TB	-C642-TB4	-C642-L-TB4	-C630-N	-C630-GT	2.5 (63.5)	1 1/4 (31.8)
	1/4" FR	-C642-FR4	-C642-L-FR4			3 (76.2)	1 1/4 (31.8)
	1/4" NPT	-C642-NS4	-C642-L-NS4			3 (76.2)	1 1/4 (31.8)
712	1/4" TB	-C712-TB4	-C712-L-TB4	-C710-N	-C630-GT	2.5 (63.5)	1 3/8 (34.9)
	1/4" FR	-C712-FR4	-C712-L-FR4			3 (76.2)	1 3/8 (34.9)
	1/4" NPT	-C712-NS4	-C712-L-NS4			3 (76.2)	1 3/8 (34.9)
714	1/4" TB	-C714-TB4	-C714-L-TB4	-C710-N	-C630-GT	2.5 (63.5)	1 3/8 (34.9)
	1/4" FR	-C714-FR4	-C714-L-FR4			3 (76.2)	1 3/8 (34.9)
	1/4" NPT	-C714-NS4	-C714-L-NS4			3 (76.2)	1 3/8 (34.9)
716	1/4" TB	-C716-TB4	-C716-L-TB4	-C710-N	-C630-GT	2.5 (63.5)	1 3/8 (34.9)
	1/4" FR	-C716-FR4	-C716-L-FR4			3 (76.2)	1 3/8 (34.9)
	1/4" NPT	-C716-NS4	-C716-L-NS4			3 (76.2)	1 3/8 (34.9)
718	1/4" TB	-C718-TB4	-C718-L-TB4	-C710-N	-C630-GT	2.5 (63.5)	1 3/8 (34.9)
	1/4" FR	-C718-FR4	-C718-L-FR4			3 (76.2)	1 3/8 (34.9)
	1/4" NPT	-C718-NS4	-C718-L-NS4			3 (76.2)	1 3/8 (34.9)
720	1/4" TB	-C720-TB4	-C720-L-TB4	-C720-N	-C630-GT	2.5 (63.5)	1 3/8 (34.9)
	1/4" FR	-C720-FR4	-C720-L-FR4			3 (76.2)	1 3/8 (34.9)
	1/4" NPT	-C720-NS4	-C720-L-NS4			3 (76.2)	1 3/8 (34.9)
722	1/4" TB	-C722-TB4	-C722-L-TB4	-C720-N	-C630-GT	2.5 (63.5)	1 3/8 (34.9)
	1/4" FR	-C722-FR4	-C722-L-FR4			3 (76.2)	1 3/8 (34.9)
	1/4" NPT	-C722-NS4	-C722-L-NS4			3 (76.2)	1 3/8 (34.9)
724	1/4" TB	-C724-TB4	-C724-L-TB4	-C720-N	-C630-GT	2.5 (63.5)	1 3/8 (34.9)
	1/4" FR	-C724-FR4	-C724-L-FR4			3 (76.2)	1 3/8 (34.9)
	1/4" NPT	-C724-NS4	-C724-L-NS4			3 (76.2)	1 3/8 (34.9)
726	1/4" TB	-C726-TB4	-C726-L-TB4	-C720-N	-C630-GT	2.5 (63.5)	1 3/8 (34.9)
	1/4" FR	-C726-FR4	-C726-L-FR4			3 (76.2)	1 3/8 (34.9)
	1/4" NPT	-C726-NS4	-C726-L-NS4			3 (76.2)	1 3/8 (34.9)
728	1/4" TB	-C728-TB4	-C728-L-TB4	-C720-N	-C630-GT	2.5 (63.5)	1 3/8 (34.9)
	1/4" FR	-C728-FR4	-C728-L-FR4			3 (76.2)	1 3/8 (34.9)
	1/4" NPT	-C728-NS4	-C728-L-NS4			3 (76.2)	1 3/8 (34.9)

Note:

Nickel is standard material for gasket. If PCTFE is required, please add a suffix of "-k" to the ordering number.

Example: 6L-C638-TB4-K


Gaskets




CGA Number	Gasket Ordering Number	Material	Dimensions					
			A		E		H	
			in.	mm	in.	mm	in.	mm
632~728	NI-C630-GT	Nickel 200	0.56	14.3	0.21	5.4	0.105	2.7
	K-C630-GT	PCTFE	0.56	14.3	0.21	5.4	0.125	3.2
	AL-C630-GT	Aluminum	0.56	14.3	0.21	5.4	0.105	2.7

Outlet Adaptors

Female NPT




Male Face Seal (FR)




CGA Number	Basic Ordering Number	Dimensions, in. (mm)	
		L	F
632	-C632-A-FNS4	1.85 (47.0)	1 1/8 (28.6)
634	-C634-A-FNS4	1.85 (47.0)	1 1/8 (28.6)
636	-C636-A-FNS4	1.85 (47.0)	1 1/8 (28.6)
638	-C638-A-FNS4	1.85 (47.0)	1 1/8 (28.6)
640	-C640-A-FNS4	1.85 (47.0)	1 1/8 (28.6)
642	-C642-A-FNS4	1.85 (47.0)	1 1/8 (28.6)
712	-C712-A-FNS4	1.85 (47.0)	1 1/4 (31.8)
714	-C714-A-FNS4	1.85 (47.0)	1 1/4 (31.8)
716	-C716-A-FNS4	1.85 (47.0)	1 1/4 (31.8)
718	-C718-A-FNS4	1.85 (47.0)	1 1/4 (31.8)
720	-C720-A-FNS4	1.85 (47.0)	1 1/4 (31.8)
722	-C722-A-FNS4	1.85 (47.0)	1 1/4 (31.8)
724	-C724-A-FNS4	1.85 (47.0)	1 1/4 (31.8)
726	-C726-A-FNS4	1.85 (47.0)	1 1/4 (31.8)
728	-C728-A-FNS4	1.85 (47.0)	1 1/4 (31.8)

CGA Number	Basic Ordering Number	Dimensions, in. (mm)	
		L	F
632	-C632-A-FR4	2.0 (50.8)	1 1/8 (28.6)
634	-C634-A-FR4	2.0 (50.8)	1 1/8 (28.6)
636	-C636-A-FR4	2.0 (50.8)	1 1/8 (28.6)
638	-C638-A-FR4	2.0 (50.8)	1 1/8 (28.6)
640	-C640-A-FR4	2.0 (50.8)	1 1/8 (28.6)
642	-C642-A-FR4	2.0 (50.8)	1 1/8 (28.6)
712	-C712-A-FR4	2.0 (50.8)	1 1/4 (31.8)
714	-C714-A-FR4	2.0 (50.8)	1 1/4 (31.8)
716	-C716-A-FR4	2.0 (50.8)	1 1/4 (31.8)
718	-C718-A-FR4	2.0 (50.8)	1 1/4 (31.8)
720	-C720-A-FR4	2.0 (50.8)	1 1/4 (31.8)
722	-C722-A-FR4	2.0 (50.8)	1 1/4 (31.8)
724	-C724-A-FR4	2.0 (50.8)	1 1/4 (31.8)
726	-C726-A-FR4	2.0 (50.8)	1 1/4 (31.8)
728	-C728-A-FR4	2.0 (50.8)	1 1/4 (31.8)

Blank Plugs



Valve Outlet Caps (Including Chains, Rings and Gaskets)



CGA Number	Basic Ordering Number	Dimensions, in. (mm)	
		L	F
632	-C632-BP	1.53 (38.9)	1 1/8 (28.6)
634	-C634-BP	1.53 (38.9)	1 1/8 (28.6)
636	-C636-BP	1.53 (38.9)	1 1/8 (28.6)
638	-C638-BP	1.53 (38.9)	1 1/8 (28.6)
640	-C640-BP	1.53 (38.9)	1 1/8 (28.6)
642	-C642-BP	1.53 (38.9)	1 1/8 (28.6)
712	-C712-BP	1.53 (38.9)	1 1/4 (31.8)
714	-C714-BP	1.53 (38.9)	1 1/4 (31.8)
716	-C716-BP	1.53 (38.9)	1 1/4 (31.8)
718	-C718-BP	1.53 (38.9)	1 1/4 (31.8)
720	-C720-BP	1.53 (38.9)	1 1/4 (31.8)
722	-C722-BP	1.53 (38.9)	1 1/4 (31.8)
724	-C724-BP	1.53 (38.9)	1 1/4 (31.8)
726	-C726-BP	1.53 (38.9)	1 1/4 (31.8)
728	-C728-BP	1.53 (38.9)	1 1/4 (31.8)

CGA Number	Basic Ordering Number	Dimensions, in. (mm)	
		L	F
632	-C632-CP	0.98 (24.9)	1 1/4 (31.8)
634	-C634-CP	0.98 (24.9)	1 1/4 (31.8)
636	-C636-CP	0.98 (24.9)	1 1/4 (31.8)
638	-C638-CP	0.98 (24.9)	1 1/4 (31.8)
640	-C640-CP	0.98 (24.9)	1 1/4 (31.8)
642	-C642-CP	0.98 (24.9)	1 1/4 (31.8)
712	-C712-CP	0.98 (24.9)	1 3/8 (34.9)
714	-C714-CP	0.98 (24.9)	1 3/8 (34.9)
716	-C716-CP	0.98 (24.9)	1 3/8 (34.9)
718	-C718-CP	0.98 (24.9)	1 3/8 (34.9)
720	-C720-CP	0.98 (24.9)	1 3/8 (34.9)
722	-C722-CP	0.98 (24.9)	1 3/8 (34.9)
724	-C724-CP	0.98 (24.9)	1 3/8 (34.9)
726	-C726-CP	0.98 (24.9)	1 3/8 (34.9)
728	-C728-CP	0.98 (24.9)	1 3/8 (34.9)

Note:

Nickel is standard material for gasket. If PCTFE is required, please add a suffix of "-k" to the ordering number.

Example: 6L-C632-CP-K


CGA Series

- CGA V-1-2005 compliant
- For nipples with TB or FR connections, inner surface electropolished to an average of Ra 9 μin . (0.23 μm); Ra 32 μin . (0.8 μm) for nipples with NPT connections
- Cleaned and packaged for Oxygen service
- Maximum allowable leak rate: 1×10^{-9} mbar·l/s

Cylinder Connections (Including Nipples, Nuts and Gaskets)


Dimensions are in. (mm).

Fig.1




1/4" Butt Weld (TB)

Fig.2



Male NPT

Fig.3



Male Face Seal (FR)

CGA Number	Ref. Fig.	End Connection	Assembly Basic Ordering Number	Nipple Basic Ordering Number	Nut Basic Ordering Number	Gasket Basic Ordering Number	Dimensions, in. (mm)	
							L	F
170	Fig.1	1/4" TB	-C170-TB4	-C170-L-TB4	-C170-N	-C170-GT	1.25 (31.8)	11/16 (17.5)
		1/8" NPT	-C170-NS2	-C170-L-NS2				
180	Fig.1	1/4" TB	-C180-TB4	-C180-L-TB4	-C180-N	-C180-GT	1.25 (31.8)	3/4 (19.1)
		1/8" NPT	-C180-NS2	-C180-L-NS2			1.75 (44.5)	
290	Fig.2	1/4" TB	-C290-TB4	-C290-L-TB4	-C290-N		2.63 (66.7)	1 (25.4)
		1/4" NPT	-C290-NS4	-C290-L-NS4			2.25 (57.2)	
296	Fig.3	1/4" TB	-C296-TB4	-C296-L-TB4	-C296-N		2.63 (66.7)	7/8 (22.3)
		1/4" NPT	-C296-NS4	-C296-L-NS4			3.5 (88.9)	
		1/4" FR	-C296-FR4	-C296-L-FR4			2.75 (69.9)	
320	Fig.1	1/4" TB	-C320-TB4	-C320-L-TB4	-C320-N	-C320-GT	1.75 (44.5)	1 1/8 (28.6)
		1/4" NPT	-C320-NS4	-C320-L-NS4			2.5 (63.5)	
		1/4" FR	-C320-FR4	-C320-L-FR4			1.75 (44.5)	

CGA Number	Ref. Fig.	End Connection	Assembly Basic Ordering Number	Nipple Basic Ordering Number	Nut Basic Ordering Number	Gasket Basic Ordering Number	Dimensions, in. (mm)	
							L	F
326	Fig.2	1/4" TB	-C326-TB4	-C326-L-TB4	-C326-N	—	2.25 (57.2)	1 1/8 (28.6)
		1/4" NPT	-C326-NS4	-C326-L-NS4			3.0 (76.2)	
		1/4" FR	-C326-FR4	-C326-L-FR4			2.25 (57.2)	
330	Fig.1	1/4" TB	-C330-TB4	-C320-L-TB4	-C330-N	-C320-GT	1.75 (44.5)	1 1/8 (28.6)
		1/4" NPT	-C330-NS4	-C320-L-NS4			2.5 (63.5)	
		1/4" FR	-C330-FR4	-C320-L-FR4			1.75 (44.5)	
346	Fig.2	1/4" TB	-C346-TB4	-C346-L-TB4	-C346-N	—	2.31 (58.7)	1 1/8 (28.6)
		1/4" NPT	-C346-NS4	-C346-L-NS4			3.0 (76.2)	
		1/4" FR	-C346-FR4	-C346-L-FR4			2.25 (57.2)	
350	Fig.2	1/4" TB	-C350-TB4	-C350-L-TB4	-C350-N	—	2.31 (58.7)	1 1/8 (28.6)
		1/4" NPT	-C350-NS4	-C350-L-NS4			3.0 (76.2)	
		1/4" FR	-C350-FR4	-C350-L-FR4			2.25 (57.2)	
510	Fig.3	1/4" TB	-C510-TB4	-C510-L-TB4	-C510-N	—	2.63 (66.7)	1 1/8 (28.6)
		1/4" NPT	-C510-NS4	-C510-L-NS4			3.5 (88.9)	
		1/4" FR	-C510-FR4	-C510-L-FR4			2.75 (69.9)	
540 ^①	Fig.2	1/4" TB	-C540-TB4	-C540-L-TB4	-C540-N	—	2.25 (57.2)	1 1/8 (28.6)
		1/4" NPT	-C540-NS4	-C540-L-NS4			3.0 (76.2)	
		1/4" FR	-C540-FR4	-C540-L-FR4			2.25 (57.2)	
580	Fig.3	1/4" TB	-C580-TB4	-C510-L-TB4	-C580-N	—	2.63 (66.7)	1 1/8 (28.6)
		1/4" NPT	-C580-NS4	-C510-L-NS4			3.5 (88.9)	
		1/4" FR	-C580-FR4	-C510-L-FR4			2.75 (69.9)	
590	Fig.3	1/4" TB	-C590-TB4	-C510-L-TB4	-C590-N	—	2.63 (66.7)	1 1/8 (28.6)
		1/4" NPT	-C590-NS4	-C510-L-NS4			3.5 (88.9)	
		1/4" FR	-C590-FR4	-C510-L-FR4			2.75 (69.9)	
660	Fig.1	1/4" TB	-C660-TB4	-C660-L-TB4	-C660-N	-C660-GT	2.19 (55.6)	1 1/4 (31.8)
		1/4" NPT	-C660-NS4	-C660-L-NS4			2.5 (63.5)	
		1/4" FR	-C660-FR4	-C660-L-FR4			1.88 (47.6)	
670	Fig.1	1/4" TB	-C670-TB4	-C660-L-TB4	-C670-N	-C660-GT	2.19 (55.6)	1 1/4 (31.8)
		1/4" NPT	-C670-NS4	-C660-L-NS4			2.5 (63.5)	
		1/4" FR	-C670-FR4	-C660-L-FR4			1.88 (47.6)	
678	Fig.1	1/4" TB	-C678-TB4	-C678-L-TB4	-C678-N	-C678-GT	2.5 (63.5)	1 1/4 (31.8)
		1/4" NPT	-C678-NS4	-C678-L-NS4			2.5 (63.5)	
		1/4" FR	-C678-FR4	-C678-L-FR4			2.0 (50.8)	
679	Fig.1	1/4" TB	-C679-TB4	-C679-L-TB4	-C679-N	-C679-GT	2.5 (63.5)	1 1/4 (31.8)
		1/4" NPT	-C679-NS4	-C679-L-NS4			3.0 (76.2)	
		1/4" FR	-C679-FR4	-C679-L-FR4			2.0 (50.8)	


① Cleaned and packaged for Oxygen Service.

Note:

PTFE is standard material for gasket. If PCTFE is required, please add a suffix of "-k" to the ordering number.

Example: 6L-C170-FR4-K

Gaskets




CGA Number	Gasket Basic Ordering Number	Dimensions					
		A		E		H	
		in.	mm	in.	mm	in.	mm
170	-C170-GT	0.43	11.0	0.19	4.8	0.10	2.5
180	-C180-GT	0.44	11.2	0.32	8.1	0.09	2.3
320, 330	-C320-GT	0.72	18.3	0.26	6.6	0.09	2.3
660, 670	-C660-GT	0.94	23.9	0.38	9.7	0.06	1.6
678	-C678-GT	0.61	15.5	0.30	7.6	0.06	1.6
679	-C679-GT	0.53	13.5	0.31	7.9	0.06	1.6

Outlet Adaptors, Blank Caps and Plugs


Blank Caps

CGA 580




Blank Plugs

CGA 350




Male Face Seal (FR)

CGA 350



Female NPT

CGA 350




CGA Number	End Connection	Assembly Basic Ordering Number	Dimensions, in. (mm)	
			L	F
180	1/4" Female NPT	-C180-A-FNS4	1.38 (35.0)	3/4 (19.1)
296	Blank Cap	-C296-BC	1.37 (34.8)	1 1/8 (28.6)
	1/4" Female NPT	-C296-A-FNS4	2.0 (50.8)	
	1/4" FR	-C296-A-FR4	2.0 (50.8)	
320	Blank Plug	-C320-BP	1.12 (28.4)	1 (25.4)
	1/4" Female NPT	-C320-A-FNS4	1.12 (28.4)	
	1/4" FR	-C320-A-FR4	1.74 (44.2)	
326	Blank Plug	-C326-BP	1.12 (28.4)	1 (25.4)
	1/4" Female NPT	-C326-A-FNS4	1.31 (33.3)	
	1/4" FR	-C326-A-FR4	1.74 (44.2)	
330	Blank Plug	-C330-BP	1.12 (28.4)	1 (25.4)
	1/4" Female NPT	-C330-A-FNS4	1.31 (33.3)	
	1/4" FR	-C330-A-FR4	1.74 (44.2)	
346	Blank Plug	-C346-BP	1.12 (28.4)	1 (25.4)
	1/4" Female NPT	-C346-A-FNS4	1.31 (33.3)	
	1/4" FR	-C346-A-FR4	1.88 (47.8)	
350	Blank Plug	-C350-BP	1.12 (28.4)	1 (25.4)
	1/4" Female NPT	-C350-A-FNS4	1.31 (33.3)	
	1/4" FR	-C350-A-FR4	1.88 (47.8)	
510	Blank Cap	-C510-BC	1.37 (34.8)	1 1/4 (31.8)
	1/4" Female NPT	-C510-A-FNS4	2.0 (50.8)	
	1/4" FR	-C510-A-FR4	2.0 (50.8)	
540 ^①	Blank Plug	-C540-BP	1.12 (28.4)	1 (25.4)
	1/4" Female NPT	-C540-A-FNS4	1.25 (31.8)	
	1/4" FR	-C540-A-FR4	1.87 (47.5)	
580	Blank Cap	-C580-BC	1.37 (34.8)	1 1/4 (31.8)
	1/4" Female NPT	-C580-A-FNS4	2.0 (50.8)	
	1/4" FR	-C580-A-FR4	2.0 (50.8)	


① Cleaned and packaged for Oxygen Service.

Female NPT



CGA 350



CGA Number	End Connection	Assembly Basic Ordering Number	Dimensions, in. (mm)	
			L	F
590	Blank Cap	-C590-BC	1.37 (34.8)	1 1/4 (31.8)
	1/4" Female NPT	-C590-A-FNS4	2.0 (50.8)	
	1/4" FR	-C590-A-FR4	2.0 (50.8)	
660	Blank Plug	-C660-BP	0.88 (22.4)	1 1/8 (28.6)
	1/4" Female NPT	-C660-A-FNS4	1.25 (31.8)	
	1/4" FR	-C660-A-FR4	1.5 (38.1)	
670	Blank Plug	-C670-BP	0.88 (22.4)	1 1/8 (28.6)
	1/4" Female NPT	-C670-A-FNS4	1.25 (31.8)	
	1/4" FR	-C670-A-FR4	1.5 (38.1)	
678	Blank Plug	-C678-BP	1.0 (25.4)	1 1/8 (28.6)
	1/4" Female NPT	-C678-A-FNS4	1.38 (35.1)	
	1/4" FR	-C678-A-FR4	1.5 (38.1)	
679	Blank Plug	-C679-BP	0.88 (22.4)	1 1/8 (28.6)
	1/4" Female NPT	-C679-A-FNS4	1.25 (31.8)	
	1/4" FR	-C679-A-FR4	1.75 (44.5)	

Cylinder Valve Outlet Plugs

CGA Number	Basic Ordering Number	Dimensions, in. (mm)	
		L	S
510	-C510-PG	1.0 (25.4)	3/8 (9.5)
580	-C580-PG	1.0 (25.4)	
590	-C590-PG	1.0 (25.4)	



CGA Number	Basic Ordering Number	Dimensions, in. (mm)	
		L	F
320	-C320-CP	0.54 (13.7)	1 (25.4)
326	-C320-CP	0.54 (13.7)	
330	-C330-CP	0.54 (13.7)	
346	-C320-CP	0.54 (13.7)	
660	-C660-CP	0.54 (13.7)	1 1/4 (31.8)
670	-C670-CP	0.54 (13.7)	
678	-C670-CP	0.54 (13.7)	
679	-C670-CP	0.54 (13.7)	

Notes:

1. PTFE is standard material for gasket. If PCTFE is required, please add a suffix of "-k" to the ordering number.
Example: S4-C330-CP-K
2. The caps listed above are only intended to keep valve outlets clean and protect its threads. They shouldn't be used to contain pressure if the valve leaks or is opened by mistake.

CGA Number	Basic Ordering Number	Dimensions, in. (mm)	
		L	F
350	-C350-CP	0.82 (20.8)	1 1/8 (28.6)

Complete Pigtail Connections (Including Nipples, Nuts, Gaskets and Blank Plugs or Caps)

Dimensions are in. (mm).

Fig.1





Fig.2

**FITOK**

CGA Number	Ref. Fig.	Assembly Basic Ordering Number	Gasket Basic Ordering Number	Dimensions, in. (mm)		
				L	F1	F2
296	Fig.2	-C296-TB4-A	—	3.03 (77.0)	7/8 (22.3) 1 1/8 (28.6) 1 (25.4) 1 1/8 (31.8) 1 1/4 (31.8)	1 1/8 (28.6) 1 1/4 (31.8) 1 (25.4) 1 1/4 (31.8)
320	Fig.1	-C320-TB4-A	-C320-GT	2.96 (75.2)		
326	Fig.1	-C326-TB4-A	—	3.01 (76.5)		
330	Fig.1	-C330-TB4-A	-C320-GT	2.96 (75.2)		
346	Fig.1	-C346-TB4-A	—	2.97 (75.4)		
350	Fig.1	-C350-TB4-A	—	2.96 (75.2)		
510	Fig.2	-C510-TB4-A	—	3.03 (77.0)		
540 ^①	Fig.1	-C540-TB4-A	—	2.96 (75.2)		
580	Fig.2	-C580-TB4-A	—	3.03 (77.0)		
590	Fig.2	-C590-TB4-A	—	3.03 (77.0)		
660	Fig.1	-C660-TB4-A	-C660-GT	2.96 (75.2)	1 1/4 (31.8)	1 1/8 (28.6)
670	Fig.1	-C670-TB4-A	-C660-GT	2.96 (75.2)		
678	Fig.1	-C678-TB4-A	-C678-GT	3.08 (78.2)		
679	Fig.1	-C679-TB4-A	-C679-GT	2.96 (75.2)		

① Cleaned and packaged for Oxygen Service.

Note:

PTFE is standard material for gasket. If PCTFE is required, please add a suffix of "-k" to the ordering number.
Example: 6L-C330-TB4-A-K

Assembly Torque For CGA Cylinder Connections

CGA NO.	Recommended Torque		CGA NO.	Recommended Torque			
	ft-lb	N·m		ft-lb	N·m		
170 ^①	10~15	14~20	510	35~50	47~68		
180 ^①	10~15	14~20	540	40~60	54~81		
290	30~45	41~61	580	40~60	54~81		
296	35~50	47~68	590	40~60	54~81		
320 ^①	20~30	27~41	660 ^①	30~45	41~61		
326	25~35	34~47	670 ^①	30~45	41~61		
330 ^①	20~30	27~41	678 ^①	25~35	34~47		
346	35~50	47~68	679 ^①	25~35	34~47		
350	35~50	47~68					
CGA DISS NO.	Recommended Torque			Gasket Material			
	ft-lb	N·m					
632-728	35~40	47~53.8	Nickel				
	12~15	16~20.1	PCTFE				


① Gasket for seal: PTFE or PCTFE.

DIN Series


- DIN 477-1 compliant
- For nipples with TB or FR connections, inner surface electropolished to an average of Ra 9 µin. (0.23 µm); Ra 32 µin. (0.8 µm) for nipples with NPT connections
- Cleaned and packaged for Oxygen service
- Maximum allowable leak rate: 1×10^{-9} mbar·l/s

Complete Pigtail Connections (Including Nipples, Nuts, Gaskets and Blank Plugs)

Dimensions are in. (mm).



1/4" Butt Weld (TB)



Male NPT

DIN Number	Assembly Basic Ordering Number	Gasket Basic Ordering Number	Dimensions, in.(mm)		
			L	F1	F2
1	-DIN1-TB4-A	-DIN1-GT	2.96 (75.2)		
	-DIN1-NS4-A		4.25 (108)		
5	-DIN5-TB4-A	-DIN5-GT	3.09 (78.5)		
	-DIN5-NS4-A		4.41 (112)		
6	-DIN6-TB4-A	-DIN1-GT	2.96 (75.2)		
	-DIN6-NS4-A		4.25 (108)		
8	-DIN8-TB4-A	-DIN5-GT	3.09 (78.5)		
	-DIN8-NS4-A		4.41 (112)		
11	-DIN11-TB4-A	-DIN11-GT	2.88 (73.2)		
	-DIN11-NS4-A		4.14 (105.2)	7/8 (22.3)	11/16 (17.5)
14	-DIN14-TB4-A		2.88 (73.2)		
	-DIN14-NS4-A		4.15 (105.5)	1 1/16 (27.0)	7/8 (22.3)

Notes:

1. Above components can be ordered separately.
2. PTFE is standard material for gasket. If PCTFE is required, please add a suffix of "-k" to the ordering number.
Example: 6L-D1N1-TB4-A-K

Gas Connection Assignment Table^②

GAS	Formula	UHP CGA	CGA	DIN	JIS
Ammonia	NH ₃	720	705	DIN6	22-R
Argon	Ar	718	580	DIN6	22-R or 23-R
Arsenic Pentafluoride	AsF ₅	642	—	—	—
Arsine	AsH ₃	632	350	—	22-L
Boron Trichloride	BCl ₃	634	660	DIN8	—
Boron Trifluoride	BF ₃	642	330	DIN8	22-L
Carbon Dioxide	CO ₂	716	320	DIN6	—
Carbon Monoxide	CO	724	350	DIN5	22-L
Chlorine	Cl ₂	728	—	DIN8	26-R
Diborane	B ₂ H ₆	632	350	—	22-L
Dichlorosilane	SiH ₂ Cl ₂	636	678 ^①	DIN5	—
Diethylzinc	Zn(C ₂ H ₅) ₂	726	510 ^①	—	—
Diethyltelluride	(C ₂ H ₅) ₂ Te	726	—	—	—
Dimethylzinc	(CH ₃) ₂ Zn	726	—	—	—
Disilane	Si ₂ H ₆	632	—	—	—
Germane	GeH ₄	632	350 or 660	—	—
Halocarbon 11	CCl ₃ F	716	660	—	—
Halocarbon 115	ClCF ₂ CF ₃	716	660	DIN6	—
Halocarbon 12	CCl ₂ F ₂	716	660	DIN6	—
Halocarbon 13	ClCF ₃	716	660	DIN6	—
Halocarbon 14	CF ₄	716	320 or 580	DIN6	—
Halocarbon 23	CHF ₃	716	660	DIN6	—
Halocarbon 116	F ₃ CCF ₃	716	660	—	—
Helium	He	718	580	DIN6	22-R or 23-R
Hydrogen	H ₂	724	350	DIN1	22-L
Hydrogen Bromide	HBr	634	330	DIN8	26-R
Hydrogen Chloride	HCl	634	330	DIN8	26-R
Hydrogen Fluoride	HF	638	660 or 670	—	26-R
Hydrogen Sulfide	H ₂ S	722	330	DIN5	—
Krypton	Kr	718	580	DIN6	22-R or 23-R
Neon	Ne	718	580	DIN6	22-R or 23-R
Nitrogen	N ₂	718	580	DIN10	22-R or 23-R
Nitrogen Trifluoride	NF ₃	640	330 or 670	DIN8	—
Nitrous Oxide	N ₂ O	712	326	DIN8	—
Oxygen	O ₂	714	540	DIN9	22-R or 23-R
Perfluoropropane	CF ₂ (CF ₃)	716	660	—	—
Phosphine	PH ₃	632	350 or 660	DIN1	—
Phosphorus Pentafluoride	PF ₅	642	330 or 660	—	—
Silane	SiH ₄	632	350	—	—
Silicon Tetrachloride	SiCl ₄	636	—	—	—
Silicon Tetrafluoride	SiF ₄	642	330	—	22-L
Sulphur Hexafluoride	SF ₆	716	590	DIN6	26-R
Trichlorosilane	SiHCl ₃	636	—	—	—
Triethylaluminum	(C ₂ H ₅) ₃ Al	726	510 ^①	—	—
Tungsten Hexafluoride	WF ₆	638	670	DIN8	—
Xenon	Xe	718	580	DIN6	22-R

^① Refer to CGA organization specification for pressure limits.

^② Information in this table is for reference only.

B

Related Products

Purge Assemblies	B-02
Diaphragm Valves	B-04
Ball Valves	B-05
Needle Valves	B-06
Check Valves	B-07
Relief Valves	B-08
Filters	B-09
Fittings	B-10
Metal Flexible Hoses	B-13
Cylinder Connections	B-14

Purge Assemblies

FPV-1 Series

Technical Data

- Maximum working pressure: 4500 psig
- Material of the main components:
Seat: PCTFE (diaphragm valve)
Diaphragm: Elgiloy (diaphragm valve)
- Temperature: -10°F~+150°F (-23°C~+65°C)
- Leak rates:
Internal: $\leq 1 \times 10^{-9}$ mbar·l/s helium
External: $\leq 1 \times 10^{-9}$ mbar·l/s helium
- Minimum orifice: $\phi 0.13"$ (3.2 mm)

Product Types

- Straight Purge Assemblies

Consisting of a diaphragm valve and a check valve (see Fig. 1-1).

Connecting the auxiliary inlet port (see Fig. 1-2) of the regulator or in between the regulator and the cylinder (see Fig. 1-3) to allow the corrosive or toxic gas to be vented through to a safe location.




Fig. 1-1




Fig. 1-2




Fig. 1-3

- Tee Purge Assemblies

Consisting of a diaphragm valve, check valve, tee, and cylinder connections (see Fig. 2-1).

Connecting the cylinder with the regulator. Before installing a new cylinder, open the diaphragm valve, and the remaining gas is vented safely; or after a new cylinder is installed, close the regulator and open the diaphragm valve, enabling the process gas inside the cylinder to purge the atmospheric contamination between the cylinder and the regulator (see Fig. 2-2).



Fig. 2-1




Fig. 2-2

Cross Purge Assemblies

Consisting of a tee purge assembly and two additional diaphragm valves (see Fig. 3-1).

Except for process gas, purging is also made possible with inert gas from outside (see Fig. 3-2). The steps are as follows:
Before installing a new cylinder, close the diaphragm valve beside the regulator, and open the shutoff diaphragm valve on the vent line to release the residual pressure.

After installing a new cylinder, open the diaphragm valve on the bottom, allowing the inert gas from outside to purge the atmospheric contaminations between the cylinder and the diaphragm valve.




Fig. 3-1




Fig. 3-2

Part Number Description

FPV - 1C 6L - DIN1 - 00 - 00 - 00

Product Type	Body Material	Inlet Port	Vent Port	Outlet Port	Purge Inlet
S Straight Purge Assemblies	6L 316L SS	00 1/4" Female NPT	00 1/4" Female NPT	Same as Vent Port	Same as Vent Port
T Tee Purge Assemblies	SS 316 SS	01 1/4" Male NPT	01 1/4" Male NPT	Same as Vent Port	Same as Vent Port
C Cross Purge Assemblies		C--- CGA Number (USA)	10 1/4" Tube Fitting		
		DIN_ DIN Number (Germany)	20 6 mm Tube Fitting		
			21 8 mm Tube Fitting		
			Other connections are available upon request		
		Refer to page B-28 for cylinder connections based on specific gas type. Cylinder connections compliant to other standards are available upon request. Please contact FITOK Group for details.			

Diaphragm Valves

DS Series


Features

- Reduced inner capacity
- Packless diaphragm seal design for high purity
- Minimized number of components
- Manual and pneumatic actuators available
- Aluminum piston to increase operation speed



Technical Data

- Maximum working pressure: 4500 psig
- Material of the internal components:
Seat: PCTFE or Vespel
Diaphragm: Elgiloy
- Temperature:
PCTFE: -10°F~+150°F (-23°C~+65°C)
Vespel: -10°F~+250°F (-23°C~+121°C)
- Leak rates:
Internal: $\leq 1 \times 10^{-9}$ mbar·l/s helium
External: $\leq 1 \times 10^{-9}$ mbar·l/s helium
- Flow coefficient (Cv): 0.17



Part Number Description

DS	6L	-	NS	4	-	FNS	4	-	R	V	F2
Body Material			Inlet Type			Inlet Size			Actuator Type		Technology Grade
6LW	316L VIM-VAR		TB	Fractional Tube Butt Weld		4 1/4"			R		General Purpose
6L	316L SS		MTB	Metric Tube Butt Weld		6 6 mm or 3/8"			C		Special Cleaning and Packaging
SS	316 SS		FR	Male FR Fitting		8 8 mm		Specify in the same way as inlet size	O		Ultra High Purity
			FFR	Female FR Fitting					Seat		
			FL	Fractional Tube Fitting					PCTFE		
			ML	Metric Tube Fitting					V		Vespel
			NS	Male NPT							
			FNS	Female NPT							

Ball Valves

BO Series


Features

- ◎ One-piece body and one-piece ball stem
- ◎ No dead zone, such as in the area between the ball and valve chamber
- ◎ In-line inspection and repair with top entry design
- ◎ Thermal cycle performance improved and wear compensated by live-loaded design
- ◎ Multiple connections available
- ◎ Pneumatic and electric actuators available



Technical Data

- ◎ Maximum working pressure: 3000 psig (207 bar)
- ◎ Temperature: -65°F to 300°F (-54°C to 148°C)
- ◎ Seat material: PTFE



Part Number Description

BO	6L	-	NS	4 - FNS	4 - H03	-	U A	-	F2
Body Material		Connection 1 Type		Connection 2 Type		Orifice Size		Flow Pattern	
6L 316L SS		FNS Female NPT		Same as Connection 1		02 0.09" (2.4 mm)		Straight	
SS 316 SS		NS Male NPT		Specify in the same way as inlet type		03 0.13" (3.2 mm)			
B Brass		FR Male FR Fitting				05 0.19" (4.8 mm)			
		FL Fractional Tube Fitting				07 0.28" (7.1 mm)			
		ML Metric Tube Fitting		Connection 2 Size		10 0.41" (10.3 mm)			
				Same as Connection 1			Handle		
				Specify in the same way as inlet size			Black Nylon		
			Connection 1 Size				C Red Nylon		
			4 1/4"				F Green Nylon		
			6 6 mm or 3/8"				J Blue Nylon		
			8 8 mm or 1/2"				U Black Aluminium		
				Seat Material					
				PTFE					
				H UHMWPE					
				A PFA					

Needle Valves

ND Series

Features

- One-piece forged body
- Straight and angle patterns
- Compact design
- Non-rotating stem
- Specially designed handle to stop contamination from entering into the valve



Technical Data

- Maximum working pressure: 3000 psig (207 bar)
- Temperature:
PCTFE stem tip: -20°F to 200°F (-28°C to 93°C)
PEEK stem tip: -20°F to 450°F (-28°C to 232°C)

Part Number Description

ND	SS	-	FNS	4	-	NS	4	-	7	P	E	-	A	F2
Body Material			Inlet Type			Outlet Type			Tip Material		Flow Pattern			Technology Grade
6L	316L SS		FNS			Same as Inlet Type			PCTFE		Straight			General Purpose
SS	316 SS		NS			Specify in the same way as inlet type			PEEK		Angle			Special Cleaning and Packaging
B	Brass		FL			Outlet Size			Orifice Size		O-ring Material			
			ML			Same as Inlet Size			5	0.08" (2.0 mm)	FKM			
						Specify in the same way as inlet size			7	0.16" (4.0 mm)	Buna-N			
									8	0.22" (5.6 mm)	Ethyene Propylene			
			Inlet Size											
			4	1/4"										
			6	6 mm or 3/8"										
			8	8 mm or 1/2"										

Check Valves

CV, CO and COA Series


Features

- Resilient O-ring seat design for leak-free sealing
- Maximum working pressure: 3000 psig (207 bar)
- Temperature: -10°F to 375°F (-23°C to 190°C)
- PTFE-coated spring available




CV Series

- Fixed cracking pressure: 1/3 to 25 psig (0.02 to 1.7 bar)




CO Series

- Compact design with one-piece body
- Fixed cracking pressure: 1/3 to 25 psig (0.02 to 1.7 bar)



COA Series

- Adjustable cracking pressure: 3 to 600 psig (0.02 to 41.4 bar)
- A variety of springs available



Part Number Description

CV	SS	-	FNS	4	-	NS	4	-	B	-	A	F2
Series			Inlet Type		Inlet Size		Outlet Size		Cracking Pressure		Technology Grade	
CV			FNS	Female NPT	4	1/4"	Same as Inlet Size		3 psig		General Purpose	
CO			NS	Male NPT	6	6 mm or 3/8"	Specify in the same way as inlet size		1 1/3 psig	CV and CO		
COA			FL	Fractional Tube Fitting (only for CV Series)	8	8 mm or 1/2"			2 1 psig			
Body Material		Outlet Type	ML	Metric Tube Fitting (only for CV Series)	Same as Inlet Type		Specify in the same way as inlet type		3 10 psig			
6L	316L SS		FR	Male FR Fitting (only for CV Series)	Same as Inlet Type				4 25 psig			
SS	316 SS				Specify in the same way as inlet type			3 to 50 psig	COA			
B	Brass				FKM			5 50 to 150 psig				
					B Buna-N			6 150 to 350 psig				
					N Neoprene			7 350 to 600 psig				
					E Ethylene Propylene							
					Z Kalrez							

Relief Valves


RUv and RV Series

Introduction

Relief valve opens when system pressure exceeds the set pressure, allowing the medium to flow out to relieve the system pressure and closes when the system pressure decreases to the resealing pressure.


RUv Series

- Compact design with one-piece body
- Standard seat: FKM
- Temperature: -10°F to 300°F (-23°C to 148°C)
- Cracking pressure: 25 to 500 psig (1.7 to 34.5 bar)
- Set pressure by nut adjustment and spring replacement



RV Series

- Working temperature: -10°F to 300°F (-23°C to 148°C)
- Cracking pressure: 50 to 6000 psig
- Adjustable bonnet cap for pressure setting
- Lead-seal line protected



Temperature Range of Sealing Material

O-ring Material	Temperature Range °F (°C)
Fluorocarbon Rubber	25 to 250 (-4 to 121)
Buna-N Rubber	0 to 250 (-17 to 121)
Neoprene Rubber	-10 to 300 (-23 to 148)
Ethylene Propylene Rubber	30 to 250 (-1 to 121)

Part Number Description


RV	SS	-	FNS	4	-	NS	4	-	6	B	-	1		F2
Series			Inlet Type			Outlet Type			Orifice Size			Set Pressure		Technology Grade
RUV			FNS Female NPT			Same as Inlet Type			0.14" (3.6 mm) (only for RUV Series)			0 10 to 25 psig		General Purpose
RV			NS Male NPT			Specify in the same way as inlet type			0.14" (3.6 mm) (only for RV Series)			1 25 to 100 psig	RUV	Special Cleaning and Packaging
			FL Fractional Tube Fitting (only for RV Series)									2 100 to 250 psig		
			ML Metric Tube Fitting (only for RV Series)									3 250 to 500 psig		
Body Material						Outlet Size						F 50 to 300 psig		
6L 316L SS						Same as Inlet Size						O 300 to 700 psig		
SS 316 SS			Inlet Size			Specify in the same way as inlet size						Y 700 to 1500 psig		
			4 1/4"									B 1500 to 2500 psig	RV	
			6 6 mm or 3/8"									W 2500 to 3500 psig		
			8 8 mm or 1/2"									J 3500 to 4500 psig		
												Z 4500 to 6000 psig		

Filters

FT Series

Tee-type Filters


- Maximum working pressure: 6000 psig (414 bar)
- Temperature: -20 °F to 900 °F (-28°C to 482 °C)
- Filter element replaceable without removing body from system



FI Series

In-line Filters


- Maximum working pressure: 3000 psig (207 bar)
- Temperature: -20 °F to 900 °F (-28°C to 482 °C)
- Compact and space-saving design



FB Series

Bypass Filters


- Maximum working pressure: 6000 psig (414 bar)
- Temperature: -20 °F to 900 °F (-28°C to 482 °C)
- Bypass port at filter bottom for easy sampling and purging



FW Series

All-welded In-line Filters

- Maximum working pressure: 6000 psig (414 bar)
- Temperature: -20 °F to 900 °F (-28°C to 482 °C)
- Large filtration area and high flow coefficient
- All-welded construction to eliminate leakage



Part Number Description


FB	SS	-	FL	4	-	NS	4	-	S	P	2	-	FL 4	F2
Series			Inlet Type			Outlet Type			Element Type		Pore Size (µm)		Bypass Port (for FB Series only)	
FT			FNS	Female NPT		Same as Inlet Type			Sintered		05		1/8" Female NPT	
FB			NS	Male NPT		Specify in the same way as inlet type			Strainer		2		1/4" Fractional Tube Fitting	
FI			FL	Fractional Tube Fitting					Gasket Material		7		1/4" Tube Socket Weld	
FW			ML	Metric Tube Fitting					Silver-plated 316 SS for FT, FB, FI Series		15		3/8" Fractional Tube Fitting	
			FR	Male FR Fitting					PTFE-plated 316 SS for FT, FB, FI Series		40			
									A		60			
									Aluminum for FT, FB, FI Series		80			
									W		100			
									Non-plated 316 SS for FT, FB, FI Series		150			
										250				
										400				
													Technology Grade	
													General Purpose	
													F2	Special Cleaning and Packaging
Body Material			Inlet Size											
6L	316L SS		4	1/4"										
SS	316 SS		6	6 mm or 3/8"										
			8	8 mm or 1/2"										

Fittings



Features


- Sizes ranging from 1/4" to 1/2" and 6 mm to 12 mm
- Diverse material and configurations available
- Precision machined components to ensure perfect deformation of the ferrules and tubing
- Hardened threads with smooth surface finish to avoid galling and to help extend the fitting cycle life
- Silver-plated female nut threads to reduce friction against the body threads
- Radius junction design with elbows to provide smooth flow path
- Every fitting marked with size, material and heat number



Ordering Information and Dimensions

Dimensions are shown with FITOK nuts finger-tight.


Male Connectors



Fractional Tube			NPT Thread					
T-Tube O.D. (in.)	P-NPT Size	Basic Ordering Number	Dimension, in. (mm)					
			L	B	C	E	G	F
1/4	1/4	-CM-FL4-NS4	1.49(37.8)	0.56(14.2)	0.60(15.2)	0.19(4.8)	0.56(14.3)	0.56(14.3)
3/8	3/8	-CM-FL6-NS6	1.57(39.9)	0.56(14.2)	0.66(16.8)	0.28(7.1)	0.69(17.5)	0.69(17.5)
1/2	1/2	-CM-FL8-NS8	1.93(49.0)	0.75(19.1)	0.90(22.9)	0.41(10.4)	0.87(22.2)	0.87(22.2)

Metric Tube			NPT Thread					
T-Tube O.D. (mm)	P-NPT Size	Basic Ordering Number	Dimension, mm (in.)					
			L	B	C	E	G	F
6	1/4	-CM-ML6-NS4	37.9(1.49)	14.2(0.56)	15.3(0.60)	4.8(0.19)	14.0(0.55)	14.0(0.55)
8	3/8	-CM-ML8-NS6	39.3(1.55)	14.2(0.56)	16.2(0.64)	6.4(0.25)	16.0(0.63)	18.0(0.71)
10	3/8	-CM-ML10-NS6	40.9(1.61)	14.2(0.56)	17.2(0.68)	7.9(0.31)	19.0(0.75)	18.0(0.71)
12	1/2	-CM-ML12-NS8	49.0(1.93)	19.1(0.75)	22.8(0.90)	9.5(0.37)	22.0(0.87)	22.0(0.87)


Unions




Fractional Tube			Dimension, in. (mm)				
T-Tube O.D. (in.)	Basic Ordering Number	L	C		G		F
						E	
1/4	-U-FL4	1.61(40.9)	0.60(15.2)	0.56(14.3)	0.50(12.7)	0.19(4.8)	
3/8	-U-FL6	1.77(45.0)	0.66(16.8)	0.69(17.5)	0.63(15.9)	0.28(7.1)	
1/2	-U-FL8	2.02(51.3)	0.90(22.9)	0.87(22.2)	0.81(20.6)	0.41(10.4)	

Metric Tube			Dimension, mm (in.)				
T-Tube O.D. (mm)	Basic Ordering Number	L	C		G		F
						E	
6	-U-ML6	41.0(1.61)	15.3(0.60)	14.0(0.55)	14.0(0.55)	4.8(0.19)	4.8(0.19)
8	-U-ML8	43.2(1.70)	16.2(0.64)	16.0(0.63)	15.0(0.59)	4.8(0.19)	6.4(0.25)
10	-U-ML10	46.2(1.82)	17.2(0.68)	19.0(0.75)	18.0(0.71)	7.9(0.31)	
12	-U-ML12	51.2(2.02)	22.8(0.90)	22.0(0.87)	22.0(0.87)	9.5(0.37)	9.5(0.37)

Conversion Unions




Metric Tube			Fractional Tube					
T-Tube O.D. (mm)	Tx-Tube O.D. (in.)	Basic Ordering Number	Dimension, mm (in.)					
			L	C	G	F	E	Cx
6	1/4	-U-ML6-FL4	41.0(1.61)	15.3(0.60)	14.0(0.55)	14.0(0.55)	4.8(0.19)	15.2(0.60)
8	1/4	-U-ML8-FL4	42.3(1.67)	16.2(0.64)	16.0(0.63)	15.0(0.59)	4.8(0.19)	15.2(0.60)
8	3/8	-U-ML8-FL6	44.3(1.74)	16.2(0.64)	16.0(0.63)	16.0(0.63)	6.4(0.25)	16.8(0.66)
10	1/4	-U-ML10-FL4	44.5(1.75)	17.2(0.68)	19.0(0.75)	18.0(0.71)	4.8(0.19)	15.2(0.60)
10	3/8	-U-ML10-FL6	45.9(1.81)	17.2(0.68)	19.0(0.75)	18.0(0.71)	7.1(0.28)	16.8(0.66)
12	3/8	-U-ML12-FL6	48.4(1.91)	22.8(0.90)	22.0(0.87)	22.0(0.87)	7.1(0.28)	17.5(0.69)
12	1/2	-U-ML12-FL8	51.2(2.02)	22.8(0.90)	22.0(0.87)	22.0(0.87)	9.5(0.37)	22.9(0.90)

Reducing Unions**Fractional Tube**

T-Tube O.D. (in.)	Tx-Tube O.D. (in.)	Basic Ordering Number	Dimension, in. (mm)						
			L	C	G	F	E	Cx	Gx
3/8	1/4	-U-FL6-FL4	1.70(43.2)	0.66(16.8)	0.69(17.5)	0.63(15.9)	0.19(4.8)	0.60(15.2)	0.56(14.3)
1/2	1/4	-U-FL8-FL4	1.85(47.0)	0.90(22.8)	0.87(22.2)	0.81(20.6)	0.19(4.8)	0.60(15.2)	0.56(14.3)
1/2	3/8	-U-FL8-FL6	1.91(48.5)	0.90(22.8)	0.87(22.2)	0.81(20.6)	0.28(7.1)	0.66(16.8)	0.69(17.5)

Metric Tube

T-Tube O.D. (mm)	Tx-Tube O.D. (mm)	Basic Ordering Number	Dimension, mm (in.)						
			L	C	G	F	E	Cx	Gx
8	6	-U-ML8-ML6	42.3(1.67)	16.3(0.64)	16.0(0.63)	15.0(0.59)	4.8(0.19)	15.3(0.60)	14.0(0.55)
10	8	-U-ML10-ML8	45.1(1.78)	17.2(0.68)	19.0(0.75)	18.0(0.71)	6.4(0.25)	16.3(0.64)	16.0(0.63)
12	10	-U-ML12-ML10	48.7(1.92)	22.8(0.90)	22.0(0.87)	22.0(0.87)	7.9(0.31)	17.2(0.68)	19.0(0.75)

Male Elbows**Fractional Tube**

T-Tube O.D. (in.)	P-NPT Size	Basic Ordering Number	Dimension, in. (mm)						
			L	C	G	F	E	B	Lx
1/4	1/4	-LM-FL4-NS4	1.06(26.9)	0.60(15.2)	0.56(14.3)	0.50(12.7)	0.19(4.8)	0.56(14.2)	0.92(23.4)
3/8	3/8	-LM-FL6-NS6	1.23(31.2)	0.66(16.8)	0.69(17.5)	0.69(17.5)	0.28(7.1)	0.56(14.2)	1.03(26.2)
1/2	1/2	-LM-FL8-NS8	1.42(36.1)	0.90(22.9)	0.87(22.2)	0.81(20.6)	0.41(10.4)	0.75(19.1)	1.30(33.0)

Metric Tube


T-Tube O.D. (mm)	P-NPT Size	Basic Ordering Number	Dimension, mm (in.)						
			L	C	G	F	E	B	Lx
6	1/4	-LM-ML6-NS4	27.0(1.06)	15.3(0.60)	14.0(0.55)	12.7(0.50)	4.8(0.19)	14.2(0.56)	23.4(0.92)
8	3/8	-LM-ML8-NS6	30.6(1.20)	16.2(0.64)	16.0(0.63)	17.5(0.69)	6.4(0.25)	14.2(0.56)	26.2(1.03)
10	3/8	-LM-ML10-NS6	31.5(1.24)	17.2(0.68)	19.0(0.75)	17.5(0.69)	7.9(0.31)	14.2(0.56)	26.2(1.03)
12	1/2	-LM-ML12-NS8	36.0(1.42)	22.8(0.90)	22.0(0.87)	20.6(0.81)	9.5(0.37)	19.1(0.75)	33.0(1.30)

Metal Flexible Hoses

MH, MM Series

Features

- Core tube and fitting material: 316 SS
- Overbraid material: 304 SS
- For vacuum and positive pressure applications
- Maximum working pressure: 3100 psig (213 bar)
- Hose size: 1/4" to 1"
- Temperature: -325°F to 800°F (-200°C to 426°C)
- End connections:
1/8 to 1 thread
3/16" to 1" and 6 mm to 22 mm tube fitting
- Welded fitting-to-hose construction to ensure reliable seal
- Standard and custom length available



Hose Technical Data (MH Series)

Nominal Hose Size	Inside Diameter	Min. Bend Radius		Temperature Range	Working Pressure @ 70°F (20°C)	Burst Pressure @ 70°F (20°C)	Hose Series
		Static	Dynamic				
in. (mm)	in. (mm)	in. (mm)	in. (mm)	°F (°C)	psig (bar)	psig (bar)	
1/4 (6.4)	0.28 (7.1)	2.25 (57.2)	10.0 (254)	-325 to 800 (-200 to 426)	3100 (213)	12400 (854)	MH4
3/8 (9.7)	0.42 (10.6)	3.00 (76.2)	12.0 (305)		2000 (137)	8000 (551)	MH6
1/2 (12.7)	0.53 (13.5)	4.50 (114)	16.0 (406)		1800 (124)	7200 (496)	MH8
3/4 (19.0)	0.80 (20.3)	6.00 (152)	17.0 (432)		1500 (103)	6000 (413)	MH12
1 (25.4)	1.03 (26.0)	6.75 (171)	20.0 (508)		1200 (82.6)	4800 (330)	MH16

Hose Technical Data (MM Series)

Nominal Hose Size	Inside Diameter	Min. Bend Radius		Temperature Range	Working Pressure @ 70°F (20°C)	Burst Pressure @ 70°F (20°C)	Hose Series
		Static	Dynamic				
in. (mm)	in. (mm)	in. (mm)	in. (mm)	°F (°C)	psig (bar)	psig (bar)	
1/4 (6.4)	0.25 (6.4)	0.75 (19.0)	4.33 (110)	-325 to 800 (-200 to 426)	1600 (110)	6400 (440)	MM4
3/8 (9.7)	0.38 (9.5)	0.87 (22.1)	5.91 (150)		1470 (101)	6000 (413)	MM6
1/2 (12.7)	0.50 (12.7)	1.04 (26.4)	6.50 (165)		1110 (76.4)	4500 (310)	MM8
3/4 (19.0)	0.75 (19.0)	1.61 (40.9)	8.86 (225)		860 (59.2)	3500 (241)	MM12
1 (25.4)	1.00 (25.4)	1.89 (48.0)	10.2 (259)		680 (46.8)	2680 (184)	MM16

Cylinder Connections



CGA DISS Series

B-16

CGA Series

B-20

DIN Series

B-27

Gas Connection Assignment Table

B-28

Features


- 100% visual inspection of critical surfaces
- Diverse material and configurations available
- Silver-plated nut threads to reduce installation torque
- Every fitting marked with size, material and heat number
- Cleaned and packaged for Oxygen and Ultra High Purity Service available
- Customized solutions available

Material

Series	Component	Material	Designator
CGA DISS	Nipples	316L SS	6L
	Nuts	304 SS	S4
	Gaskets	Nickel 200	NI
		PCTFE	K
		Aluminum	AL
	Plugs	316L SS	6L
	Adapters	316L SS	6L
CGA DIN	Caps	316L SS	6L
	Nipples	316L SS	6L
	Nuts	304 SS	S4
	Gaskets	PTFE	T
		PCTFE	K
	Plugs, Caps	316L SS	6L
	Adapters	316L SS	6L

Notes:

1. Nickel gasket heat treated; surface hardness < HB 100
2. 316L SS in compliance with SEMI F20



Ordering information


- Add material designator as a prefix to the basic ordering number to get the complete ordering number.
Example: 6L-C634-L-FR4
- CGA, DIN Series
PTFE is standard material for gasket. If PCTFE is required, please add a suffix of "-k" to the ordering number.
Example: 6L-C350-NS4-K
- CGA DISS Series
Nickel is standard material for gasket. If PCTFE is required, please add a suffix of "-k" to the ordering number.
Example: 6L-C632-FR4-K

CGA DISS Series

- Non-rotating design
- For nipples with TB or FR connections, inner surface electropolished to an average of Ra 9 µin. (0.23 µm); Ra 16 µin. (0.4 µm) for nipples with NPT connections
- Nipples with TB or FR connections cleaned for Ultra High Purity Service and packaged in a Class 100 clean room; Nipples with NPT connections packaged and cleaned for Oxygen service
- Maximum allowable leak rate: 1×10^{-9} mbar·l/s

Cylinder Connections (Including Nipples, Nuts and Gaskets)

Dimensions are in. (mm).



1/4" Butt Weld (TB)

Male NPT

Male Face Seal (FR)

CGA Number	End Connection	Assembly Basic Ordering Number	Nipple Basic Ordering Number	Nut Basic Ordering Number	Gasket Basic Ordering Number	Dimensions, in. (mm)	
						L	F
632	1/4" TB	-C632-TB4	-C632-L-TB4	-C630-N	-C630-GT	2.5 (63.5)	1 1/4 (31.8)
	1/4" FR	-C632-FR4	-C632-L-FR4			3 (76.2)	1 1/4 (31.8)
	1/4" NPT	-C632-NS4	-C632-L-NS4			3 (76.2)	1 1/4 (31.8)
634	1/4" TB	-C634-TB4	-C634-L-TB4	-C630-N	-C630-GT	2.5 (63.5)	1 1/4 (31.8)
	1/4" FR	-C634-FR4	-C634-L-FR4			3 (76.2)	1 1/4 (31.8)
	1/4" NPT	-C634-NS4	-C634-L-NS4			3 (76.2)	1 1/4 (31.8)
636	1/4" TB	-C636-TB4	-C636-L-TB4	-C630-N	-C630-GT	2.5 (63.5)	1 1/4 (31.8)
	1/4" FR	-C636-FR4	-C636-L-FR4			3 (76.2)	1 1/4 (31.8)
	1/4" NPT	-C636-NS4	-C636-L-NS4			3 (76.2)	1 1/4 (31.8)
638	1/4" TB	-C638-TB4	-C638-L-TB4	-C630-N	-C630-GT	2.5 (63.5)	1 1/4 (31.8)
	1/4" FR	-C638-FR4	-C638-L-FR4			3 (76.2)	1 1/4 (31.8)
	1/4" NPT	-C638-NS4	-C638-L-NS4			3 (76.2)	1 1/4 (31.8)


CGA Number	End Connection	Assembly Basic Ordering Number	Nipple Basic Ordering Number	Nut Basic Ordering Number	Gasket Basic Ordering Number	Dimensions, in. (mm)	
						L	F
640	1/4" TB	-C640-TB4	-C640-L-TB4	-C630-N	-C630-GT	2.5 (63.5)	1 1/4 (31.8)
	1/4" FR	-C640-FR4	-C640-L-FR4			3 (76.2)	1 1/4 (31.8)
	1/4" NPT	-C640-NS4	-C640-L-NS4			3 (76.2)	1 1/4 (31.8)
642	1/4" TB	-C642-TB4	-C642-L-TB4	-C630-N	-C630-GT	2.5 (63.5)	1 1/4 (31.8)
	1/4" FR	-C642-FR4	-C642-L-FR4			3 (76.2)	1 1/4 (31.8)
	1/4" NPT	-C642-NS4	-C642-L-NS4			3 (76.2)	1 1/4 (31.8)
712	1/4" TB	-C712-TB4	-C712-L-TB4	-C710-N	-C630-GT	2.5 (63.5)	1 3/8 (34.9)
	1/4" FR	-C712-FR4	-C712-L-FR4			3 (76.2)	1 3/8 (34.9)
	1/4" NPT	-C712-NS4	-C712-L-NS4			3 (76.2)	1 3/8 (34.9)
714	1/4" TB	-C714-TB4	-C714-L-TB4	-C710-N	-C630-GT	2.5 (63.5)	1 3/8 (34.9)
	1/4" FR	-C714-FR4	-C714-L-FR4			3 (76.2)	1 3/8 (34.9)
	1/4" NPT	-C714-NS4	-C714-L-NS4			3 (76.2)	1 3/8 (34.9)
716	1/4" TB	-C716-TB4	-C716-L-TB4	-C710-N	-C630-GT	2.5 (63.5)	1 3/8 (34.9)
	1/4" FR	-C716-FR4	-C716-L-FR4			3 (76.2)	1 3/8 (34.9)
	1/4" NPT	-C716-NS4	-C716-L-NS4			3 (76.2)	1 3/8 (34.9)
718	1/4" TB	-C718-TB4	-C718-L-TB4	-C710-N	-C630-GT	2.5 (63.5)	1 3/8 (34.9)
	1/4" FR	-C718-FR4	-C718-L-FR4			3 (76.2)	1 3/8 (34.9)
	1/4" NPT	-C718-NS4	-C718-L-NS4			3 (76.2)	1 3/8 (34.9)
720	1/4" TB	-C720-TB4	-C720-L-TB4	-C720-N	-C630-GT	2.5 (63.5)	1 3/8 (34.9)
	1/4" FR	-C720-FR4	-C720-L-FR4			3 (76.2)	1 3/8 (34.9)
	1/4" NPT	-C720-NS4	-C720-L-NS4			3 (76.2)	1 3/8 (34.9)
722	1/4" TB	-C722-TB4	-C722-L-TB4	-C720-N	-C630-GT	2.5 (63.5)	1 3/8 (34.9)
	1/4" FR	-C722-FR4	-C722-L-FR4			3 (76.2)	1 3/8 (34.9)
	1/4" NPT	-C722-NS4	-C722-L-NS4			3 (76.2)	1 3/8 (34.9)
724	1/4" TB	-C724-TB4	-C724-L-TB4	-C720-N	-C630-GT	2.5 (63.5)	1 3/8 (34.9)
	1/4" FR	-C724-FR4	-C724-L-FR4			3 (76.2)	1 3/8 (34.9)
	1/4" NPT	-C724-NS4	-C724-L-NS4			3 (76.2)	1 3/8 (34.9)
726	1/4" TB	-C726-TB4	-C726-L-TB4	-C720-N	-C630-GT	2.5 (63.5)	1 3/8 (34.9)
	1/4" FR	-C726-FR4	-C726-L-FR4			3 (76.2)	1 3/8 (34.9)
	1/4" NPT	-C726-NS4	-C726-L-NS4			3 (76.2)	1 3/8 (34.9)
728	1/4" TB	-C728-TB4	-C728-L-TB4	-C720-N	-C630-GT	2.5 (63.5)	1 3/8 (34.9)
	1/4" FR	-C728-FR4	-C728-L-FR4			3 (76.2)	1 3/8 (34.9)
	1/4" NPT	-C728-NS4	-C728-L-NS4			3 (76.2)	1 3/8 (34.9)

Note:

Nickel is standard material for gasket. If PCTFE is required, please add a suffix of "-k" to the ordering number.

Example: 6L-C638-TB4-K


Gaskets




CGA Number	Gasket Ordering Number	Material	Dimensions					
			A		E		H	
			in.	mm	in.	mm	in.	mm
632~728	NI-C630-GT	Nickel 200	0.56	14.3	0.21	5.4	0.105	2.7
	K-C630-GT	PCTFE	0.56	14.3	0.21	5.4	0.125	3.2
	AL-C630-GT	Aluminum	0.56	14.3	0.21	5.4	0.105	2.7

Outlet Adaptors

Female NPT




Male Face Seal (FR)




CGA Number	Basic Ordering Number	Dimensions, in. (mm)	
		L	F
632	-C632-A-FNS4	1.85 (47.0)	1 1/8 (28.6)
634	-C634-A-FNS4	1.85 (47.0)	1 1/8 (28.6)
636	-C636-A-FNS4	1.85 (47.0)	1 1/8 (28.6)
638	-C638-A-FNS4	1.85 (47.0)	1 1/8 (28.6)
640	-C640-A-FNS4	1.85 (47.0)	1 1/8 (28.6)
642	-C642-A-FNS4	1.85 (47.0)	1 1/8 (28.6)
712	-C712-A-FNS4	1.85 (47.0)	1 1/4 (31.8)
714	-C714-A-FNS4	1.85 (47.0)	1 1/4 (31.8)
716	-C716-A-FNS4	1.85 (47.0)	1 1/4 (31.8)
718	-C718-A-FNS4	1.85 (47.0)	1 1/4 (31.8)
720	-C720-A-FNS4	1.85 (47.0)	1 1/4 (31.8)
722	-C722-A-FNS4	1.85 (47.0)	1 1/4 (31.8)
724	-C724-A-FNS4	1.85 (47.0)	1 1/4 (31.8)
726	-C726-A-FNS4	1.85 (47.0)	1 1/4 (31.8)
728	-C728-A-FNS4	1.85 (47.0)	1 1/4 (31.8)

CGA Number	Basic Ordering Number	Dimensions, in. (mm)	
		L	F
632	-C632-A-FR4	2.0 (50.8)	1 1/8 (28.6)
634	-C634-A-FR4	2.0 (50.8)	1 1/8 (28.6)
636	-C636-A-FR4	2.0 (50.8)	1 1/8 (28.6)
638	-C638-A-FR4	2.0 (50.8)	1 1/8 (28.6)
640	-C640-A-FR4	2.0 (50.8)	1 1/8 (28.6)
642	-C642-A-FR4	2.0 (50.8)	1 1/8 (28.6)
712	-C712-A-FR4	2.0 (50.8)	1 1/4 (31.8)
714	-C714-A-FR4	2.0 (50.8)	1 1/4 (31.8)
716	-C716-A-FR4	2.0 (50.8)	1 1/4 (31.8)
718	-C718-A-FR4	2.0 (50.8)	1 1/4 (31.8)
720	-C720-A-FR4	2.0 (50.8)	1 1/4 (31.8)
722	-C722-A-FR4	2.0 (50.8)	1 1/4 (31.8)
724	-C724-A-FR4	2.0 (50.8)	1 1/4 (31.8)
726	-C726-A-FR4	2.0 (50.8)	1 1/4 (31.8)
728	-C728-A-FR4	2.0 (50.8)	1 1/4 (31.8)

Blank Plugs



Valve Outlet Caps (Including Chains, Rings and Gaskets)



CGA Number	Basic Ordering Number	Dimensions, in. (mm)	
		L	F
632	-C632-BP	1.53 (38.9)	1 1/8 (28.6)
634	-C634-BP	1.53 (38.9)	1 1/8 (28.6)
636	-C636-BP	1.53 (38.9)	1 1/8 (28.6)
638	-C638-BP	1.53 (38.9)	1 1/8 (28.6)
640	-C640-BP	1.53 (38.9)	1 1/8 (28.6)
642	-C642-BP	1.53 (38.9)	1 1/8 (28.6)
712	-C712-BP	1.53 (38.9)	1 1/4 (31.8)
714	-C714-BP	1.53 (38.9)	1 1/4 (31.8)
716	-C716-BP	1.53 (38.9)	1 1/4 (31.8)
718	-C718-BP	1.53 (38.9)	1 1/4 (31.8)
720	-C720-BP	1.53 (38.9)	1 1/4 (31.8)
722	-C722-BP	1.53 (38.9)	1 1/4 (31.8)
724	-C724-BP	1.53 (38.9)	1 1/4 (31.8)
726	-C726-BP	1.53 (38.9)	1 1/4 (31.8)
728	-C728-BP	1.53 (38.9)	1 1/4 (31.8)

CGA Number	Basic Ordering Number	Dimensions, in. (mm)	
		L	F
632	-C632-CP	0.98 (24.9)	1 1/4 (31.8)
634	-C634-CP	0.98 (24.9)	1 1/4 (31.8)
636	-C636-CP	0.98 (24.9)	1 1/4 (31.8)
638	-C638-CP	0.98 (24.9)	1 1/4 (31.8)
640	-C640-CP	0.98 (24.9)	1 1/4 (31.8)
642	-C642-CP	0.98 (24.9)	1 1/4 (31.8)
712	-C712-CP	0.98 (24.9)	1 3/8 (34.9)
714	-C714-CP	0.98 (24.9)	1 3/8 (34.9)
716	-C716-CP	0.98 (24.9)	1 3/8 (34.9)
718	-C718-CP	0.98 (24.9)	1 3/8 (34.9)
720	-C720-CP	0.98 (24.9)	1 3/8 (34.9)
722	-C722-CP	0.98 (24.9)	1 3/8 (34.9)
724	-C724-CP	0.98 (24.9)	1 3/8 (34.9)
726	-C726-CP	0.98 (24.9)	1 3/8 (34.9)
728	-C728-CP	0.98 (24.9)	1 3/8 (34.9)

Note:

Nickel is standard material for gasket. If PCTFE is required, please add a suffix of "-k" to the ordering number.

Example: 6L-C632-CP-K


CGA Series

- CGA V-1-2005 compliant
- For nipples with TB or FR connections, inner surface electropolished to an average of Ra 9 µin. (0.23 µm); Ra 32 µin. (0.8 µm) for nipples with NPT connections
- Cleaned and packaged for Oxygen service
- Maximum allowable leak rate: 1×10^{-9} mbar·l/s

Cylinder Connections (Including Nipples, Nuts and Gaskets)


Dimensions are in. (mm).

Fig.1




1/4" Butt Weld (TB)

Fig.2



Male NPT

Fig.3



Male Face Seal (FR)

CGA Number	Ref. Fig.	End Connection	Assembly Basic Ordering Number	Nipple Basic Ordering Number	Nut Basic Ordering Number	Gasket Basic Ordering Number	Dimensions, in. (mm)	
							L	F
170	Fig.1	1/4" TB	-C170-TB4	-C170-L-TB4	-C170-N	-C170-GT	1.25 (31.8)	11/16 (17.5)
		1/8" NPT	-C170-NS2	-C170-L-NS2				
180	Fig.1	1/4" TB	-C180-TB4	-C180-L-TB4	-C180-N	-C180-GT	1.25 (31.8)	3/4 (19.1)
		1/8" NPT	-C180-NS2	-C180-L-NS2			1.75 (44.5)	
290	Fig.2	1/4" TB	-C290-TB4	-C290-L-TB4	-C290-N		2.63 (66.7)	1 (25.4)
		1/4" NPT	-C290-NS4	-C290-L-NS4			2.25 (57.2)	
296	Fig.3	1/4" TB	-C296-TB4	-C296-L-TB4	-C296-N		2.63 (66.7)	7/8 (22.3)
		1/4" NPT	-C296-NS4	-C296-L-NS4			3.5 (88.9)	
		1/4" FR	-C296-FR4	-C296-L-FR4			2.75 (69.9)	
320	Fig.1	1/4" TB	-C320-TB4	-C320-L-TB4	-C320-N	-C320-GT	1.75 (44.5)	1 1/8 (28.6)
		1/4" NPT	-C320-NS4	-C320-L-NS4			2.5 (63.5)	
		1/4" FR	-C320-FR4	-C320-L-FR4			1.75 (44.5)	

CGA Number	Ref. Fig.	End Connection	Assembly Basic Ordering Number	Nipple Basic Ordering Number	Nut Basic Ordering Number	Gasket Basic Ordering Number	Dimensions, in. (mm)	
							L	F
326	Fig.2	1/4" TB	-C326-TB4	-C326-L-TB4	-C326-N	—	2.25 (57.2)	1 1/8 (28.6)
		1/4" NPT	-C326-NS4	-C326-L-NS4			3.0 (76.2)	
		1/4" FR	-C326-FR4	-C326-L-FR4			2.25 (57.2)	
330	Fig.1	1/4" TB	-C330-TB4	-C320-L-TB4	-C330-N	-C320-GT	1.75 (44.5)	1 1/8 (28.6)
		1/4" NPT	-C330-NS4	-C320-L-NS4			2.5 (63.5)	
		1/4" FR	-C330-FR4	-C320-L-FR4			1.75 (44.5)	
346	Fig.2	1/4" TB	-C346-TB4	-C346-L-TB4	-C346-N	—	2.31 (58.7)	1 1/8 (28.6)
		1/4" NPT	-C346-NS4	-C346-L-NS4			3.0 (76.2)	
		1/4" FR	-C346-FR4	-C346-L-FR4			2.25 (57.2)	
350	Fig.2	1/4" TB	-C350-TB4	-C350-L-TB4	-C350-N	—	2.31 (58.7)	1 1/8 (28.6)
		1/4" NPT	-C350-NS4	-C350-L-NS4			3.0 (76.2)	
		1/4" FR	-C350-FR4	-C350-L-FR4			2.25 (57.2)	
510	Fig.3	1/4" TB	-C510-TB4	-C510-L-TB4	-C510-N	—	2.63 (66.7)	1 1/8 (28.6)
		1/4" NPT	-C510-NS4	-C510-L-NS4			3.5 (88.9)	
		1/4" FR	-C510-FR4	-C510-L-FR4			2.75 (69.9)	
540 ^①	Fig.2	1/4" TB	-C540-TB4	-C540-L-TB4	-C540-N	—	2.25 (57.2)	1 1/8 (28.6)
		1/4" NPT	-C540-NS4	-C540-L-NS4			3.0 (76.2)	
		1/4" FR	-C540-FR4	-C540-L-FR4			2.25 (57.2)	
580	Fig.3	1/4" TB	-C580-TB4	-C510-L-TB4	-C580-N	—	2.63 (66.7)	1 1/8 (28.6)
		1/4" NPT	-C580-NS4	-C510-L-NS4			3.5 (88.9)	
		1/4" FR	-C580-FR4	-C510-L-FR4			2.75 (69.9)	
590	Fig.3	1/4" TB	-C590-TB4	-C510-L-TB4	-C590-N	—	2.63 (66.7)	1 1/8 (28.6)
		1/4" NPT	-C590-NS4	-C510-L-NS4			3.5 (88.9)	
		1/4" FR	-C590-FR4	-C510-L-FR4			2.75 (69.9)	
660	Fig.1	1/4" TB	-C660-TB4	-C660-L-TB4	-C660-N	-C660-GT	2.19 (55.6)	1 1/4 (31.8)
		1/4" NPT	-C660-NS4	-C660-L-NS4			2.5 (63.5)	
		1/4" FR	-C660-FR4	-C660-L-FR4			1.88 (47.6)	
670	Fig.1	1/4" TB	-C670-TB4	-C660-L-TB4	-C670-N	-C660-GT	2.19 (55.6)	1 1/4 (31.8)
		1/4" NPT	-C670-NS4	-C660-L-NS4			2.5 (63.5)	
		1/4" FR	-C670-FR4	-C660-L-FR4			1.88 (47.6)	
678	Fig.1	1/4" TB	-C678-TB4	-C678-L-TB4	-C678-N	-C678-GT	2.5 (63.5)	1 1/4 (31.8)
		1/4" NPT	-C678-NS4	-C678-L-NS4			2.5 (63.5)	
		1/4" FR	-C678-FR4	-C678-L-FR4			2.0 (50.8)	
679	Fig.1	1/4" TB	-C679-TB4	-C679-L-TB4	-C679-N	-C679-GT	2.5 (63.5)	1 1/4 (31.8)
		1/4" NPT	-C679-NS4	-C679-L-NS4			3.0 (76.2)	
		1/4" FR	-C679-FR4	-C679-L-FR4			2.0 (50.8)	


① Cleaned and packaged for Oxygen Service.

Note:

PTFE is standard material for gasket. If PCTFE is required, please add a suffix of "-k" to the ordering number.

Example: 6L-C170-FR4-K

Gaskets




CGA Number	Gasket Basic Ordering Number	Dimensions					
		A		E		H	
		in.	mm	in.	mm	in.	mm
170	-C170-GT	0.43	11.0	0.19	4.8	0.10	2.5
180	-C180-GT	0.44	11.2	0.32	8.1	0.09	2.3
320, 330	-C320-GT	0.72	18.3	0.26	6.6	0.09	2.3
660, 670	-C660-GT	0.94	23.9	0.38	9.7	0.06	1.6
678	-C678-GT	0.61	15.5	0.30	7.6	0.06	1.6
679	-C679-GT	0.53	13.5	0.31	7.9	0.06	1.6

Outlet Adaptors, Blank Caps and Plugs


Blank Caps

CGA 580




Blank Plugs

CGA 350




Male Face Seal (FR)

CGA 350



Female NPT

CGA 350




CGA Number	End Connection	Assembly Basic Ordering Number	Dimensions, in. (mm)	
			L	F
180	1/4" Female NPT	-C180-A-FNS4	1.38 (35.0)	3/4 (19.1)
296	Blank Cap	-C296-BC	1.37 (34.8)	1 1/8 (28.6)
	1/4" Female NPT	-C296-A-FNS4	2.0 (50.8)	
	1/4" FR	-C296-A-FR4	2.0 (50.8)	
320	Blank Plug	-C320-BP	1.12 (28.4)	1 (25.4)
	1/4" Female NPT	-C320-A-FNS4	1.12 (28.4)	
	1/4" FR	-C320-A-FR4	1.74 (44.2)	
326	Blank Plug	-C326-BP	1.12 (28.4)	1 (25.4)
	1/4" Female NPT	-C326-A-FNS4	1.31 (33.3)	
	1/4" FR	-C326-A-FR4	1.74 (44.2)	
330	Blank Plug	-C330-BP	1.12 (28.4)	1 (25.4)
	1/4" Female NPT	-C330-A-FNS4	1.31 (33.3)	
	1/4" FR	-C330-A-FR4	1.74 (44.2)	
346	Blank Plug	-C346-BP	1.12 (28.4)	1 (25.4)
	1/4" Female NPT	-C346-A-FNS4	1.31 (33.3)	
	1/4" FR	-C346-A-FR4	1.88 (47.8)	
350	Blank Plug	-C350-BP	1.12 (28.4)	1 (25.4)
	1/4" Female NPT	-C350-A-FNS4	1.31 (33.3)	
	1/4" FR	-C350-A-FR4	1.88 (47.8)	
510	Blank Cap	-C510-BC	1.37 (34.8)	1 1/4 (31.8)
	1/4" Female NPT	-C510-A-FNS4	2.0 (50.8)	
	1/4" FR	-C510-A-FR4	2.0 (50.8)	
540 ^①	Blank Plug	-C540-BP	1.12 (28.4)	1 (25.4)
	1/4" Female NPT	-C540-A-FNS4	1.25 (31.8)	
	1/4" FR	-C540-A-FR4	1.87 (47.5)	
580	Blank Cap	-C580-BC	1.37 (34.8)	1 1/4 (31.8)
	1/4" Female NPT	-C580-A-FNS4	2.0 (50.8)	
	1/4" FR	-C580-A-FR4	2.0 (50.8)	


① Cleaned and packaged for Oxygen Service.

Female NPT



CGA 350



CGA Number	End Connection	Assembly Basic Ordering Number	Dimensions, in. (mm)	
			L	F
590	Blank Cap	-C590-BC	1.37 (34.8)	1 1/4 (31.8)
	1/4" Female NPT	-C590-A-FNS4	2.0 (50.8)	
	1/4" FR	-C590-A-FR4	2.0 (50.8)	
660	Blank Plug	-C660-BP	0.88 (22.4)	1 1/8 (28.6)
	1/4" Female NPT	-C660-A-FNS4	1.25 (31.8)	
	1/4" FR	-C660-A-FR4	1.5 (38.1)	
670	Blank Plug	-C670-BP	0.88 (22.4)	1 1/8 (28.6)
	1/4" Female NPT	-C670-A-FNS4	1.25 (31.8)	
	1/4" FR	-C670-A-FR4	1.5 (38.1)	
678	Blank Plug	-C678-BP	1.0 (25.4)	1 1/8 (28.6)
	1/4" Female NPT	-C678-A-FNS4	1.38 (35.1)	
	1/4" FR	-C678-A-FR4	1.5 (38.1)	
679	Blank Plug	-C679-BP	0.88 (22.4)	1 1/8 (28.6)
	1/4" Female NPT	-C679-A-FNS4	1.25 (31.8)	
	1/4" FR	-C679-A-FR4	1.75 (44.5)	

Cylinder Valve Outlet Plugs

CGA Number	Basic Ordering Number	Dimensions, in. (mm)	
		L	S
510	-C510-PG	1.0 (25.4)	3/8 (9.5)
580	-C580-PG	1.0 (25.4)	
590	-C590-PG	1.0 (25.4)	



CGA Number	Basic Ordering Number	Dimensions, in. (mm)	
		L	F
320	-C320-CP	0.54 (13.7)	1 (25.4)
326	-C320-CP	0.54 (13.7)	
330	-C330-CP	0.54 (13.7)	
346	-C320-CP	0.54 (13.7)	
660	-C660-CP	0.54 (13.7)	1 1/4 (31.8)
670	-C670-CP	0.54 (13.7)	
678	-C670-CP	0.54 (13.7)	
679	-C670-CP	0.54 (13.7)	

Notes:

1. PTFE is standard material for gasket. If PCTFE is required, please add a suffix of "-k" to the ordering number.
Example: S4-C330-CP-K
2. The caps listed above are only intended to keep valve outlets clean and protect its threads. They shouldn't be used to contain pressure if the valve leaks or is opened by mistake.

CGA Number	Basic Ordering Number	Dimensions, in. (mm)	
		L	F
350	-C350-CP	0.82 (20.8)	1 1/8 (28.6)

Complete Pigtail Connections (Including Nipples, Nuts, Gaskets and Blank Plugs or Caps)

Dimensions are in. (mm).

Fig.1





Fig.2

**FITOK**

CGA Number	Ref. Fig.	Assembly Basic Ordering Number	Gasket Basic Ordering Number	Dimensions, in. (mm)		
				L	F1	F2
296	Fig.2	-C296-TB4-A	—	3.03 (77.0)	7/8 (22.3) 1 1/8 (28.6) 1 (25.4) 1 1/8 (31.8) 1 1/4 (31.8)	1 1/8 (28.6) 1 1/4 (31.8) 1 (25.4) 1 1/4 (31.8)
320	Fig.1	-C320-TB4-A	-C320-GT	2.96 (75.2)		
326	Fig.1	-C326-TB4-A	—	3.01 (76.5)		
330	Fig.1	-C330-TB4-A	-C320-GT	2.96 (75.2)		
346	Fig.1	-C346-TB4-A	—	2.97 (75.4)		
350	Fig.1	-C350-TB4-A	—	2.96 (75.2)		
510	Fig.2	-C510-TB4-A	—	3.03 (77.0)		
540 ^①	Fig.1	-C540-TB4-A	—	2.96 (75.2)		
580	Fig.2	-C580-TB4-A	—	3.03 (77.0)		
590	Fig.2	-C590-TB4-A	—	3.03 (77.0)		
660	Fig.1	-C660-TB4-A	-C660-GT	2.96 (75.2)	1 1/4 (31.8)	1 1/8 (28.6)
670	Fig.1	-C670-TB4-A	-C660-GT	2.96 (75.2)		
678	Fig.1	-C678-TB4-A	-C678-GT	3.08 (78.2)		
679	Fig.1	-C679-TB4-A	-C679-GT	2.96 (75.2)		

① Cleaned and packaged for Oxygen Service.

Note:

PTFE is standard material for gasket. If PCTFE is required, please add a suffix of "-k" to the ordering number.

Example: 6L-C330-TB4-A-K

Assembly Torque For CGA Cylinder Connections

CGA NO.	Recommended Torque		CGA NO.	Recommended Torque			
	ft-lb	N·m		ft-lb	N·m		
170 ^①	10~15	14~20	510	35~50	47~68		
180 ^①	10~15	14~20	540	40~60	54~81		
290	30~45	41~61	580	40~60	54~81		
296	35~50	47~68	590	40~60	54~81		
320 ^①	20~30	27~41	660 ^①	30~45	41~61		
326	25~35	34~47	670 ^①	30~45	41~61		
330 ^①	20~30	27~41	678 ^①	25~35	34~47		
346	35~50	47~68	679 ^①	25~35	34~47		
350	35~50	47~68					
CGA DISS NO.	Recommended Torque			Gasket Material			
	ft-lb	N·m					
632-728	35~40	47~53.8	Nickel				
	12~15	16~20.1	PCTFE				


① Gasket for seal: PTFE or PCTFE.

DIN Series


- DIN 477-1 compliant
- For nipples with TB or FR connections, inner surface electropolished to an average of Ra 9 µin. (0.23 µm); Ra 32 µin. (0.8 µm) for nipples with NPT connections
- Cleaned and packaged for Oxygen service
- Maximum allowable leak rate: 1×10^{-9} mbar·l/s

Complete Pigtail Connections (Including Nipples, Nuts, Gaskets and Blank Plugs)

Dimensions are in. (mm).



1/4" Butt Weld (TB)



Male NPT

DIN Number	Assembly Basic Ordering Number	Gasket Basic Ordering Number	Dimensions, in.(mm)		
			L	F1	F2
1	-DIN1-TB4-A	-DIN1-GT	2.96 (75.2)		
	-DIN1-NS4-A		4.25 (108)		
5	-DIN5-TB4-A	-DIN5-GT	3.09 (78.5)		
	-DIN5-NS4-A		4.41 (112)		
6	-DIN6-TB4-A	-DIN1-GT	2.96 (75.2)	1 1/4 (31.8)	1 1/4 (31.8)
	-DIN6-NS4-A		4.25 (108)		
8	-DIN8-TB4-A	-DIN5-GT	3.09 (78.5)		
	-DIN8-NS4-A		4.41 (112)		
11	-DIN11-TB4-A	-DIN11-GT	2.88 (73.2)	7/8 (22.3)	11/16 (17.5)
	-DIN11-NS4-A		4.14 (105.2)		
14	-DIN14-TB4-A		2.88 (73.2)	1 1/16 (27.0)	7/8 (22.3)
	-DIN14-NS4-A		4.15 (105.5)		

Notes:

1. Above components can be ordered separately.
2. PTFE is standard material for gasket. If PCTFE is required, please add a suffix of "-k" to the ordering number.
Example: 6L-D1N1-TB4-A-K

Gas Connection Assignment Table^②

GAS	Formula	UHP CGA	CGA	DIN	JIS
Ammonia	NH ₃	720	705	DIN6	22-R
Argon	Ar	718	580	DIN6	22-R or 23-R
Arsenic Pentafluoride	AsF ₅	642	—	—	—
Arsine	AsH ₃	632	350	—	22-L
Boron Trichloride	BCl ₃	634	660	DIN8	—
Boron Trifluoride	BF ₃	642	330	DIN8	22-L
Carbon Dioxide	CO ₂	716	320	DIN6	—
Carbon Monoxide	CO	724	350	DIN5	22-L
Chlorine	Cl ₂	728	—	DIN8	26-R
Diborane	B ₂ H ₆	632	350	—	22-L
Dichlorosilane	SiH ₂ Cl ₂	636	678 ^①	DIN5	—
Diethylzinc	Zn(C ₂ H ₅) ₂	726	510 ^①	—	—
Diethyltelluride	(C ₂ H ₅) ₂ Te	726	—	—	—
Dimethylzinc	(CH ₃) ₂ Zn	726	—	—	—
Disilane	Si ₂ H ₆	632	—	—	—
Germane	GeH ₄	632	350 or 660	—	—
Halocarbon 11	CCl ₃ F	716	660	—	—
Halocarbon 115	ClCF ₂ CF ₃	716	660	DIN6	—
Halocarbon 12	CCl ₂ F ₂	716	660	DIN6	—
Halocarbon 13	ClCF ₃	716	660	DIN6	—
Halocarbon 14	CF ₄	716	320 or 580	DIN6	—
Halocarbon 23	CHF ₃	716	660	DIN6	—
Halocarbon 116	F ₃ CCF ₃	716	660	—	—
Helium	He	718	580	DIN6	22-R or 23-R
Hydrogen	H ₂	724	350	DIN1	22-L
Hydrogen Bromide	HBr	634	330	DIN8	26-R
Hydrogen Chloride	HCl	634	330	DIN8	26-R
Hydrogen Fluoride	HF	638	660 or 670	—	26-R
Hydrogen Sulfide	H ₂ S	722	330	DIN5	—
Krypton	Kr	718	580	DIN6	22-R or 23-R
Neon	Ne	718	580	DIN6	22-R or 23-R
Nitrogen	N ₂	718	580	DIN10	22-R or 23-R
Nitrogen Trifluoride	NF ₃	640	330 or 670	DIN8	—
Nitrous Oxide	N ₂ O	712	326	DIN8	—
Oxygen	O ₂	714	540	DIN9	22-R or 23-R
Perfluoropropane	CF ₂ (CF ₃)	716	660	—	—
Phosphine	PH ₃	632	350 or 660	DIN1	—
Phosphorus Pentafluoride	PF ₅	642	330 or 660	—	—
Silane	SiH ₄	632	350	—	—
Silicon Tetrachloride	SiCl ₄	636	—	—	—
Silicon Tetrafluoride	SiF ₄	642	330	—	22-L
Sulphur Hexafluoride	SF ₆	716	590	DIN6	26-R
Trichlorosilane	SiHCl ₃	636	—	—	—
Triethylaluminum	(C ₂ H ₅) ₃ Al	726	510 ^①	—	—
Tungsten Hexafluoride	WF ₆	638	670	DIN8	—
Xenon	Xe	718	580	DIN6	22-R

^① Refer to CGA organization specification for pressure limits.

^② Information in this table is for reference only.

C

Technical References

Common Terms and Definitions	C-02
Gas Purity Values	C-03
How to Use the FITOK Flow Charts	C-04
Conversion Factors	C-05
Material Compatibility for Gases	C-06
Ordering Details for Specialty Gas Equipment	C-08

Common Terms and Definitions

Inlet Pressure

The pressure of media of gas or liquid on the inlet port of the regulator or valve;
Typical units of measure: psig, bar and MPa.

Outlet Pressure

The pressure of media of gas or liquid on the outlet port of the regulator or valve.

Accuracy

The variation in control pressure which occurs under steady state conditions within the control range of a regulator.

Sensitivity

The ability of a pressure regulator to respond to change in discharge conditions: pressure, flow, temperature, etc.

Flow Coefficient (Cv)

A flow coefficient that is numerically equal to the number of U.S. Gallons of water at 60°F/16°C that will flow through a valve or regulator in one minute when the pressure differential between the inlet and outlet is 1 psi. When gas is used instead of liquid, the equation is modified to account for the use of a compressible fluid. For a regulator, Cv is determined when the regulator is wide open and not regulating. When determining flow performance use actual flow curves.

Leakage - External

The loss of fluid from the external surfaces or joints of a regulator or valve. Example: From the body-bonnet-diaphragm joint. Leakage to atmosphere. The leakage rate is measured in mbar l/s Helium.

Leakage - Internal

The loss of fluid through a regulator or valve, between pressure zones normally expected to be sealed. Example: Between the inlet pressure and the outlet pressure zones.

Load Element

One of the three basic elements of a pressure reducing regulator. It provides the means by which the operator can set the force that determines the control pressure of a regulator. This element includes the spring and the stem.

Sensing Element

One of the three basic elements of a pressure reducing regulator. It senses the changes of the outlet pressure and acts as a physical connection between the load element and control element.

Control Element

One of the three basic elements of a pressure regulator to reduce the high inlet pressure to a stable lower outlet pressure by adjusting the orifice.

Diaphragm

One type of sensing elements, which is sensitive in reacting to outlet pressure change, normally used for gas media. Common material include elastomeric and metallic.

Piston

One type of sensing element. Used in high pressure regulators. Normally with O-ring seals.

Unbalanced Main Valve

Inlet pressure provides the majority of the shutoff force. The function of the main valve is to reduce the high inlet pressure to a lower outlet pressure.

Balanced Valve

A main valve designed to relieve the inlet force loading on the seat.

Venting

When the load pressure is relieved, the vent valve shall be opened by the downstream force to vent the downstream pressure.

Gas Purity Values

Type	Degree	Purity Value	Max. Contamination (ppm)
Pure	2.5	99.5%	5000
	3.0	99.9%	1000
High Purity	3.5	99.95%	500
	4.0	99.99%	100
	4.5	99.995%	50
	5.0	99.999%	10
	5.5	99.9995%	5
	6.0	99.9999%	1.0
Ultra High Purity	7.0	99.99999%	0.1

How to Use the FITOK Flow Chart

A FITOK Flow Chart is a graphic representation of test results, in curves, showing the changes in outlet pressure of a regulator with the varying flow rate basing on different inlet pressures. The regulator is so designed that at the time the outlet pressure reaches the set pressure, the flow rate would be zero. The inlet pressure is indicated on the right end of each curve.

To use the FITOK Flow Charts, the first step is to select the chart that fits the following:

- Regulator model
- Expected flow range
- Inlet pressure range
- Outlet pressure range

Subsequently, select a curve, if available, plotted for the exact inlet pressure and set pressure of the outlet (zero flow). Locate the set pressure on the vertical axis. Follow the curve until it crosses the vertical line corresponding to the desired flow rate. Read horizontally from the cross point to the vertical axis to locate the actual working pressure for this flow rate. If no curve is plotted for the exact pressure, extrapolate a new curve between and referring to the two closest existing curves.

Example:

Using the flow chart to determine the pressure drop (from the set pressure to the outlet pressure at 30 SCFM condition).

Given Conditions: Inlet pressure=3000 psig, Set pressure=2250 psig


Steps: 1. Locate the set pressure (2250 psig) with zero flow on the vertical axis;

2. Follow the curve until it crosses the vertical line corresponding to 30 SCFM;

3. Read horizontally from the cross point to the vertical axis. The corresponding pressure read is 1945 psig.

Therefore, the pressure drop is 305 psig.

Flow Chart



Notes:

1. The performance of regulator is more accurate in the range where the curve is comparatively flat.
2. All test results on the FITOK Flow Charts are based on utilization of Nitrogen as a medium in standard testing conditions. Please contact FITOK for additional information.

Conversion Factors

Pressure

From \ To	psi	bar	atm	KPa	ft. of H ₂ O	in. of H ₂ O	mm of Hg	in. of Hg	Kg/cm ²
psi	1	0.068948	0.06805	6.89465	2.3089	27.708	51.175	2.036	0.070307
bar	14.5038	1	0.98692	100	33.4883	401.8596	750.062	29.53	1.0197
atm	14.696	1.01325	1	101.3171	33.932	407.1827	760	29.921	1.0332
KPa	0.14504	0.010	0.00987	1	0.33456	4.01472	7.5006	0.29613	0.0102
ft. of H ₂ O	0.433107	0.029891	0.02947	2.989	1	12	22.4198	0.882646	0.03048
in. of H ₂ O	0.03609	0.002499	0.00246	0.0249089	0.08333	1	1.86832	0.073556	0.00254
mm of Hg	0.019337	0.001333	0.00132	0.133322	0.044603	0.535240	1	0.03937	0.00136
in. of Hg	0.49115	0.033864	0.03342	3.376895	1.134	13.6	25.4	1	0.034532
Kg/cm ²	14.22334	0.980665	0.9678	98.03922	32.8084	393.7008	735.5592	28.95903	1

Flow

From \ To	cm ³ /min	cm ³ /sec	ft ³ /hr	ft ³ /min	m ³ /hr	m ³ /min	L/hr	L/min
cm ³ /min	1	0.0166667	0.0021189	0.0000353	0.00006	0.000001	0.06	0.001
cm ³ /sec	60	1	0.127134	0.0021189	0.0036	0.00006	3.6	0.06
ft ³ /hr	471.9474	7.86579	1	0.0166667	0.0283168	0.0004719	28.31685	0.4719474
ft ³ /min	28316.85	471.9474	60	1	1.699008	0.0283168	1699.008	28.31686
m ³ /hr	16666.67	277.7778	35.31467	0.5885777	1	0.0166667	1000	16.66667
m ³ /min	1000000	16666.67	2118.876	35.31467	60	1	60000	1000
L/hr	16.66667	0.2777778	0.0353147	0.0005885	0.001	0.0000167	1	0.0166667
L/min	1000	16.66667	2.118876	0.0353147	0.06	0.001	60	1

Density

From \ To	gms/cm ³	kg/m ³	lbs/ft ³	lbs/in ³	lbs/U.S. gal
gms/cm ³	1	1000	62.428	0.0361273	8.3454
kg/m ³	0.001	1	0.062428	3.61273×10 ⁻⁵	0.0083454
lbs/ft ³	0.0160185	16.018463	1	5.78704×10 ⁻⁴	0.13368
lbs/in ³	27.679905	27679.9	1728	1	231
lbs/U.S. gal	0.1198264	119.8264	7.4805195	0.004329	1

Material Compatibility for Gases

Material	Metals						Plastics			Elastomers		
	Copper	Brass	Aluminum	SS	Hastelloy C 22	Monel	PCTFE	Teflon PTFE	PEEK	Vespel	Viton	Buna-N
Acetylene	3	2	1	1	1	1	1	1	4	4	1	1
Ammonia	3	3	2	1	1	1	1	1	4	3	3	2
Argon	1	1	1	1	1	1	1	1	1	1	1	1
Argon/Methane	1	1	1	1	1	1	1	1	1	1	1	1
Arsine	3	2	3	1	1	1	1	1	4	4	1	4
Boron Trichloride	3	3	3	2	1	1	1	1	4	4	4	3
Boron Trifluoride	3	3	3	2	1	1	1	1	4	4	4	3
N-Butane	1	1	1	1	1	1	1	1	1	1	1	1
Carbon Dioxide	1	1	1	1	1	1	1	1	1	1	1	1
Carbon Monoxide	1	1	1	1	1	1	1	1	4	4	1	1
Chlorine	3	3	3	2	1	1	1	1	4	2	1	3
Deuterium	1	1	1	1	1	1	1	1	1	1	1	1
Diborane	1	1	1	1	1	1	1	1	1	1	1	3
Ethane	1	1	1	1	1	1	1	1	1	1	1	1
Ethylene	1	1	1	1	1	1	1	1	1	1	1	1
Fluorine	2	3	2	3	3	1	2	1	3	3	3	3
Hydrogen	1	1	1	1	1	1	1	1	1	1	1	1
Hydrogen Chloride	3	3	3	2	1	1	1	1	4	2	2	3
Hydrogen Flouride	3	3	3	3	2	1	1	1	4	4	4	3
Hydrogen Sulphide	3	3	3	1	1	4	4	4	4	4	1	4
Hydrogen Iodide	3	3	3	4	4	4	4	4	4	4	4	4
Helium	1	1	1	1	1	1	1	1	1	1	1	1
Hexafluoro Ethane	1	1	1	1	1	1	2	1	4	4	4	4

Codes

- 1 Recommended
- 2 Use with Limitations
- 3 Not Applicable
- 4 Insufficient Data

Material Media	Metals						Plastics			Elastomers		
	Copper	Brass	Aluminum	SS	Hastelloy C 22	Monel	PCTFE	Teflon PTFE	PEEK	Vespel	Viton	Buna-N
Isobutene	1	1	1	1	1	1	1	1	1	1	1	1
Isobutane	1	1	1	1	1	1	1	1	1	1	1	1
Krypton	1	1	1	1	1	1	1	1	1	1	1	1
Methane	1	1	1	1	1	1	1	1	1	1	1	1
Methyl Chloride	4	4	3	1	1	4	4	1	4	4	1	3
Methyl Mercaptan	3	2	1	1	4	4	1	1	4	4	4	4
Neon	1	1	1	1	1	1	1	1	1	1	1	1
Nitrogen	1	1	1	1	1	1	1	1	1	1	1	1
Nitrous Oxide	1	1	1	1	1	1	2	1	1	1	1	1
Nitrogen Dioxide	4	2	2	1	4	2	1	1	4	4	4	4
Nitrogen Trifluoride	2	4	4	2	4	1	4	4	4	4	4	4
Nitrogen Monoxide	3	3	1	1	1	3	1	1	4	4	4	4
Phosphine	2	1	2	1	1	1	1	1	4	4	2	4
Propane	1	1	1	1	1	1	1	1	1	1	1	1
Propylene	1	1	1	1	1	1	1	1	1	1	1	3
Oxygen	1	1	1	1	1	1	1	1	1	1	1	1
Sulphur Dioxide	2	2	2	1	1	4	1	1	4	4	3	3
Sulphur Hexafluoride	1	1	1	1	1	1	1	1	1	1	1	1
Silane	1	1	1	1	1	1	1	1	4	4	1	4
Synthetic Air	1	1	1	1	1	1	1	1	1	1	1	1
Tetrafluoro Methane	1	1	1	1	1	1	1	1	4	4	1	4
Trifluoro Methane R23	1	1	1	1	1	1	1	1	4	4	4	4
Xenon	1	1	1	1	1	1	1	1	1	1	1	1

Codes

- 1 Recommended
- 2 Use with Limitations
- 3 Not Applicable
- 4 Insufficient Data

Ordering Details for Specialty Gas Equipment

Company _____

Name _____

Tel _____

E-mail _____

Application Information

Gas _____ **Chemical formula** _____ **Purity** _____

Upstream pressure _____ psig, _____ bar, _____ Mpa

Downstream pressure range _____ psig, _____ bar, _____ Mpa

Temperature _____ °C _____ °F **Cv or flow rate** _____

Application _____

Pressure Regulator Data

Single-stage **Dual-stage**

Material (mostly gas type dependent): **Stainless Steel** **Brass** **Hastelloy**

Cylinder pressure regulator

Cylinder connection Yes No

Purge unit Yes No

Panel and line pressure regulator

2 ports 3 ports 4 ports

Pressure control panel

Purge unit Yes No

Changeover system

With line regulator Yes No

Point-of-use panel


Integrated Gas System



FITOK

Integrated Gas System

Integrated Gas System is a device used for gas control in the semiconductor industry. As semiconductor manufacturing processes become more advanced, the requirements for gas control device are also increasing. FITOK Integrated Gas System uses SEMI compliant surface-mounted components and is modularly designed. While reducing the size of the device, installation and maintenance become easier.



Substrates

Features

- 316L VIM-VAR
- Non-fixed installation to ensure the sealing effect
- The wetted parts are treated with EP, and the surface roughness does not exceed Ra 5 µin. (0.13 µm)



W-seal Gaskets

Features

- 316L VIM-VAR
- Sealing faces independent of components receiving external forces
- After EP treatment, the surface roughness does not exceed Ra 5 µin. (0.13 µm)



Diaphragm Valves

Features


- Body material: 316L VIM-VAR
- Elgiloy diaphragm improves strength and corrosion resistance
- 1.125" W-seal modular design
- No packing diaphragm seal ensures high purity
- No dead zone structure design of flow channel, easy to purge
- Pneumatic actuator optional
- The wetted parts are treated with EP, and the surface roughness does not exceed Ra 5 µin. (0.13 µm)



Technical Data

Max. Working Pressure	Manual	145 psig (10 bar)
	Pneumatic	
Working Temperature		14°F~176°F (-10~80°C)
Flow Coefficient (Cv)		0.2
Actuator Working Pressure		60~90 psig (4.2~6.2 bar)
Leak Rate	Internal	$\leq 1 \times 10^{-9}$ mbar l/s
	External	$\leq 1 \times 10^{-9}$ mbar l/s

Dimensions and Ordering Information



Ordering Number	Port Type and Size	Dimensions, in. (mm)				
		A	B	C	H	H1
DS6LW-WS11-CF3	1.125" W-seal	0.86 (21.8)	0.39 (10.0)	1.13 (28.6)	3.46 (88.0)	0.26 (6.5)
DS6LW-WS11-OF3	1.125" W-seal	0.86 (21.8)	0.39 (10.0)	1.13 (28.6)	3.46 (88.0)	0.26 (6.5)
DS6LW-WS11-RF3	1.125" W-seal	0.86 (21.8)	0.39 (10.0)	1.13 (28.6)	2.99 (76.0)	0.26 (6.5)

Note: For other materials and port types, please contact FITOK.

FITOK

Check Valves

Features


- Body material: 316L VIM-VAR
- 1.125" W-seal modular design
- The wetted parts are treated with EP, and the surface roughness does not exceed Ra 5 μ in. (0.13 μ m)



Technical Data

Max. Working Pressure	145 psig (10 bar)				
Working Temperature	14°F~176°F (-10~80°C)				
Flow Coefficient (Cv)	0.2				
Cracking Pressure	2.26 KPa				
Leak Rate	<table><tr><td>Internal</td><td>$\leq 1 \times 10^{-9}$ mbar l/s</td></tr><tr><td>External</td><td>$\leq 1 \times 10^{-9}$ mbar l/s</td></tr></table>	Internal	$\leq 1 \times 10^{-9}$ mbar l/s	External	$\leq 1 \times 10^{-9}$ mbar l/s
Internal	$\leq 1 \times 10^{-9}$ mbar l/s				
External	$\leq 1 \times 10^{-9}$ mbar l/s				

Dimensions and Ordering Information



Ordering Number	Port Type and Size	Dimensions, in. (mm)				
		A	B	C	H	H1
CW6LW-WS11-F3	1.125" W-seal	0.86 (21.8)	0.39 (10.0)	1.13 (28.6)	1.85 (47.0)	0.26 (6.5)

Note: For other materials and port types, please contact FITOK.

Regulators

Features


- Body material: 316L VIM-VAR
- Hastelloy poppet and diaphragm
- Metal-to-metal diaphragm seal design
- 1.125" W-seal modular design
- Reinforced diaphragm design improves sealing performance and service life
- No springs and threads in the wetted zone, easy to purge
- The wetted parts are treated with EP, and the surface roughness does not exceed Ra 5 µin. (0.13 µm)



Technical Data

Max. Working Pressure	145 psig (10 bar)
Working Temperature	-40~160°F (-40~71°C)
Outlet Pressure Range	0~60 psig (0~4.1 bar)
Flow Coefficient (Cv)	0.06
Leak Rate	Internal $\leq 5 \times 10^{-8}$ mbar l/s
	External $\leq 2 \times 10^{-9}$ mbar l/s

Dimensions and Ordering Information




Bottom View

Ordering Number	Connection Type and Size	Dimensions, in. (mm)				
		A	B	C	H	H1
FHR-M6LW-145-60-WS11-F3	1.125" W-seal	0.86 (21.8)	0.39 (10.0)	1.13 (28.6)	4.10 (104.0)	0.27 (6.9)

Note: For other materials and port types, please contact FITOK.

FITOK



FITOK Group

FITOK GmbH

Spredlinger Landstr. 115, 63069 Offenbach am Main,
Germany
Tel.: +49 69 8900 4498 Fax: +49 69 8900 4495

FITOK (Wuhan) Incorporated

Zhongbai Yangluo Industrial Park, Hanshi Road,
Xinzhou District, Wuhan 430415, China
Tel.: +86 27 8983 8988 Fax: +86 27 8983 8980

FITOK (Suzhou) Metal Products Co., Ltd.

No. 29 Changsheng Road, Yangyuan Industrial Park,
Xinzhuan Town, Changshu, Jiangsu 215562, China
Tel.: +86 512 5247 9001 Fax: +86 512 5247 9002

info@fitokgroup.com
www.fitokgroup.com



Installation Instructions and Cautions

1. Before installing the pressure regulator, the pipeline must be purged to remove foreign matter and particles, such as remaining scrap iron from pipe cutting.



2. Filter must be installed upstream of the pressure regulator, otherwise system particles will damage the seat, causing internal leakage in the pressure regulator, increasing downstream pressure, and damaging the gauge or other equipment. FITOK FT series 15 µm filter is recommended and poppet in-line replacement is available.



3. Thread adhesive or liquid tape is not recommended for NPT thread installation, otherwise the filter in the pressure regulator may be blocked, resulting in no pressure at the outlet.



4. Turn the handle clockwise to increase outlet pressure and counterclockwise to reduce outlet pressure. The regulator handle can be in loose state when the outlet pressure is zero. Forcefully loose the handle may cause the stem thread stuck, then turn the handle clockwise, the stem will not move and the handle will fall off, resulting in unable to adjust pressure.

5. It is not recommended to use the pressure regulator for shutoff for a long time, otherwise the seat will deform, resulting in flow instability.

6. Handle with care and avoid any strike, especially for pressure regulator with gauge. The gauge is a sensitive element and external force may cause damage.

VPR Series Steam Heated Vaporizing Pressure Regulator

Features


- 316L SS or Alloy 400 body optional
- Low internal volume
- Convoluted diaphragm design to improve regulation precision and cycle life
- Good thermal conductivity saves energy and cost
- With special cleaning and packaging, applicable to oxygen-enriched environments

Technical Data

- Maximum inlet pressure: 3600 psig (248.2 bar)
- Outlet pressure range: 0~25 psig (0~1.7 bar), 0~50 psig (0~3.4 bar), 0~100 psig (0~6.9 bar), 0~250 psig (0~17.2 bar), 0~500 psig (0~34.5 bar)
- Materials of the internal components:
 - Body: 316L SS or Alloy 400
 - Seat: PEEK
 - Diaphragm: Hastelloy
 - Poppet spring: Alloy X-750
 - Lift poppet: Hastelloy
- Maximum vapor pressure and temperature: 600 psig (41 bar) and 500°F (260°C)
- Medium working temperature: -40°F~+500°F (-40°C~+260°C)
- Leak rates:
 - Internal $\leqslant 1 \times 10^{-7}$ mbar l/s helium
 - External $\leqslant 1 \times 10^{-7}$ mbar l/s helium
- Flow coefficient (Cv): 0.06
- Weight: ≈ 5.5 lbs (2.5 Kg)
- Standard Connections: 1/4" female NPT for inlet and outlet port, 3/8" female NPT steam supply connections




Typical Flow Chart




Dimensions

Dimensions, in inches (millimeters), are for reference only.



Port Configuration



Part Number Description

VPR - M	-	36	-	100	-	00	-	00	-	B	-	R
Body Material		Inlet Pressure P1 psig (bar)		Connection 1		Connection 2		Connection 3		Connection 4		
6L 316L SS		36 3600 (248.2)		00 1/4" Female NPT		B With Gauge (psi/bar)		Same as Connection 1		Same as Connection 2		
M Alloy 400		Outlet Pressure Range P2 psig (bar)		01 1/4" Male NPT		M With Gauge (MPa)						
		25 0~25 (0~1.7)		10 1/4" Tube Fitting		R Relief Valve						
		50 0~50 (0~3.4)		11 3/8" Tube Fitting		P Plug						
		100 0~100 (0~6.9)		20 6 mm Tube Fitting		00 1/4" Female NPT						
		250 0~250 (0~17.2)		21 8 mm Tube Fitting		01 1/4" Male NPT						
		500 0~500 (0~34.5)		Other connections are available upon request								

Examples of part number:

- a. 2-port type (1 in, 1 out): VPR-6L-36-50-00-00
- b. 3-port type (1 in, 2 out): VPR-6L-36-100-00-B-00
- c. 4-port type (1 in, 3 out): VPR-6L-36-250-00-B-00-R

Other connections are available upon request