



aerospace
climate control
electromechanical
filtration
fluid & gas handling
hydraulics
pneumatics
process control
sealing & shielding



Pneumatic Cylinders

Series P1A
According to ISO 6432

Catalogue PDE2564TCUK-ul. August 2009



ENGINEERING YOUR SUCCESS.

Features	Air cylinder	Hydraulic cylinder	Electro mechanical actuators
Overload safe	***	***	*
Easy to limit force	***	***	*
Easy to vary speed	***	***	*
Speed	***	**	**
Reliability	***	***	***
Robustness	***	***	*
Installation cost	***	*	**
Ease of service	***	**	*
Safety in damp environments	***	***	*
Safety in explosive atmospheres	***	***	*
Safety risk with electrical installations	***	***	*
Risk of oil leak	***	*	***
Clean, hygienic	***	**	*
Standardised measurements	***	***	*
Service life	***	***	*
Hydraulic system required	***	*	***
Weight	**	**	**
Purchase price	***	**	*
Power density	**	***	*
Noise level during operation	**	***	**
High force for size	**	***	*
Positioning possibilities	*	***	***
Total energy consumption	*	**	***
Service interval	*	**	***
Compressor capacity required	*	***	***

* = good, **=average, ***=excellent

Important

 Before attempting any external or internal work on the cylinder or any connected components, make sure the cylinder is vented and disconnect the air supply in order to ensure isolation of the air supply.

Note

All technical data in this catalogue are typical data only.
Air quality is essential for maximum cylinder service life (see ISO 8573).

WARNING

FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS AND/OR SYSTEMS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.


This document and other information from Parker Hannifin Corporation, its subsidiaries and authorized distributors provide product and/or system options for further investigation by users having technical expertise. It is important that you analyze all aspects of your application and review the information concerning the product or system in the current product catalog. Due to the variety of operating conditions and applications for these products or systems, the user, through its own analysis and testing, is solely responsible for making the final selection of the products and systems and assuring that all performance, safety and warning requirements of the application are met. The products described herein, including without limitation, product features, specifications, designs, availability and pricing, are subject to change by Parker Hannifin Corporation and its subsidiaries at any time without notice.

SALE CONDITIONS

The items described in this document are available for sale by Parker Hannifin Corporation, its subsidiaries or its authorized distributors. Any sale contract entered into by Parker will be governed by the provisions stated in Parker's standard terms and conditions of sale (copy available upon request).

Contents

	Page
ISO cylinder series P1A.....	4-5
Cylinder forces	6
Main data.....	7
Working medium, air quality	7
Material specification	8
Cushioning diagram	8
Dimensions.....	9
Guide for selecting suitable tubing	10-11
Order key.....	12
Stroke length	12
Order codes single-acting P1A.....	13
Order codes double-acting P1A	14-15
P1A with rod guidance modules	16-18
Mountings.....	19-22
Sensors.....	23-26
Connecting cables with one connector.....	27
Male connectors for connecting cables	27
Ready to use connecting cables with connectors at each end	27
Connection block Valvetronic 110.....	28



Double and single-acting versions

The P1A range of cylinders is intended for use in a wide range of applications. The cylinders are particularly suitable for lighter duties in the packaging, food and textile industries. Hygienic design, the use of corrosion-resistant materials and initial lubrication with our food-grade grease makes the cylinders suitable for food industry applications.

Careful design and high quality manufacture throughout ensure long service life and optimum economy.

Mounting dimensions fully in accordance with ISO 6432 and CETOP RP52P greatly simplifies installation and world-wide interchangeability.

The cylinders are available in bores of 10, 12, 16, 20 and 25 mm, with stroke lengths from 10 mm to 320 mm.

Single-acting cylinders with spring return in the retract direction are available in stroke lengths up to 80 mm.

Single-acting cylinders with spring return in the advance direction are available in 16 mm, 20 mm and 25 mm bore sizes and with stroke lengths up to 80 mm.

Double-acting cushioned cylinders

Adjustable pneumatic cushioning permits greater loads and higher operating speeds, making the cylinders suitable for more demanding duties.

These cylinders are available in bores of 16, 20 and 25 mm, with stroke lengths from 20 mm to 500 mm.

Options

In addition to a wide range of standard cylinders, Mini ISO cylinders are available in several standard variants, such as non-standard stroke length, extended piston rods, double piston rods, high temperature versions etc. In addition, a complete range of sensors and mountings are available.

Effective cushioning

The Mini ISO range is available with fixed end cushioning or with adjustable pneumatic cushioning, controlled by simple bleed screws for fine adjustment. The adjustable cushioned cylinders can be operated with higher mass loads and at higher speeds than those with fixed end cushioning, reducing overall cycle times.

Smooth external design

There are no recesses or pockets in the end covers that could trap dirt or liquid, making cleaning simple and effective.

Corrosion-resistant

Even the basic versions of the cylinders have good corrosion resistance through appropriate choice of materials and surface treatment, allowing them to be used in demanding environments.

Stainless steel versions

The Mini ISO range is also available in an all-stainless version with piston rod, barrel and end covers of stainless steel for use in particularly severe environments. See separate brochure for cylinder series P1S.

Proximity sensing

A complete range of sensors for proximity sensing is available as accessories: both reed switch and Hall effect sensors are available. They are supplied with either flying lead or cable plug connector.

Complete mounting programme

A complete ISO compatible mounting programme with surface-treated/stainless steel piston rod and cylinder mountings for both pivoted and fixed operation are available.

Variants

In addition to the basic versions, a number of standard variants of Parker Pneumatics cylinders are available to meet all demands on function and environmental adaptation:

Non-standard stroke lengths

Extended piston rods

Through piston rods


Single acting cylinder with spring return
(in the retract direction).

Single acting cylinder with spring return in the advance direction (piston rod in extended position)


External guide, for controlled guidance of the piston rod
High-temperature cylinder versions for use in ambient temperatures ranging from -10 °C to +150 °C for bores 12, 16, 20 and 25 mm

Cylinders with outer sealings in fluorocarbon rubber FPM


Stainless steel cylinders, see brochure for series P1S




Double-acting, cushioned stroke




Double-acting, adjustable cushioning




Double-acting, through piston rod



Single-acting, spring return



Single-acting, spring-extended



Double-acting, external guide device

Cylinder forces, double acting variants

Cyl. bore/ pist. rod mm	Stroke	Pistonarea cm ²	Max theoretical force in N (bar)									
			1,0	2,0	3,0	4,0	5,0	6,0	7,0	8,0		
10/4	+	0,8	8	16	24	31	39	47	55	63	71	79
	-	0,7	7	13	20	26	33	40	46	53	59	66
12/6	+	1,1	11	23	34	45	57	68	79	90	102	113
	-	0,8	8	17	25	34	42	51	59	68	76	85
16/6	+	2,0	20	40	60	80	100	120	141	161	181	201
	-	1,7	17	35	52	69	86	104	121	138	156	173
20/8	+	3,1	31	63	94	126	157	188	220	251	283	314
	-	2,6	26	53	79	106	132	158	185	211	238	264
25/10	+	4,9	49	98	147	196	245	295	344	393	442	491
	-	4,1	41	82	124	165	206	247	289	330	371	412

+ = Outward stroke
- = Return stroke

Note!
Select a theoretical force 50-100%
larger than the force required

Cylinder forces single acting variants

Indicated cylinder forces are theoretical and should be reduced according to the working conditions.

Order code	Theoretical piston force at 6 bar				Order code	Theoretical piston force at 6 bar				Order code	Theoretical piston force at 6 bar				
	Nmax	Nmin	Spring retraction			Nmax	Nmin	Spring retraction			Nmax	Nmin	Spring retraction		
Single acting, spring return								Single acting, spring-extended							
P1A-S010SS-0010	38	36	10	8,5	P1A-S016TS-0010	85	84	22,3	20,2	P1A-S020TS-0010	132	130	30	28	
P1A-S010SS-0015	38	36	10	7,8	P1A-S016TS-0015	86	84	22,3	19	P1A-S020TS-0015	133	130	30	27	
P1A-S010SS-0025	39	36	10	6,6	P1A-S016TS-0025	88	84	22,3	17	P1A-S020TS-0025	135	130	30	25	
P1A-S010SS-0040	38	34	13	9	P1A-S016TS-0040	90	84	22,3	14	P1A-S020TS-0040	138	130	30	22	
P1A-S010SS-0050	39	34	13	8	P1A-S016TS-0050	91	84	22,3	12	P1A-S020TS-0050	140	130	30	20	
P1A-S010SS-0080	39	34	12	7	P1A-S020TS-0080	139	108	31	17	P1A-S020TS-0080	139	108	31	17	
P1A-S012SS-0010	53	51	16	14,4	P1A-S025TS-0010	205	203	38,5	36	P1A-S025TS-0015	207	203	38,5	34,7	
P1A-S012SS-0015	53	51	16	13,6	P1A-S025TS-0025	210	203	38,5	32	P1A-S025TS-0025	210	203	38,5	32	
P1A-S012SS-0025	55	51	16	12	P1A-S025TS-0040	214	203	38,5	28,5	P1A-S025TS-0040	214	203	38,5	28,5	
P1A-S012SS-0040	52	48	19	13,4	P1A-S025TS-0050	217	203	38,5	26	P1A-S025TS-0050	217	203	38,5	26	
P1A-S012SS-0050	53	48	19	12	P1A-S025TS-0080	223	206	36	21	P1A-S025TS-0080	223	206	36	21	
P1A-S012SS-0080	55	48	21,4	12											
P1A-S016SS-0010	102	99	22,3	20,2											
P1A-S016SS-0015	103	99	22,3	19											
P1A-S016SS-0025	105	99	22,3	17											
P1A-S016SS-0040	106	95	22,3	14											
P1A-S016SS-0050	108	95	22,3	12											
P1A-S016SS-0080	107	95	22,5	12											
P1A-S020SS-0010	163	161	30	28											
P1A-S020SS-0015	164	161	30	27											
P1A-S020SS-0025	167	161	30	25											
P1A-S020SS-0040	166	159	30	22											
P1A-S020SS-0050	168	159	30	20											
P1A-S020SS-0080	170	161	29,4	18											
P1A-S025SS-0010	256	253	44,3	41,4											
P1A-S025SS-0015	258	253	44,3	40											
P1A-S025SS-0025	262	253	44,3	37											
P1A-S025SS-0040	261	250	44,3	32											
P1A-S025SS-0050	264	250	44,3	30											
P1A-S025SS-0080	264	251	44,4	30											

Main data

Cylinder designation	Cylinder bore	area	Piston rod bore	area	thread	Total mass at 0 mm stroke	addition per 10 mm stroke	Air consumption	Conn. thread
	mm	cm ²	mm	cm ²		kg	kg	litres	
Double acting, cushioned stroke									
P1A-S010D	10	0,78	4	0,13	M4	0,04	0,003	0,0100 ¹⁾	M5
P1A-S012D	12	1,13	6	0,28	M6	0,07	0,004	0,0139 ¹⁾	M5
P1A-S016D	16	2,01	6	0,28	M6	0,09	0,005	0,0262 ¹⁾	M5
P1A-S020D	20	3,14	8	0,50	M8	0,18	0,007	0,0405 ¹⁾	G1/8
P1A-S025D	25	4,91	10	0,78	M10x1,25	0,25	0,011	0,0633 ¹⁾	G1/8
Double acting, adjustable cushioning									
P1A-S016M	16	2,01	6	0,28	M6	0,09	0,005	0,0262 ¹⁾	M5
P1A-S020M	20	3,14	8	0,50	M8	0,18	0,007	0,0405 ¹⁾	G1/8
P1A-S025M	25	4,91	10	0,78	M10x1,25	0,25	0,011	0,0633 ¹⁾	G1/8
Single acting, spring return									
P1A-S010SS	10	0,78	4	0,13	M4	0,04	0,003	0,0055 ¹⁾	M5
P1A-S012SS	12	1,13	6	0,28	M6	0,08	0,004	0,0079 ¹⁾	M5
P1A-S016SS	16	2,01	6	0,28	M6	0,10	0,005	0,0141 ¹⁾	M5
P1A-S020SS	20	3,14	8	0,50	M8	0,18	0,007	0,0220 ¹⁾	G1/8
P1A-S025SS	25	4,91	10	0,78	M10x1,25	0,26	0,011	0,0344 ¹⁾	G1/8
Single acting, spring-extended									
P1A-S016TS	16	2,01	6	0,28	M6	0,10	0,005	0,0141 ¹⁾	M5
P1A-S020TS	20	3,14	8	0,50	M8	0,18	0,007	0,0220 ¹⁾	G1/8
P1A-S025TS	25	4,91	10	0,78	M10x1,25	0,26	0,011	0,0344 ¹⁾	G1/8

1) Free air consumption per 10 mm stroke length for a double stroke at 6 bar

Working medium, air quality

Working medium Dry, filtered compressed air to ISO 8573-1 class 3.4.3.

Recommended air quality for cylinders

For best possible service life and trouble-free operation, ISO 8573-1 quality class 3.4.3 should be used. This means 5 µm filter (standard filter) dew point +3 °C for indoor operation (a lower dew point should be selected for outdoor operation) and oil concentration 1.0 mg oil/m³, which is what a standard compressor with a standard filter gives.

ISO 8573-1 quality classes

Quality class	Pollution particle size (µm)	max concentration (mg/m ³)	Water max. press. dew point (°C)	Oil max concentration (mg/m ³)
1	0,1	0,1	-70	0,01
2	1	1	-40	0,1
3	5	5	-20	1,0
4	15	8	+3	5,0
5	40	10	+7	25
6	-	-	+10	-

Additional data

Working pressure	max 10 bar
Working temperature	max +80 °C min -20 °C

High-temperature version (Ø12, 16, 20 and 25 mm)min	max +150 °C -10 °C
--	-----------------------

Prelubricated, further lubrication is not normally necessary. If additional lubrication is introduced it must be continued.

Material specification

Piston rod	Stainless steel, DIN X 10 CrNiS 18 9
Piston rod seal	Nitrile rubber, NBR
Piston rod bearing	Multilayer PTFE/steel
End covers	Anodized aluminium
O-ring, internal	Nitrile rubber, NBR
Cylinder barrel	Stainless steel, DIN X 5 CrNi 18 10
Piston, complete	Nitrile rubber, NBR/steel
Magnet holder	Thermoplastic elastomer
Magnet	Plastic-coated magnetic material
Return spring	Surface-treated steel
Cushioning screw	Stainless steel, DIN X 10 CrNiS 18 9

Variants Mini ISO:

Low-temperature version, type L:

Piston rod seal	Nitrile rubber, NBR
Piston complete	Nitrile rubber, NBR/steel

High-temperature version, type F:

Piston rod seal	Fluorocarbon rubber, FPM
Piston complete	HNBR/steel

Cylinders with outer sealings in fluorcarbon, type V:

Piston rod seal/ Scraper ring	Fluorocarbon rubber, FPM
----------------------------------	--------------------------

Spare part = new cylinder

Cushioning diagram


Use the diagram below to determine the necessary size of cylinder to provide the requisite cushioning performance. The maximum cushioning performance, as indicated in the diagram, is based on the following assumptions:

- Low load, i.e. low pressure drop across the piston
- Steady-state piston speed
- Correctly adjusted cushioning screw

The load is the sum of the internal and external friction, together with any gravity forces. At high relative loading it is recommended that, for a given speed, the load should be reduced by a factor of 2.5, or that, for a given mass, the speed should be reduced by a factor of 1.5. These factors apply in relation to the maximum performance as shown in the diagram.


Fixed end-cushioning

Speed [m/s]



Adjustable pneumatic end-cushioning

Speed [m/s]




Dimensions**Double and single acting cylinders****CAD drawings on the Internet**




Our home page www.parker.com/euro_pneumatic includes the AirCad Drawing Library with 2D and 3D drawings for the main versions.

AirCad™
Drawing Library

Single Acting type T



Through piston rod



Cylinder bore mm	AM 0/-2 mm	BE	AF mm	BF mm	C mm	CDH9 mm	EE mm	EW mm	H mm	KK	L mm	SW mm	WH±1,2 mm
10	12	M12x1,25	12	10	13,0	4	M5	8	13,0	M4	6	—	16
12	16	M16x1,5	18	13	17,8	6	M5	12	17,8	M6	9	5	22
16 ¹⁾	16	M16x1,5	18	13	17,8	6	M5	12	17,8	M6	9	5	22
16 ²⁾	16	M16x1,5	18	13	23,8	6	M5	12	23,8	M6	9	5	22
20	20	M22x1,5	20	14	23,8	8	G1/8	16	23,8	M8	12	7	24
25	22	M22x1,5	22	14	26,8	8	G1/8	16	26,8	M10x1,25	12	9	28

1) P1A-S016DS/SS/TS

2) P1A-S016MS

Double acting cylinders

Cylinder bore mm	XC mm	ZJ mm	P mm
10	64 + stroke	84 + stroke	46 + stroke
12	75 + stroke	99 + stroke	48 + stroke
16	82 + stroke	104 + stroke	53 + stroke
20	95 + stroke	125 + stroke	67 + stroke
25	104 + stroke	132 + stroke	68 + stroke

Single-acting, spring return, type SS

Stroke/ Cylinder bore mm	10 XC mm	15 XC mm	25 XC mm	40 XC mm	50 XC mm	80 XC mm	10 ZJ mm	15 ZJ mm	25 ZJ mm	40 ZJ mm	50 ZJ mm	80 ZJ mm	10 P mm	15 P mm	25 P mm	40 P mm	50 P mm	80 P mm
10	74	79	89	126	136	174	94	99	109	146	156	194	56	61	71	108	118	156
12	85	90	100	132	142	185	109	114	124	156	166	209	58	63	73	105	115	158
16	92	97	107	122	132	184	114	119	129	144	154	206	63	68	78	93	103	155
20	105	110	120	135	145	191	135	140	150	165	175	221	77	82	92	107	117	163
25	114	119	129	144	154	201	142	147	157	172	182	229	78	83	93	108	118	165

Single-acting, spring-extended, type TS

Stroke/ Cylinder bore mm	10 XC ³⁾ mm	15 XC ³⁾ mm	25 XC ³⁾ mm	40 XC ³⁾ mm	50 XC ³⁾ mm	80 XC ³⁾ mm	10 ZJ ³⁾ mm	15 ZJ ³⁾ mm	25 ZJ ³⁾ mm	40 ZJ ³⁾ mm	50 ZJ ³⁾ mm	80 ZJ ³⁾ mm	10 P mm	15 P mm	25 P mm	40 P mm	50 P mm	80 P mm
16	107	112	122	137	147	—	129	134	144	159	169	—	78	83	93	108	118	—
20	120	125	135	150	160	195	150	155	165	180	190	225	92	97	107	122	132	167
25	129	134	144	159	169	205	157	162	172	187	197	233	93	98	108	123	133	169

3) With piston rod retracted, as shown in the dimension drawing

Length tolerances ±1 mm

Stroke length tolerances +1,5/0 mm

Guide for selecting suitable tubing

The selection of the correct size of tubing is often based on experience, with no great thought to optimizing energy efficiency and cylinder velocity. This is usually acceptable, but making a rough calculation can result in worthwhile economic gains.

The following is the basic principle:


1. The primary line to the working valve could be over sized (this does not cause any extra air consumption and consequently does not create any extra costs in operation).
2. The tubes between the valve and the cylinder should, however, be optimized according to the principle that an insufficient bore throttles the flow and thus limits the cylinder speed, while an oversized pipe creates a dead volume which increases the air consumption and filling time.

The chart below is intended to help when selecting the correct size of tube to use between the valve and the cylinder.

The following prerequisites apply:

The *cylinder load* should be about 50% of the theoretical force (= normal load). A lower load gives a higher velocity and vice versa. The tube size is selected as a function of the *cylinder bore*, the desired *cylinder velocity* and the *tube length* between the valve and the cylinder.

If you want to use the capacity of the valve to its maximum, and obtain maximum speed, the tubing should be chosen so that they at least correspond with the equivalent restriction diameter (see description below), so that the tubing does not restrict the total flow. This means that a short tubing must have at least the equivalent restriction diameter. If the tubing is longer, choose it from the table below. Straight fittings should be chosen for highest flow rates. (Elbow and banjo fittings cause restriction.)



- 1) The "equivalent throttling bore" is a long throttle (for example a tube) or a series of throttles (for example, through a valve) converted to a short throttle which gives a corresponding flow rate. This should not be confused with the "orifice" which is sometimes specified for valves. The value for the orifice does not normally take account of the fact that the valve contains a number of throttles.
- 2) Qn is a measure of the valve flow capacity, with flow measured in litre per minute (l/min) at 6 bar(e) supply pressure and 1 bar pressure drop across the valve.

Example ①: Which tube diameter should be used?

A 50 mm bore cylinder is to be operated at 0.5 m/s. The tube length between the valve and cylinder is 2 m. In the diagram we follow the line from 50 mm bore to 0.5 m/s and get an "equivalent throttling bore" of approximately 4 mm. We continue out to the right in the chart and intersect the line for a 2 m tube between the curves for 4 mm (6/4 tube) and 6 mm(8/6 tube). This means that a 6/4 tube throttles the velocity somewhat, while an 8/6 tube is a little too large. We select the 8/6 tube to obtain full cylinder velocity.

Example ②: What cylinder velocity will be obtained?

A 80 mm bore cylinder will be used, connected by 8 m 12/10 tube to a P2L-B valve. What cylinder velocity will we get? We refer to the diagram and follow the line from 8 mm tube length up to the curve for 12/10 tube. From there, we go horizontally to the curve for the Ø80 cylinder. We find that the velocity will be about 0.5 m/s.

Example ③: What is the minimum inner diameter and maximum lenght of tube?

For a application a 125 mm bore cylinder will be used. Maximum velocity of piston rod is 0.5 m/s. The cylinder will be controlled by a P2L-D valve. What diameter of tube can be used and what is maximum lenght of tube.
We refer to the diagram. We start at the left side of the diagram cylinder Ø125. We follow the line until the intersection with the velocity line of 0.5 m/s. From here we draw a horizontal line in the diagram. This line shows us we need an equivalent throttling bore of approximately 10 mm. Following this line horizontally we cross a few intersections. These intersections shows us the minimum inner diameter (rightside diagram) in combination with the maximum length of tube (bottomside diagram).

For example:

Intersection one: When a tube (14/11) will be used, the maximum length of tube is 0.7 meter.

Intersection two: When a tube (—/13) will be used, the maximum length of tube is 3.7 meter.

Intersection three: When a tube (—/14) will be used, the maximum length of tube is 6 meter.

Example ④: Determining tube size and cylinder**velocity with a particular cylinder and valve?**

For an application using a 40 mm bore cylinder with a valve with $Q_n=800$ NL/min. The distance between the cylinder and valve has been set to 5 m.

Tube dimension: What tube bore should be selected to obtain the maximum cylinder velocity? Start at pipe length 5 m, follow the line up to the intersection with 800 NL/min. Select the next largest tube diameter, in this case Ø10/8 mm.

Cylinder velocity: What maximum cylinder velocity will be obtained? Follow the line for 800 NL/min to the left until it intersects with the line for the Ø40 mm cylinder. In this example, the speed is just above 1.1 m/s.

Valve series with respective flows in NL/minute

Valve series	Qn in NL/Min
Valvetronic Solstar	33
Interface PS1	100
Adex A05	173
Moduflex size 1, (2 x 3/2)	220
Valvetronic PVL-B 5/3 closed centre, 6 mm push in	290
Moduflex size 1, (4/2)	320
B43 Manual and mechanical	340
Valvetronic PVL-B 2 x 2/3, 6 mm push in	350
Valvetronic PVL-B 5/3 closed centre, G1/8	370
Compact Isomax DX02	385
Valvetronic PVL-B 2 x 3/2 G1/8	440
Valvetronic PVL-B 5/2, 6 mm push in	450
Valvetronic PVL-B 5/3 vented centre, 6 mm push in	450
Moduflex size 2, (2 x 3/2)	450
Flowstar P2V-A	520
Valvetronic PVL-B 5/3 vented centre, G1/8	540
Valvetronic PVL-B 5/2, G1/8	540
Valvetronic PVL-C 2 x 3/2, 8 mm push in	540
Adex A12	560
Valvetronic PVL-C 2 x 3/2 G1/8	570
Compact Isomax DX01	585
VIKING Xtreme P2LAX	660
Valvetronic PVL-C 5/3 closed centre, 8 mm push in	700
Valvetronic PVL-C 5/3 vented centre, G1/4	700
B3-Series	780
Valvetronic PVL-C 5/3 closed centre, G1/4	780
Moduflex size 2, (4/2)	800
Valvetronic PVL-C 5/2, 8 mm push in	840
Valvetronic PVL-C 5/3 vented centre, 8 mm push in	840
Valvetronic PVL-C 5/2, G1/4	840
Flowstar P2V-B	1090
ISOMAX DX1	1150
B53 Manual and mechanical	1160
B4-Series	1170
VIKING Xtreme P2LCX, G3/8	1290
B5-Series, G1/4	1440
Airline Isolator Valve VE22/23	1470
ISOMAX DX2	2330
VIKING Xtreme P2LDX, G1/2	2460
ISOMAX DX3	2660
Airline Isolator Valve VE42/43	4050
Airline Isolator Valve VE82/83	5520
	13680

Order key

P1A - S	016	M	S	-	0025
Cylinder bore mm	Cylinder type / function				
010	M Double-acting, adjustable cushioning, Ø16-25 mm. Not for sealing material type F and L				
012	D Double-acting, non-adjustable cushioning, Ø10 - Ø25				
016	F Double-acting, adjustable cushioning, thru-rod, Ø16-25 mm. Not for sealing material type F				
020	K Double-acting, non-adjustable cushioning, thru-rod, Ø10 - Ø25				
025	S Single-acting, non-adjustable cushioning, spring return for retract stroke, Ø10-25 mm				
	T Single-acting, non-adjustable cushioning, spring return for advance stroke, Ø16-25 mm				
	Stroke length, mm				
	E.g. 0025 = 25 mm For standard stroke length and max length see table below.				
	Sealing material				
	S Standard, -20 °C to +80 °C. Magnetic piston				
	F High temperature, Ø12, 16, 20 and 25 mm -10 °C to +150 °C. Non-magnetic piston				
	V External seals of fluorinated rubber. -20 °C to +80 °C. Magnetic piston				

Stroke length

Cylinder designation	Cylinder bore	● Standard stroke length in mm	10	15	20	25*	30	40	50*	80*	100*	125*	160*	200*	250*	320*	400*	500*	Non standard stroke length
Double acting with fixed end-cushioning:																			
P1A-S010D	10	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
P1A-S012D	12	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
P1A-S016D	16	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
P1A-S020D	20	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	**
P1A-S025D	25	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	**
Double acting with adjustable end-cushioning:																			
P1A-S016M	16	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
P1A-S020M	20	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	**
P1A-S025M	25	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	**
Single acting, spring return:																			
P1A-S010SS	10	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
P1A-S012SS	12	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
P1A-S016SS	16	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
P1A-S020SS	20	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
P1A-S025SS	25	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Single acting, spring-extended:																			
P1A-S016TS	16	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
P1A-S020TS	20	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
P1A-S025TS	25	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	

* Standard stroke lengths in mm according to ISO 4393

** Max stroke 1000 mm


Data

Working pressure
Working temperature

max. 10 bar
max. +80 °C
min. -20 °C



**Single-acting
spring return
Fixed end cushioning**



Cyl.bore mm	Stroke mm	Order code
10 Conn. M5	10	P1A-S010SS-0010
	15	P1A-S010SS-0015
	25	P1A-S010SS-0025
	40	P1A-S010SS-0040
	50	P1A-S010SS-0050
	80	P1A-S010SS-0080
12 Conn. M5	10	P1A-S012SS-0010
	15	P1A-S012SS-0015
	25	P1A-S012SS-0025
	40	P1A-S012SS-0040
	50	P1A-S012SS-0050
	80	P1A-S012SS-0080
16 Conn. M5	10	P1A-S016SS-0010
	15	P1A-S016SS-0015
	25	P1A-S016SS-0025
	40	P1A-S016SS-0040
	50	P1A-S016SS-0050
	80	P1A-S016SS-0080
20 Conn. G1/8	10	P1A-S020SS-0010
	15	P1A-S020SS-0015
	25	P1A-S020SS-0025
	40	P1A-S020SS-0040
	50	P1A-S020SS-0050
	80	P1A-S020SS-0080
25 Conn. G1/8	10	P1A-S025SS-0010
	15	P1A-S025SS-0015
	25	P1A-S025SS-0025
	40	P1A-S025SS-0040
	50	P1A-S025SS-0050
	80	P1A-S025SS-0080

Cylinders are supplied complete with neck mounting and piston rod nuts.

**Single-acting
spring-extended
Fixed end cushioning**




Cyl.bore mm	Stroke mm	Order code
16 Conn. M5	10	P1A-S016TS-0010
	15	P1A-S016TS-0015
	25	P1A-S016TS-0025
	40	P1A-S016TS-0040
	50	P1A-S016TS-0050
	80	P1A-S016TS-0080
20 Conn. G1/8	10	P1A-S020TS-0010
	15	P1A-S020TS-0015
	25	P1A-S020TS-0025
	40	P1A-S020TS-0040
	50	P1A-S020TS-0050
	80	P1A-S020TS-0080
25 Conn. G1/8	10	P1A-S025TS-0010
	15	P1A-S025TS-0015
	25	P1A-S025TS-0025
	40	P1A-S025TS-0040
	50	P1A-S025TS-0050
	80	P1A-S025TS-0080


Cylinders are supplied complete with neck mounting and piston rod nuts.

Data

Working pressure max. 10 bar
 Working temperature max. +80 °C
 min. -20 °C

**Double-acting****Fixed end cushioning**

Cyl.bore mm	Stroke mm	Order code
10 Conn. M5	10	P1A-S010DS-0010
	15	P1A-S010DS-0015
	20	P1A-S010DS-0020
	25	P1A-S010DS-0025
	30	P1A-S010DS-0030
	40	P1A-S010DS-0040
	50	P1A-S010DS-0050
	80	P1A-S010DS-0080
	100	P1A-S010DS-0100
	125	P1A-S010DS-0125
Max stroke 500 mm		
12 Conn. M5	10	P1A-S012DS-0010
	15	P1A-S012DS-0015
	20	P1A-S012DS-0020
	25	P1A-S012DS-0025
	30	P1A-S012DS-0030
	40	P1A-S012DS-0040
	50	P1A-S012DS-0050
	80	P1A-S012DS-0080
	100	P1A-S012DS-0100
	125	P1A-S012DS-0125
Max stroke 500 mm		
16 Conn. M5	10	P1A-S016DS-0010
	15	P1A-S016DS-0015
	20	P1A-S016DS-0020
	25	P1A-S016DS-0025
	30	P1A-S016DS-0030
	40	P1A-S016DS-0040
	50	P1A-S016DS-0050
	80	P1A-S016DS-0080
	100	P1A-S016DS-0100
	125	P1A-S016DS-0125
Max stroke 500 mm		

Fixed end cushioning


Cyl.bore mm	Stroke mm	Order code
20 Conn. G1/8	10	P1A-S020DS-0010
	15	P1A-S020DS-0015
	20	P1A-S020DS-0020
	25	P1A-S020DS-0025
	30	P1A-S020DS-0030
	40	P1A-S020DS-0040
	50	P1A-S020DS-0050
	80	P1A-S020DS-0080
	100	P1A-S020DS-0100
	125	P1A-S020DS-0125
Max stroke 1000 mm		
25 Conn. G1/8	10	P1A-S025DS-0010
	15	P1A-S025DS-0015
	20	P1A-S025DS-0020
	25	P1A-S025DS-0025
	30	P1A-S025DS-0030
	40	P1A-S025DS-0040
	50	P1A-S025DS-0050
	80	P1A-S025DS-0080
	100	P1A-S025DS-0100
	125	P1A-S025DS-0125
Max stroke 1000 mm		

Cylinders are supplied complete with neck mounting and piston rod nuts.

Cylinders with Through piston rods are supplied with two piston rod nuts and one neck mounting nut.

Data



Working pressure max. 10 bar
 Working temperature max. +80 °C
 min. -20 °C

**Double-acting****Adjustable cushioning**

Cyl.bore mm	Stroke mm	Order code	Cyl.bore mm	Stroke mm	Order code
16 Conn. M5	20	P1A-S016MS-0020	25 Conn. G1/8	20	P1A-S025MS-0020
	25	P1A-S016MS-0025		25	P1A-S025MS-0025
	30	P1A-S016MS-0030		30	P1A-S025MS-0030
	40	P1A-S016MS-0040		40	P1A-S025MS-0040
	50	P1A-S016MS-0050		50	P1A-S025MS-0050
	80	P1A-S016MS-0080		80	P1A-S025MS-0080
	100	P1A-S016MS-0100		100	P1A-S025MS-0100
	125	P1A-S016MS-0125		125	P1A-S025MS-0125
	160	P1A-S016MS-0160		160	P1A-S025MS-0160
	200	P1A-S016MS-0200		200	P1A-S025MS-0200
	250	P1A-S016MS-0250		250	P1A-S025MS-0250
	320	P1A-S016MS-0320		320	P1A-S025MS-0320
	400	P1A-S016MS-0400		400	P1A-S025MS-0400
Max stroke 500 mm	500	P1A-S016MS-0500	Max stroke 1000 mm	500	P1A-S025MS-0500
20 Conn. G1/8	20	P1A-S020MS-0020			
	25	P1A-S020MS-0025			
	30	P1A-S020MS-0030			
	40	P1A-S020MS-0040			
	50	P1A-S020MS-0050			
	80	P1A-S020MS-0080			
	100	P1A-S020MS-0100			
	125	P1A-S020MS-0125			
	160	P1A-S020MS-0160			
	200	P1A-S020MS-0200			
	250	P1A-S020MS-0250			
	320	P1A-S020MS-0320			
	400	P1A-S020MS-0400			
Max stroke 1000 mm	500	P1A-S020MS-0500			

Cylinders are supplied complete with neck mounting and piston rod nuts.

Cylinders with Through piston rods are supplied with two piston rod nuts and one neck mounting nut.

U style**H style**

P1A with rod guidance modules

The P1A series cylinders can be equipped with an external guiding device to prevent the piston rod from turning. When fitted the guide provides a guided piston movement enabling the cylinder to resist turning moments on the piston rod, as well as greater transverse forces. Rod guides are available with plain bearings as U style or linear ball bearings as H style.

The bracket, which has pre-drilled mounting holes, is connected to the piston rod by means of a flexocoupling, which prevents the build-up of stress in the cylinder.

P1A cylinders with guiding device are available with bores from 12 to 25 mm, and stroke lengths up to 250 mm. Separate guiding device kits can be supplied on request according to the order key below.

Technical data

Working pressure
Working temperature

max 10 bar
-20 °C to +80 °C

Material specifications, guidance modules



Body	Anodised aluminium
Guide bars, H style	Hardened stainless steel
Front plate	Anodised aluminium
Guide bars, U style	Stainless steel
Front plate	Zinc-plated steel
Plain bearings	Bronze

Other data as standard cylinder.


Order key

P1A	-	4 D R H	-	XXX
Cylinder version		Bore size mm		Guide module type
A Mini ISO cylinders		D 12, 16		H H style, ball bearings
		H 20		K U style, plain bearings
		J 25		
				Stroke length (mm)
				Same as for the cylinder

Transverse force as a function of load distance



Dimensions, U style guidance modules, plain bearings




Cyl. bore	A1	A2	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	C1	C2	D1	D2	D3	D4
12/16	30	65	27	63	32	25,0	54	7,5	10	24	15	22	8	46	4,5	8,0	5,5	-
20	34	79	32	76	40	32,5	68	14,0	12	38	20	23	10	58	5,5	10,5	6,5	11
25	34	79	32	76	40	32,5	68	14,0	12	38	20	23	10	58	5,5	10,5	6,5	11

Cyl. bore	D5	D6	E1	E2	E3	F1	G1	L1	L2	L3	L5	SW1	SW2	SW3	R1	R2	H1	H2
12/16	M4	M4	8	4,6	-	16	16	69	39	17	52	22	8	19	M4	8	46	20
20	M5	M6	12	5,6	7	22	30	85	55	15	70	30	13	27	M6	11	58	30
25	M5	M6	12	5,6	7	22	23	85	55	15	70	30	13	27	M6	11	58	30

Cyl. bore	Weight stroke 0 mm kg	Additional weight per 10 mm stroke kg
12/16	0,26	0,0078
20	0,47	0,1233
25	0,47	0,1233

S = Stroke

Dimensions, H style guidance modules, ball bearings



Cyl. bore	A1	A2	B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	C1	C2	C3	D1	D2	D3
12/16	30	65	27	63	32	32,5	54	13	10	24	15	22	8	46	27	4,5	8,0	5,5
20	34	79	32	76	40	32,5	68	21	12	38	20	23	10	58	37	5,5	10,5	6,5
25	34	79	32	76	40	32,5	68	21	12	38	20	23	10	58	37	5,5	10,5	6,5

Cyl. bore	D4	D5	D6	E1	E2	E3	F1	G1	L1	L2	L3	L4	L5	SW1	SW2	SW3	R1	R2
12/16	9	M4	M4	8	4,6	6	16	16	130	75	44	35	51	22	8	19	M4	8
20	11	M5	M6	12	5,6	7	22	30	160	108	43	52	65	30	13	27	M6	11
25	11	M5	M6	12	5,6	7	22	23	160	108	43	52	65	30	13	27	M6	11

Cyl. bore	H1	H2	H3
12/16	46	-3,25	8,5
20	58	4,75	15,0
25	58	4,75	15,0

Cyl. bore	Weight stroke 0 mm kg	Additional weight per 10 mm stroke kg
12/16	0,43	0,0078
20	0,77	0,1233
25	0,77	0,1233

S = Stroke

Cylinder mountings

Type	Description	Cyl. bore Ø mm	Weight kg	Order code
Flange-MF8	Intended for fixed attachment of the cylinder. The flange is designed for mounting on the front or rear end-covers.	10 12-16 20-25	0,012 0,025 0,045	P1A-4CMB P1A-4DMB P1A-4HMB



Material:
Surface-treated steel


Stainless Flange-MF8

Intended for fixed attachment of the cylinder. The flange is designed for mounting on the front or rear end-covers.	10 12-16 20-25	0,012 0,025 0,045	P1S-4CMB P1S-4DMB P1S-4HMB
---	----------------------	-------------------------	---



Material:
Stainless steel, DIN X 10 CrNiS 18 9

Cylinder Ø mm	A mm	B mm	C mm	D mm	E mm	F mm
10	4,5	30	40	22	3	13
12-16	5,5	40	52	30	4	18
20	6,6	50	66	40	5	19
25	6,6	50	66	40	5	23

**Foot-MS3**

Intended for fixed attachment of the cylinder. The bracket is designed for mounting on the front or rear end-covers.	10 12-16 20-25	0,020 0,040 0,080	P1A-4CMF P1A-4DMF P1A-4HMF
--	----------------------	-------------------------	---



Material:
Surface-treated steel


Stainless Foot-MS3

Intended for fixed attachment of the cylinder. The bracket is designed for mounting on the front or rear end-covers.	10 12-16 20-25	0,020 0,040 0,080	P1S-4CMF P1S-4DMF P1S-4HMF
--	----------------------	-------------------------	---



Material:
Stainless steel, DIN X 10 CrNiS 18 9


Cylinder Ø mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm
10	4,5	16	25	35	3	24	26,0	16	11
12-16	5,5	20	32	42	4	32	32,5	20	14
20	6,5	25	40	54	5	36	45,0	25	17
25	6,5	25	40	54	5	40	45,0	25	17



Cylinder mountings


Type	Description	Cyl. bore Ø mm	Weight kg	Order code
Cover trunnion	Intended for articulated mounting of the cylinder. The flange is designed for mounting on the front or rear end-covers. Material: Surface-treated steel	10 12-16 20-25	0,014 0,033 0,037	P1A-4CMJZ P1A-4DMJZ P1A-4HMJZ

Cylinder Ø mm	A mm	B h14 mm	C mm	D mm	E1 mm	F e9 mm	G mm	H mm
10	12,5	26	38	20	9	4	6	10
12-16	16,5	38	58	25	13	6	8	14
20	22,5	46	66	30	13	6	8	16
25	22,5	46	66	30	13	6	8	20




Cover trunnion Stainless steel	Intended for articulated mounting of the cylinder. The flange is designed for mounting on the front or rear end-covers. Material: Stainless steel, DIN X 10 CrNiS 18 9	10 12-16 20-25	0,014 0,033 0,037	P1A-4CMJ P1A-4DMJ P1A-4HMJ
---	--	----------------------	-------------------------	---

Cylinder Ø mm	A mm	B h14 mm	C mm	D mm	E mm	F e9 mm	G mm	H mm
10	12,5	26	38	20	8	4	6	10
12-16	16,5	38	58	25	10	6	8	14
20	22,5	46	66	30	10	6	8	16
25	22,5	46	66	30	10	6	8	20



Stainless Mounting nut	Intended for fixed mounting of the cylinder. Cylinders are supplied complete with one mounting nut. Material: Stainless steel, DIN X 5 CrNi 18 10	10 12-16 20-25	0,009 0,018 0,042	9126725405 9126725406 9126725407
-------------------------------	--	----------------------	-------------------------	---

Cylinder Ø mm	A mm	B mm	C mm
10	19	6	M12x1,25
12-16	24	8	M16x1,50
20-25	32	11	M22x1,50




Cylinder mountings

Type	Description	Cyl. bore Ø mm	Weight kg	Order code
Clevis bracket	Intended for articulated mounting of the cylinder. Supplied with shaft for mounting on the rear end cover.	10 12-16 20-25	0,020 0,040 0,080	P1A-4CMT P1A-4DMT P1A-4HMT
	Material: Bracket: surface-treated steel, black Pin: surface hardened steel Circlips: according to DIN 471: Stainless steel			
Clevis bracket	Intended for articulated mounting of the cylinder. Supplied with shaft for mounting on the rear end cover.	10 12-16 20-25	0,020 0,040 0,080	P1S-4CMT P1S-4DMT P1S-4HMT
	Material: Bracket: stainless steel, DIN X 5 CrNi 18 10 Pin: tempered stainless steel, DIN X 20 Cr 13 Locking rings: stainless steel, DIN X 5 CrNi 18 10			


Cylinder Ø mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I °	J °
10	4,5	13	8	24	12,5	20	65,3	5	160	17
12	5,5	18	12	27	15,0	25	73,0	7	170	15
16	5,5	18	12	27	15,0	25	80,0	7	170	15
20	6,5	24	16	30	20,0	32	91,0	10	165	10
25	6,5	24	16	30	20,0	32	100,0	10	165	10

S=stroke



Clevis	According to ISO 8140 Intended for articulated mounting of the cylinder. This mounting is adjustable in the axial direction. Supplied complete with pin.	10 12-16 20 25	0,007 0,022 0,045 0,095	P1A-4CRC P1A-4DRC P1A-4HRC P1A-4JRC
Stainless Clevis	According to ISO 8140 Intended for articulated mounting of the cylinder. This mounting is adjustable in the axial direction. Supplied complete with pin.	10 12-16 20 25	0,007 0,022 0,045 0,095	P1S-4CRC P1S-4DRC P1S-4HRC P1S-4JRC
	Material: Stainless steel, DIN X 5 CrNi 18 10			


Cylinder Ø mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	J mm
10	4	M4	2,2	8	8	5	16	4	22,0	2,0
12-16	6	M6	3,2	12	12	7	24	6	31,0	3,0
20	8	M8	4,0	16	16	10	32	8	40,5	3,5
25	10	M10x1,25	5,0	20	20	12	40	10	49,0	3,0



Cylinder mountings


Type	Description	Cyl. bore Ø mm	Weight kg	Order code
Swivel rod eye	According to ISO 8139 Intended for articulated mounting of the cylinder. This mounting is adjustable in the axial direction. Material: Swivel rod eye: Galvanized steel Ball: hardened steel	10 12-16 20 25	0,017 0,025 0,045 0,085	P1A-4CRS P1A-4DRS P1A-4HRS P1A-4JRS
Stainless Swivel rod eye	According to ISO 8139 Intended for articulated mounting of the cylinder. This mounting is adjustable in the axial direction. Material: Swivel rod eye: stainless steel, DIN X 5 CrNi 18 10 Ball: hardened stainless steel, DIN X 5 CrNi 18 10	10 12-16 20 25	0,017 0,025 0,045 0,085	P1S-4CRT P1S-4DRT P1S-4HRT P1S-4JRT

Cylinder Ø mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	J mm	K mm	L mm
10	5	M4	2,2	8	10	9	27	6,0	8	33,0	9	2,0
12-16	6	M6	3,2	9	10	10	30	6,8	9	38,5	11	1,5
20	8	M8	4,0	12	12	12	36	9,0	12	46,0	14	2,0
25	10	M10x1,25	5,0	14	14	14	43	10,5	15	52,5	17	2,5



Stainless Rod nut	Intended for fixed mounting on the piston rod. Cylinders are supplied complete with one rod nut. (cylinders with through piston rod are supplied with two rod nuts.) Material: Stainless steel, DIN X 5 CrNi 18 10	10 12-16 20 25	0,001 0,002 0,005 0,007	9127385121 9127385122 9127385123 9126725404
--------------------------	--	-------------------------	----------------------------------	--

Cylinder Ø mm	D mm	F mm	E mm
10	M4	7	2,2
12-16	M6	10	3,2
20	M8	13	4,0
25	M10x1,25	17	5,0



Our global series of sensors

This series of sensors is already being used or will be used in all future ranges in our global product programme involving cylinders/actuators. The sensors have small installation dimensions and either fit into the groove in the case profile or, as shown here, are fastened to the cylinder using a special attachment.

You can choose from electronic or reed sensors with a range of cable lengths fitted with 8 mm or M12 terminals.



Electronic sensors

The new electronic sensors are "Solid State", i.e. they have no moving parts at all. They are provided with short-circuit protection and transient protection as standard. The built-in electronics make the sensors suitable for applications with high on and off switching frequency, and where very long service life is required.

Technical data









Design	GMR (Giant Magnetic Resistance) magneto-resistive function
Installation	Sensor mounting P8S-TMC01
Outputs	PNP, normally open (also available in NPN design, normally closed, on request)
Voltage range	10-30 VDC 10-18 V DC, ATEX sensor
Ripple	max 10%
Voltage drop	max 2,5 V
Load current	max 100 mA
Internal consumption	max 10 mA
Actuating distance	min 9 mm
Hysteresis	max 1,5 mm
Repeatability accuracy	max 0,2 mm
On/off switching frequency	max 5 kHz
On switching time	max 2 ms
Off switching time	max 2 ms
Encapsulation	IP 67 (EN 60529)
Temperature range	-25 °C to +75 °C -20 °C to +45 °C, ATEX sensor
Indication	LED, yellow
Material housing	PA 12
Material screw	Stainless steel
Cable	PVC or PUR 3x0.25 mm ² see order code respectively

Reed sensors

The sensors are based on proven reed switches, which offer reliable function in many applications. Simple installation, a protected position on the cylinder and clear LED indication are important advantages of this range of sensors.

Technical data

Design	Reed element
Mounting	Sensor mounting P8S-TMC01
Output	Normally open , or normally closed
Voltage range	10-30 V AC/DC or 10-120 V AC/DC 24-230 V AC/DC
Load current	max 500 mA for 10-30 V or max 100 mA for 10-120 V max 30 mA for 24-230 V
Breaking power (resistive)	max 6 W/VA
Actuating distance	min 9 mm
Hysteresis	max 1,5 mm
Repeatability accuracy	0,2 mm
On/off switching frequency	max 400 Hz
On switching time	max 1,5 ms
Off switching time	max 0,5 ms
Encapsulation	IP 67 (EN 60529)
Temperature range	-25 °C to +75 °C
Indication	LED, yellow
Material housing	PA12
Material screw	Stainless steel
Cable	PVC or PUR 3x0.14 mm ² see order code respectively

Electronic sensors**Reed sensors****P8S-GCFPX****P8S-GRFLX / P8S-GRFLX2****Dimensions****Sensors****Sensor mounting P8S-TMC01**

Ordering data

Output/function	Cable/connector	Weight kg	Order code
Electronic sensors , 10-30 V DC			
PNP type, normally open	0,27 m PUR-cable and 8 mm snap-in male connector	0,007	P8S-GPSHX
PNP type, normally open	1,0 m PUR-cable and 8 mm snap-in male connector	0,013	P8S-GPSCX
PNP type, normally open	1,0 m PUR-cable and M8 screw male connector	0,013	P8S-GPCCX
PNP type, normally open	0,27 m PUR-cable and M12 screw male connector	0,015	P8S-GPMHX
PNP type, normally open	3 m PVC-cable without connector	0,030	P8S-GPFLX
PNP type, normally open	10 m PVC-cable without connector	0,110	P8S-GPFTX
Electronic sensor 18-30 V DC			
ATEX-certified			
 II3G EEx nA II T4X II3D 135 °C IP67			
Type PNP , normally open	3 m PVC-cable without connector	0,030	P8S-GPFLX/EX
Reed sensors , 10-30 V AC/DC			
Normally open	0,27 m PUR-cable and 8 mm snap-in male connector	0,007	P8S-GSSHX
Normally open	1,0 m PUR-cable and 8 mm snap-in male connector	0,013	P8S-GSSCX
Normally open	1,0 m PUR-cable and M8 male connector	0,013	P8S-GSCCX
Normally open	0,27 m PUR-cable and M12 screw male connector	0,015	P8S-GSMHX
Normally open	1,0 m PUR-cable and M12 screw male connector	0,023	P8S-GSMCX
Normally open	3 m PVC-cable without connector	0,030	P8S-GSFLX
Normally open	10 m PVC-cable without connector	0,110	P8S-GSFTX
Normally closed	5m PVC-cable without connector ¹⁾	0,050	P8S-GCFPX
Reed sensors, 10-120 V AC/DC			
Normally open	3 m PVC-cable without connector	0,030	P8S-GRFLX
Reed sensorer, 24-230 V AC/DC			
Normally open	3 m PVC-cable without connector	0,030	P8S-GRFLX2

1) Without LED

Sensor mounting


Description	Weight kg	Order code
Sensor mounting for cylinder P1A cylinder bore Ø10 to Ø25 mm	0,07	P8S-TMC01

Sensors for special applications


Sensors for applications where the short installation length and the 90 degree cable outlet are important factors. This type of sensor is a good alternative if a cylinder has a short stroke or tight installation, and installation is easier than our global series of sensors.

Electronic sensor symbol

P1A-2XMK



P1A-2XLK




Technical data

Design	Hall element
Output	PNP resp. NPN, N.O.
Voltage range	10-30 VDC
Max permissible ripple	10%
Max voltage drop	$\leq 0,5$ V at 100 mA
Max load current, P1A-2XMK, LK	150 mA
P1A-2XHK, EK, JH, FH	100 mA
Max breaking power (resistive)	6 W
Internal consumption	<30 mA at 30 V
Min actuating distance	5 mm
Hysteresis	1,1 - 1,3 mm
Repeatability accuracy	$\pm 0,1$ mm
Max on/off switching frequency	1 kHz
Max on/off switching time	0,8/3,0 μ s
Encapsulation, P1A-2XJH, FH	IP 65
Encapsulation, P1A-2XHK, EK, MK, LK	IP 67
Temperature range	-10 °C to +60 °C
Indication	LED
Shock resistance	40 g
Material, housing	Polyamid 11
Material, mould	Epoxy
Cable	PVC 3x0,15 mm ²
Cable incl. female part connector	PVC 3x0,15 mm ²
Connector	Diam. 8 mm snap on
Mounting	Mounting yoke
Material, mounting	Acetal/Stainless steel
Material, screw	Stainless steel


Dimensions

P1A-2XMK and P1A-2XLK



Ordering data

Output	Cable length	Weight kg	Order code
Electronic sensors			
PNP, N.O.	2 m	0,040	P1A-2XMK
NPN, N.O.	2 m	0,040	P1A-2XLK
Mountings for sensors			
For cylinder Ø10		0,005	P1A-2CCC
For cylinder Ø12		0,005	P1A-2DCC
For cylinder Ø16		0,008	P1A-2FCC
For cylinder Ø20		0,008	P1A-2HCC
For cylinder Ø25		0,010	P1A-2JCC



Connecting cables with one connector

The cables have an integral snap-in female connector.



Type of cable	Cable/connector	Weight kg	Order code
Cables for sensors, complete with one female connector			
Cable, Flex PVC	3 m, 8 mm Snap-in connector	0,07	9126344341
Cable, Flex PVC	10 m, 8 mm Snap-in connector	0,21	9126344342
Cable, Super Flex PVC	3 m, 8 mm Snap-in connector	0,07	9126344343
Cable, Super Flex PVC	10 m, 8 mm Snap-in connector	0,21	9126344344
Cable, Polyurethane	3 m, 8 mm Snap-in connector	0,01	9126344345
Cable, Polyurethane	10 m, 8 mm Snap-in connector	0,20	9126344346
Cable, Polyurethane	5 m, M12 screw connector	0,07	9126344348
Cable, Polyurethane	10 m, M12 screw connector	0,20	9126344349

Male connectors for connecting cables

Cable connectors for producing your own connecting cables. The connectors can be quickly attached to the cable without special tools. Only the outer sheath of the cable is removed. The connectors are available for M8 and M12 screw connectors and meet protection class IP 65.



Connector	Weight kg	Order code
M8 screw connector	0,017	P8SCS0803J
M12 screw connector	0,022	P8SCS1204J

Ready to use connecting cables with connectors at each end

As accessories the system comprises a large number of different cables in order to meet all requirements that may arise and to make the installation simple, fast and reliable.

Cables with moulded 8 mm snap-in round contacts in both ends. The cables are available in two types, one with a straight male and female connectors respectively, and one with a straight 3-pole male connector in one end and an angled 3-pole female connector in the other end.



Technical data

Contacts

Moulded 8 mm snap-in male/female contacts.

Enclosure IP67

Cable

Conductor 3x0,25 mm² (32x0,10 mm²)

Sheath PVC/PUR

Colour Black

Cables with straight 3-pole male and female connectors respectively.



Cables with a straight 3-pole male connector in one end and an angled 3-pole female connector in the other end.



Designation	Weight kg	Order code
Cable with straight contacts, 0,2 m	0,02	9121717014
Cable with straight contacts, 0,3 m	0,02	9121717015
Cable with straight contacts, 0,5 m	0,03	9121717016
Cable with straight contacts, 1,0 m	0,03	9121717017
Cable with straight contacts, 2,0 m	0,05	9121717018
Cable with straight contacts, 3,0 m	0,07	9121717019
Cable with straight contacts, 5,0 m	0,12	9121717020
Cable with straight contacts, 10 m	0,23	9121717021
Cable with straight and angled connectors, 0,2 m	0,02	9121717022
Cable with straight and angled connectors, 0,3 m	0,02	9121717023
Cable with straight and angled connectors, 0,5 m	0,03	9121717024
Cable with straight and angled connectors, 1,0 m	0,03	9121717025
Cable with straight and angled connectors, 2,0 m	0,05	9121717026
Cable with straight and angled connectors, 3,0 m	0,07	9121717027
Cable with straight and angled connectors, 5,0 m	0,12	9121717028
Cable with straight and angled connectors, 10 m	0,23	9121717029

Connection block Valvetronic 110

The Valvetronic 110 is a connection block that can be used for collecting signals from sensors at various points on a machine and connecting them to the control system via a multicore cable. Valvetronic 110 can also be used for central connection of the multi-core cable to the outputs of a control system, and can be laid to a machine where the output signals can be connected. The connection block has ten 8 mm snap-in circular connectors and a multi-core cable which is available in lengths of 3 or 10 m. The connections on the block are numbered from 1 to 10. Blanking plugs are available for unused connections, as labels for marking the connections of each block.

Technical data

Connections:

Ten 3-pole numbered 8 mm round snap-in female contacts

Input block

Pin 1	Common, +24 VDC
Pin 2	Input signal
Pin 3	Common, 0V

Output block

Pin 1	Common, GND
Pin 2	Output signal
Pin 3	Common, 0V

Electrical data:

Voltage	24 VDC (max. 60 V AC/75 V DC)
Insulation group	according to DIN 0110 class C
Load	max. 1 A per connection total max. 3 A


Cable:

Length	3 m or 10 m
Type of cable	LiYY11Y
Conductor	12
Area	0.34 mm ²
Colour marking	According to DIN 47 100

Ordering data

Designation	Weight kg	Order code
Connection block Valvetronic 110 with 3 m cable	0,32	9121719001
Connection block Valvetronic 110 with 10 m cable	0,95	9121719002
Blanking plugs (pack of 10) Use blanking plugs to close unused connections.	0,02	9121719003
Labels (pack of 10) White labels to insert in grooves on the side of the connection	0,02	9121719004

Dimensions and wiring diagrams



Mechanical data

Enclosure IP 67, DIN 40050 with fitted contacts and/or blanking plugs.


Temperature -20 °C to +70 °C

Material

Body	PA 6,6 VD according to UL 94
Contact holder	PBTP
Snap-in ring	LDPE
Moulding mass	Epoxy
Seal	NBR
Screws	Plated steel

Industrial durability

Good chemical and oil resistance. Tests should be performed in aggressive environments.



ConductorColour	Input	Output
1 Pink	Signal 1	Signal 1
2 Grey	Signal 2	Signal 2
3 Yellow	Signal 3	Signal 3
4 Green	Signal 4	Signal 4
5 White	Signal 5	Signal 5
6 Red	Signal 6	Signal 6
7 Black	Signal 7	Signal 7
8 Violet	Signal 8	Signal 8
9 Grey-Pink	Signal 9	Signal 9
10 Red-Blue	Signal 10	Signal 10
A Blue	0 V	0 V
B Brown	+24 V	PE

Notes

Notes

Notes

Parker Worldwide

AE – UAE , Dubai Tel: +971 4 8875600 parker.me@parker.com	FR – France , Contamine s/Arve Tel: +33 (0)4 50 25 80 25 parker.france@parker.com	PT – Portugal , Leca da Palmeira Tel: +351 22 999 7360 parker.portugal@parker.com
AR – Argentina , Buenos Aires Tel: +54 3327 44 4129	GR – Greece , Athens Tel: +30 210 933 6450 parker.greece@parker.com	RO – Romania , Bucharest Tel: +40 21 252 1382 parker罗马尼亚@parker.com
AT – Austria , Wiener Neustadt Tel: +43 (0)2622 23501-0 parker.austria@parker.com	HK – Hong Kong Tel: +852 2428 8008	RU – Russia , Moscow Tel: +7 495 645-2156 parker.russia@parker.com
AT – Eastern Europe , Wiener Neustadt Tel: +43 (0)2622 23501 970 parker.easternEurope@parker.com	HU – Hungary , Budapest Tel: +36 1 220 4155 parker.hungary@parker.com	SE – Sweden , Spånga Tel: +46 (0)8 59 79 50 00 parker.sweden@parker.com
AU – Australia , Castle Hill Tel: +61 (0)2-9634 7777	IE – Ireland , Dublin Tel: +353 (0)1 466 6370 parker.ireland@parker.com	SG – Singapore Tel: +65 6887 6300
AZ – Azerbaijan , Baku Tel: +994 50 2233 458 parker.azerbaijan@parker.com	IN – India , Mumbai Tel: +91 22 6513 7081-85	SK – Slovakia , Banska Bystrica Tel: +421 484 162 252 parker.slovakia@parker.com
BE/LX – Belgium , Nivelles Tel: +32 (0)67 280 900 parker.belgium@parker.com	IT – Italy , Corsico (MI) Tel: +39 02 45 19 21 parker.italy@parker.com	SL – Slovenia , Novo Mesto Tel: +386 7 337 6650 parker.slovenia@parker.com
BR – Brazil , Cachoeirinha RS Tel: +55 51 3470 9144	JP – Japan , Fujisawa Tel: +(81) 4 6635 3050	TH – Thailand , Bangkok Tel: +662 717 8140
BY – Belarus , Minsk Tel: +375 17 209 9399 parker.belarus@parker.com	KR – South Korea , Seoul Tel: +82 2 559 0400	TR – Turkey , Istanbul Tel: +90 216 4997081 parker.turkey@parker.com
CA – Canada , Milton, Ontario Tel: +1 905 693 3000	KZ – Kazakhstan , Almaty Tel: +7 7272 505 800 parker.easternEurope@parker.com	TW – Taiwan , Taipei Tel: +886 2 2298 8987
CH – Switzerland , Etoy Tel: +41 (0) 21 821 02 30 parker.switzerland@parker.com	LV – Latvia , Riga Tel: +371 6 745 2601 parker.latvia@parker.com	UA – Ukraine , Kiev Tel: +380 44 494 2731 parker.ukraine@parker.com
CN – China , Shanghai Tel: +86 21 5031 2525	MX – Mexico , Apodaca Tel: +52 81 8156 6000	UK – United Kingdom , Warwick Tel: +44 (0)1926 317 878 parker.uk@parker.com
CZ – Czech Republic , Klicany Tel: +420 284 083 111 parker.czechrepublic@parker.com	MY – Malaysia , Subang Jaya Tel: +60 3 5638 1476	US – USA , Cleveland Tel: +1 216 896 3000
DE – Germany , Kaarst Tel: +49 (0)2131 4016 0 parker.germany@parker.com	NL – The Netherlands , Oldenzaal Tel: +31 (0)541 585 000 parker.nl@parker.com	VE – Venezuela , Caracas Tel: +58 212 238 5422
DK – Denmark , Ballerup Tel: +45 43 56 04 00 parker.denmark@parker.com	NO – Norway , Ski Tel: +47 64 91 10 00 parker.norway@parker.com	ZA – South Africa , Kempton Park Tel: +27 (0)11 961 0700 parker.southafrica@parker.com
ES – Spain , Madrid Tel: +34 902 33 00 01 parker.spain@parker.com	NZ – New Zealand , Mt Wellington Tel: +64 9 574 1744	
FI – Finland , Vantaa Tel: +358 (0)20 753 2500 parker.finland@parker.com	PL – Poland , Warsaw Tel: +48 (0)22 573 24 00 parker.poland@parker.com	

European Product Information Centre
Free phone: 00 800 27 27 5374
**(from AT, BE, CH, CZ, DE, DK, EE, EI, ES, FI,
FR, IT, NL, NO, PL, RU, SE, SK, UK, ZA)**

